
PyTeal

Mar 07, 2022

Getting Started

1	Overview	3
2	Install PyTeal	5
3	PyTeal Examples	7
4	Data Types and Constants	31
5	Arithmetic Operations	33
6	Byte Operators	37
7	Transaction Fields and Global Parameters	39
8	Cryptographic Primitives	47
9	Scratch Space	49
10	Loading Values from Group Transactions	51
11	Control Flow	53
12	State Access and Manipulation	61
13	Asset Information	67
14	TEAL Versions	71
15	PyTeal Package	73
16	Indices and tables	123
	Python Module Index	125
	Index	127

PyTeal is a Python language binding for [Algorand Smart Contracts \(ASC1s\)](#).

Algorand Smart Contracts are implemented using a new language that is stack-based, called [Transaction Execution Approval Language \(TEAL\)](#). This is a non-Turing complete language that allows branch forwards but prevents recursive logic to maximize safety and performance.

However, TEAL is essentially an assembly language. With PyTeal, developers can express smart contract logic purely using Python. PyTeal provides high level, functional programming style abstractions over TEAL and does type checking at construction time.

The [User Guide](#) describes many useful features in PyTeal, and the complete documentation for every expression and operation can be found in the [PyTeal Package API documentation](#).

PyTeal **hasn't been security audited**. Use it at your own risk.

CHAPTER 1

Overview

With PyTeal, developers can easily write **Algorand Smart Contracts (ASC1s)** in Python. PyTeal supports both stateless and statefull smart contracts.

Below is an example of writing a basic stateless smart contract that allows a specific receiver to withdraw funds from an account.

```
# This example is provided for informational purposes only and has not been audited,
↳ for security.

from pyteal import *

"""Basic Bank"""

def bank_for_account(receiver):
    """Only allow receiver to withdraw funds from this contract account.

    Args:
        receiver (str): Base 32 Algorand address of the receiver.
    """

    is_payment = Txn.type_enum() == TxnType.Payment
    is_single_tx = Global.group_size() == Int(1)
    is_correct_receiver = Txn.receiver() == Addr(receiver)
    no_close_out_addr = Txn.close_remainder_to() == Global.zero_address()
    no_rekey_addr = Txn.rekey_to() == Global.zero_address()
    acceptable_fee = Txn.fee() <= Int(1000)

    return And(
        is_payment,
        is_single_tx,
        is_correct_receiver,
        no_close_out_addr,
        no_rekey_addr,
```

(continues on next page)

(continued from previous page)

```
        acceptable_fee,
    )

if __name__ == "__main__":
    program = bank_for_account(
        "ZZAF5ARA4MEC5PVDOP64JM5O5MQST63Q2KOY2FLYFLXXD3PFSNJJBYPFZM"
    )
    print(compileTeal(program, mode=Mode.Signature, version=3))
```

As shown in this example, the logic of smart contract is expressed using PyTeal expressions constructed in Python. PyTeal overloads Python's arithmetic operators such as `<` and `==` (more overloaded operators can be found in [Arithmetic Operations](#)), allowing Python developers express smart contract logic more naturally.

Lastly, `compileTeal` is called to convert an PyTeal expression to a TEAL program, consisting of a sequence of TEAL opcodes. The output of the above example is:

```
#pragma version 3
txn TypeEnum
int pay
==
global GroupSize
int 1
==
&&
txn Receiver
addr ZZAF5ARA4MEC5PVDOP64JM5O5MQST63Q2KOY2FLYFLXXD3PFSNJJBYPFZM
==
&&
txn CloseRemainderTo
global ZeroAddress
==
&&
txn RekeyTo
global ZeroAddress
==
&&
txn Fee
int 1000
<=
&&
return
```


CHAPTER 2

Install PyTeal

The easiest way of installing PyTeal is using `pip` :

```
$ pip3 install pyteal
```

Alternatively, choose a [distribution file](#), and run

```
$ pip3 install [file name]
```


Here are some additional PyTeal example programs:

3.1 Signature Mode

3.1.1 Atomic Swap

Atomic Swap allows the transfer of Algos from a buyer to a seller in exchange for a good or service. This is done using a *Hashed Time Locked Contract*. In this scheme, the buyer funds a TEAL account with the sale price. The buyer also picks a secret value and encodes a secure hash of this value in the TEAL program. The TEAL program will transfer its balance to the seller if the seller is able to provide the secret value that corresponds to the hash in the program. When the seller renders the good or service to the buyer, the buyer discloses the secret from the program. The seller can immediately verify the secret and withdraw the payment.

```
# This example is provided for informational purposes only and has not been audited_
↪ for security.

from pyteal import *

"""Atomic Swap"""

alice = Addr("6ZHGHH5Z5CTPCF5WCESXMGRSVK7QJETR63M3NY5FJCUYDH057VTCMJOBGY")
bob = Addr("7Z5PWO2C6LFNQFGHWKSK5H47IQP5OJW2M3HA2QPXTY3WTNP5NU2MHBW27M")
secret = Bytes("base32", "2323232323232323")
timeout = 3000

def htlc(
    tmpl_seller=alice,
    tmpl_buyer=bob,
    tmpl_fee=1000,
    tmpl_secret=secret,
```

(continues on next page)

(continued from previous page)

```

    tmpl_hash_fn=Sha256,
    tmpl_timeout=timeout,
):

    fee_cond = Txn.fee() < Int(tmpl_fee)
    safety_cond = And(
        Txn.type_enum() == TxnType.Payment,
        Txn.close_remainder_to() == Global.zero_address(),
        Txn.rekey_to() == Global.zero_address(),
    )

    recv_cond = And(Txn.receiver() == tmpl_seller, tmpl_hash_fn(Arg(0)) == tmpl_
↪secret)

    esc_cond = And(Txn.receiver() == tmpl_buyer, Txn.first_valid() > Int(tmpl_
↪timeout))

    return And(fee_cond, safety_cond, Or(recv_cond, esc_cond))

if __name__ == "__main__":
    print(compileTeal(htlc(), mode=Mode.Signature, version=2))

```

3.1.2 Split Payment

Split Payment splits payment between `tmpl_rcv1` and `tmpl_rcv2` on the ratio of `tmpl_ratn` / `tmpl_ratd`.

```

# This example is provided for informational purposes only and has not been audited_
↪for security.

from pyteal import *

"""Split Payment"""

tmpl_fee = Int(1000)
tmpl_rcv1 = Addr("6ZHGH5Z5CTPCF5WCESXMGRSVK7QJETR63M3NY5FJCUYDHO57VTCMJOBGY")
tmpl_rcv2 = Addr("7Z5PWO2C6LFNQFGHWKSK5H47IQP5OJW2M3HA2QPXTY3WTNP5NU2MHBW27M")
tmpl_own = Addr("5MK5NGBRT5RL6IGUSYDIX5P7TNNZKRVXKT6FGVI6UVK6IZAWTYQGE4RZIQ")
tmpl_ratn = Int(1)
tmpl_ratd = Int(3)
tmpl_min_pay = Int(1000)
tmpl_timeout = Int(3000)

def split(
    tmpl_fee=tmpl_fee,
    tmpl_rcv1=tmpl_rcv1,
    tmpl_rcv2=tmpl_rcv2,
    tmpl_own=tmpl_own,
    tmpl_ratn=tmpl_ratn,
    tmpl_ratd=tmpl_ratd,
    tmpl_min_pay=tmpl_min_pay,
    tmpl_timeout=tmpl_timeout,
):

```

(continues on next page)

(continued from previous page)

```

split_core = And(
    Txn.type_enum() == TxnType.Payment,
    Txn.fee() < tmpl_fee,
    Txn.rekey_to() == Global.zero_address(),
)

split_transfer = And(
    Gtxn[0].sender() == Gtxn[1].sender(),
    Txn.close_remainder_to() == Global.zero_address(),
    Gtxn[0].receiver() == tmpl_rcv1,
    Gtxn[1].receiver() == tmpl_rcv2,
    Gtxn[0].amount()
    == ((Gtxn[0].amount() + Gtxn[1].amount()) * tmpl_ratn) / tmpl_ratd,
    Gtxn[0].amount() == tmpl_min_pay,
)

split_close = And(
    Txn.close_remainder_to() == tmpl_own,
    Txn.receiver() == Global.zero_address(),
    Txn.amount() == Int(0),
    Txn.first_valid() > tmpl_timeout,
)

split_program = And(
    split_core, If(Global.group_size() == Int(2), split_transfer, split_close)
)

return split_program

if __name__ == "__main__":
    print(compileTeal(split(), mode=Mode.Signature, version=2))

```

3.1.3 Periodic Payment

Periodic Payment allows some account to execute periodic withdrawal of funds. This PyTeal program creates an contract account that allows `tmpl_rcv` to withdraw `tmpl_amt` every `tmpl_period` rounds for `tmpl_dur` after every multiple of `tmpl_period`.

After `tmpl_timeout`, all remaining funds in the escrow are available to `tmpl_rcv`.

```

# This example is provided for informational purposes only and has not been audited_
↳ for security.

from pyteal import *

"""Periodic Payment"""

tmpl_fee = Int(1000)
tmpl_period = Int(50)
tmpl_dur = Int(5000)
tmpl_lease = Bytes("base64", "023sdDE2")
tmpl_amt = Int(2000)
tmpl_rcv = Addr("6ZHGHH5Z5CTPCF5WCESXMGRSVK7QJETR63M3NY5FJCUYDHO57VTCMJOBGY")
tmpl_timeout = Int(30000)

```

(continues on next page)

```

def periodic_payment(
    tmpl_fee=tmpl_fee,
    tmpl_period=tmpl_period,
    tmpl_dur=tmpl_dur,
    tmpl_lease=tmpl_lease,
    tmpl_amt=tmpl_amt,
    tmpl_rcv=tmpl_rcv,
    tmpl_timeout=tmpl_timeout,
):
    periodic_pay_core = And(
        Txn.type_enum() == TxnType.Payment,
        Txn.fee() < tmpl_fee,
        Txn.first_valid() % tmpl_period == Int(0),
        Txn.last_valid() == tmpl_dur + Txn.first_valid(),
        Txn.lease() == tmpl_lease,
    )

    periodic_pay_transfer = And(
        Txn.close_remainder_to() == Global.zero_address(),
        Txn.rekey_to() == Global.zero_address(),
        Txn.receiver() == tmpl_rcv,
        Txn.amount() == tmpl_amt,
    )

    periodic_pay_close = And(
        Txn.close_remainder_to() == tmpl_rcv,
        Txn.rekey_to() == Global.zero_address(),
        Txn.receiver() == Global.zero_address(),
        Txn.first_valid() == tmpl_timeout,
        Txn.amount() == Int(0),
    )

    periodic_pay_escrow = periodic_pay_core.And(
        periodic_pay_transfer.Or(periodic_pay_close)
    )

    return periodic_pay_escrow

if __name__ == "__main__":
    print(compileTeal(periodic_payment(), mode=Mode.Signature, version=2))

```

3.2 Application Mode

3.2.1 Voting

Voting allows accounts to register and vote for arbitrary choices. Here a *choice* is any byte slice and anyone is allowed to register to vote.

This example has a configurable *registration period* defined by the global state `RegBegin` and `RegEnd` which restrict when accounts can register to vote. There is also a separate configurable *voting period* defined by the global

state `VotingBegin` and `VotingEnd` which restrict when voting can take place.

An account must register in order to vote. Accounts cannot vote more than once, and if an account opts out of the application before the voting period has concluded, their vote is discarded. The results are visible in the global state of the application, and the winner is the candidate with the highest number of votes.

```
# This example is provided for informational purposes only and has not been audited,
↳ for security.

from pyteal import *

def approval_program():
    on_creation = Seq(
        [
            App.globalPut(Bytes("Creator"), Txn.sender()),
            Assert(Txn.application_args.length() == Int(4)),
            App.globalPut(Bytes("RegBegin"), Btoi(Txn.application_args[0])),
            App.globalPut(Bytes("RegEnd"), Btoi(Txn.application_args[1])),
            App.globalPut(Bytes("VoteBegin"), Btoi(Txn.application_args[2])),
            App.globalPut(Bytes("VoteEnd"), Btoi(Txn.application_args[3])),
            Return(Int(1)),
        ]
    )

    is_creator = Txn.sender() == App.globalGet(Bytes("Creator"))

    get_vote_of_sender = App.localGetEx(Int(0), App.id(), Bytes("voted"))

    on_closeout = Seq(
        [
            get_vote_of_sender,
            If(
                And(
                    Global.round() <= App.globalGet(Bytes("VoteEnd")),
                    get_vote_of_sender.hasValue(),
                ),
                App.globalPut(
                    get_vote_of_sender.value(),
                    App.globalGet(get_vote_of_sender.value()) - Int(1),
                ),
            ),
            Return(Int(1)),
        ]
    )

    on_register = Return(
        And(
            Global.round() >= App.globalGet(Bytes("RegBegin")),
            Global.round() <= App.globalGet(Bytes("RegEnd")),
        )
    )

    choice = Txn.application_args[1]
    choice_tally = App.globalGet(choice)
    on_vote = Seq(
        [
            Assert(
```

(continues on next page)

(continued from previous page)

```

        And(
            Global.round() >= App.globalGet(Bytes("VoteBegin")),
            Global.round() <= App.globalGet(Bytes("VoteEnd")),
        )
    ),
    get_vote_of_sender,
    If(get_vote_of_sender.hasValue(), Return(Int(0))),
    App.globalPut(choice, choice_tally + Int(1)),
    App.localPut(Int(0), Bytes("voted"), choice),
    Return(Int(1)),
]
)

program = Cond(
    [Txn.application_id() == Int(0), on_creation],
    [Txn.on_completion() == OnComplete.DeleteApplication, Return(is_creator)],
    [Txn.on_completion() == OnComplete.UpdateApplication, Return(is_creator)],
    [Txn.on_completion() == OnComplete.CloseOut, on_closeout],
    [Txn.on_completion() == OnComplete.OptIn, on_register],
    [Txn.application_args[0] == Bytes("vote"), on_vote],
)

return program

def clear_state_program():
    get_vote_of_sender = App.localGetEx(Int(0), App.id(), Bytes("voted"))
    program = Seq(
        [
            get_vote_of_sender,
            If(
                And(
                    Global.round() <= App.globalGet(Bytes("VoteEnd")),
                    get_vote_of_sender.hasValue(),
                ),
                App.globalPut(
                    get_vote_of_sender.value(),
                    App.globalGet(get_vote_of_sender.value()) - Int(1),
                ),
            ),
            Return(Int(1)),
        ]
    )

    return program

if __name__ == "__main__":
    with open("vote_approval.teal", "w") as f:
        compiled = compileTeal(approval_program(), mode=Mode.Application, version=2)
        f.write(compiled)

    with open("vote_clear_state.teal", "w") as f:
        compiled = compileTeal(clear_state_program(), mode=Mode.Application,
↪version=2)
        f.write(compiled)

```


A reference script that deploys the voting application is below:

```
# based off https://github.com/algorand/docs/blob/
↪cdf11d48a4b1168752e6ccaf77c8b9e8e599713a/examples/smart_contracts/v2/python/
↪stateful_smart_contracts.py

import base64
import datetime

from algosdk.future import transaction
from algosdk import account, mnemonic
from algosdk.v2client import algod
from pyteal import compileTeal, Mode
from vote import approval_program, clear_state_program

# user declared account mnemonics
creator_mnemonic = "Your 25-word mnemonic goes here"
user_mnemonic = "A second distinct 25-word mnemonic goes here"

# user declared algod connection parameters. Node must have EnableDeveloperAPI set to_
↪true in its config
algod_address = "http://localhost:4001"
algod_token = "aaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaa"

# helper function to compile program source
def compile_program(client, source_code):
    compile_response = client.compile(source_code)
    return base64.b64decode(compile_response["result"])

# helper function that converts a mnemonic passphrase into a private signing key
def get_private_key_from_mnemonic(mn):
    private_key = mnemonic.to_private_key(mn)
    return private_key

# helper function that waits for a given txid to be confirmed by the network
def wait_for_confirmation(client, txid):
    last_round = client.status().get("last-round")
    txinfo = client.pending_transaction_info(txid)
    while not (txinfo.get("confirmed-round") and txinfo.get("confirmed-round") > 0):
        print("Waiting for confirmation...")
        last_round += 1
        client.status_after_block(last_round)
        txinfo = client.pending_transaction_info(txid)
    print(
        "Transaction {} confirmed in round {}".format(
            txid, txinfo.get("confirmed-round")
        )
    )
    return txinfo

def wait_for_round(client, round):
    last_round = client.status().get("last-round")
    print(f"Waiting for round {round}")
    while last_round < round:
        last_round += 1
```

(continues on next page)

(continued from previous page)

```

        client.status_after_block(last_round)
        print(f"Round {last_round}")

# create new application
def create_app(
    client,
    private_key,
    approval_program,
    clear_program,
    global_schema,
    local_schema,
    app_args,
):
    # define sender as creator
    sender = account.address_from_private_key(private_key)

    # declare on_complete as NoOp
    on_complete = transaction.OnComplete.NoOpOC.real

    # get node suggested parameters
    params = client.suggested_params()
    # comment out the next two (2) lines to use suggested fees
    params.flat_fee = True
    params.fee = 1000

    # create unsigned transaction
    txn = transaction.ApplicationCreateTxn(
        sender,
        params,
        on_complete,
        approval_program,
        clear_program,
        global_schema,
        local_schema,
        app_args,
    )

    # sign transaction
    signed_txn = txn.sign(private_key)
    tx_id = signed_txn.transaction.get_txid()

    # send transaction
    client.send_transactions([signed_txn])

    # await confirmation
    wait_for_confirmation(client, tx_id)

    # display results
    transaction_response = client.pending_transaction_info(tx_id)
    app_id = transaction_response["application-index"]
    print("Created new app-id:", app_id)

    return app_id

# opt-in to application

```

(continues on next page)

(continued from previous page)

```

def opt_in_app(client, private_key, index):
    # declare sender
    sender = account.address_from_private_key(private_key)
    print("OptIn from account: ", sender)

    # get node suggested parameters
    params = client.suggested_params()
    # comment out the next two (2) lines to use suggested fees
    params.flat_fee = True
    params.fee = 1000

    # create unsigned transaction
    txn = transaction.ApplicationOptInTxn(sender, params, index)

    # sign transaction
    signed_txn = txn.sign(private_key)
    tx_id = signed_txn.transaction.get_txid()

    # send transaction
    client.send_transactions([signed_txn])

    # await confirmation
    wait_for_confirmation(client, tx_id)

    # display results
    transaction_response = client.pending_transaction_info(tx_id)
    print("OptIn to app-id:", transaction_response["txn"]["txn"]["apid"])

# call application
def call_app(client, private_key, index, app_args):
    # declare sender
    sender = account.address_from_private_key(private_key)
    print("Call from account:", sender)

    # get node suggested parameters
    params = client.suggested_params()
    # comment out the next two (2) lines to use suggested fees
    params.flat_fee = True
    params.fee = 1000

    # create unsigned transaction
    txn = transaction.ApplicationNoOpTxn(sender, params, index, app_args)

    # sign transaction
    signed_txn = txn.sign(private_key)
    tx_id = signed_txn.transaction.get_txid()

    # send transaction
    client.send_transactions([signed_txn])

    # await confirmation
    wait_for_confirmation(client, tx_id)

def format_state(state):
    formatted = {}

```

(continues on next page)

(continued from previous page)

```

    for item in state:
        key = item["key"]
        value = item["value"]
        formatted_key = base64.b64decode(key).decode("utf-8")
        if value["type"] == 1:
            # byte string
            if formatted_key == "voted":
                formatted_value = base64.b64decode(value["bytes"]).decode("utf-8")
            else:
                formatted_value = value["bytes"]
            formatted[formatted_key] = formatted_value
        else:
            # integer
            formatted[formatted_key] = value["uint"]
    return formatted

# read user local state
def read_local_state(client, addr, app_id):
    results = client.account_info(addr)
    for local_state in results["apps-local-state"]:
        if local_state["id"] == app_id:
            if "key-value" not in local_state:
                return {}
            return format_state(local_state["key-value"])
    return {}

# read app global state
def read_global_state(client, addr, app_id):
    results = client.account_info(addr)
    apps_created = results["created-apps"]
    for app in apps_created:
        if app["id"] == app_id:
            return format_state(app["params"]["global-state"])
    return {}

# delete application
def delete_app(client, private_key, index):
    # declare sender
    sender = account.address_from_private_key(private_key)

    # get node suggested parameters
    params = client.suggested_params()
    # comment out the next two (2) lines to use suggested fees
    params.flat_fee = True
    params.fee = 1000

    # create unsigned transaction
    txn = transaction.ApplicationDeleteTxn(sender, params, index)

    # sign transaction
    signed_txn = txn.sign(private_key)
    tx_id = signed_txn.transaction.get_txid()

    # send transaction

```

(continues on next page)

(continued from previous page)

```

client.send_transactions([signed_txn])

# await confirmation
wait_for_confirmation(client, tx_id)

# display results
transaction_response = client.pending_transaction_info(tx_id)
print("Deleted app-id:", transaction_response["txn"]["txn"]["apid"])

# close out from application
def close_out_app(client, private_key, index):
    # declare sender
    sender = account.address_from_private_key(private_key)

    # get node suggested parameters
    params = client.suggested_params()
    # comment out the next two (2) lines to use suggested fees
    params.flat_fee = True
    params.fee = 1000

    # create unsigned transaction
    txn = transaction.ApplicationCloseOutTxn(sender, params, index)

    # sign transaction
    signed_txn = txn.sign(private_key)
    tx_id = signed_txn.transaction.get_txid()

    # send transaction
    client.send_transactions([signed_txn])

    # await confirmation
    wait_for_confirmation(client, tx_id)

    # display results
    transaction_response = client.pending_transaction_info(tx_id)
    print("Closed out from app-id: ", transaction_response["txn"]["txn"]["apid"])

# clear application
def clear_app(client, private_key, index):
    # declare sender
    sender = account.address_from_private_key(private_key)

    # get node suggested parameters
    params = client.suggested_params()
    # comment out the next two (2) lines to use suggested fees
    params.flat_fee = True
    params.fee = 1000

    # create unsigned transaction
    txn = transaction.ApplicationClearStateTxn(sender, params, index)

    # sign transaction
    signed_txn = txn.sign(private_key)
    tx_id = signed_txn.transaction.get_txid()

```

(continues on next page)

(continued from previous page)

```

# send transaction
client.send_transactions([signed_txn])

# await confirmation
wait_for_confirmation(client, tx_id)

# display results
transaction_response = client.pending_transaction_info(tx_id)
print("Cleared app-id:", transaction_response["txn"]["txn"]["apid"])

# convert 64 bit integer i to byte string
def intToBytes(i):
    return i.to_bytes(8, "big")

def main():
    # initialize an algodClient
    algod_client = algod.AlgodClient(algod_token, algod_address)

    # define private keys
    creator_private_key = get_private_key_from_mnemonic(creator_mnemonic)
    user_private_key = get_private_key_from_mnemonic(user_mnemonic)

    # declare application state storage (immutable)
    local_ints = 0
    local_bytes = 1
    global_ints = (
        24 # 4 for setup + 20 for choices. Use a larger number for more choices.
    )
    global_bytes = 1
    global_schema = transaction.StateSchema(global_ints, global_bytes)
    local_schema = transaction.StateSchema(local_ints, local_bytes)

    # get PyTeal approval program
    approval_program_ast = approval_program()
    # compile program to TEAL assembly
    approval_program_teal = compileTeal(
        approval_program_ast, mode=Mode.Application, version=2
    )
    # compile program to binary
    approval_program_compiled = compile_program(algod_client, approval_program_teal)

    # get PyTeal clear state program
    clear_state_program_ast = clear_state_program()
    # compile program to TEAL assembly
    clear_state_program_teal = compileTeal(
        clear_state_program_ast, mode=Mode.Application, version=2
    )
    # compile program to binary
    clear_state_program_compiled = compile_program(
        algod_client, clear_state_program_teal
    )

    # configure registration and voting period
    status = algod_client.status()
    regBegin = status["last-round"] + 10

```

(continues on next page)

(continued from previous page)

```

regEnd = regBegin + 10
voteBegin = regEnd + 1
voteEnd = voteBegin + 10

print(f"Registration rounds: {regBegin} to {regEnd}")
print(f"Vote rounds: {voteBegin} to {voteEnd}")

# create list of bytes for app args
app_args = [
    intToBytes(regBegin),
    intToBytes(regEnd),
    intToBytes(voteBegin),
    intToBytes(voteEnd),
]

# create new application
app_id = create_app(
    algod_client,
    creator_private_key,
    approval_program_compiled,
    clear_state_program_compiled,
    global_schema,
    local_schema,
    app_args,
)

# read global state of application
print(
    "Global state:",
    read_global_state(
        algod_client, account.address_from_private_key(creator_private_key), app_
↪id
    ),
)

# wait for registration period to start
wait_for_round(algod_client, regBegin)

# opt-in to application
opt_in_app(algod_client, user_private_key, app_id)

wait_for_round(algod_client, voteBegin)

# call application without arguments
call_app(algod_client, user_private_key, app_id, [b"vote", b"choiceA"])

# read local state of application from user account
print(
    "Local state:",
    read_local_state(
        algod_client, account.address_from_private_key(user_private_key), app_id
    ),
)

# wait for registration period to start
wait_for_round(algod_client, voteEnd)

```

(continues on next page)

(continued from previous page)

```

# read global state of application
global_state = read_global_state(
    algod_client, account.address_from_private_key(creator_private_key), app_id
)
print("Global state:", global_state)

max_votes = 0
max_votes_choice = None
for key, value in global_state.items():
    if (
        key
        not in (
            "RegBegin",
            "RegEnd",
            "VoteBegin",
            "VoteEnd",
            "Creator",
        )
        and isinstance(value, int)
    ):
        if value > max_votes:
            max_votes = value
            max_votes_choice = key

print("The winner is:", max_votes_choice)

# delete application
delete_app(algod_client, creator_private_key, app_id)

# clear application from user account
clear_app(algod_client, user_private_key, app_id)

if __name__ == "__main__":
    main()

```

Example output for deployment would be:

```

Registration rounds: 592 to 602
Vote rounds: 603 to 613
Waiting for confirmation...
Transaction KXJHR6J4QSCAH036L77DPJ53CLZBCCSPSBAOGTGQDRA7WECDXUEA confirmed in round_
↳ 584.
Created new app-id: 29
Global state: {'RegEnd': 602, 'VoteBegin': 603, 'VoteEnd': 613, 'Creator':
↳ '49y8gDrKSnm77cgRyFzYdlkw18SDVnKhhoiS6NVVH8U=', 'RegBegin': 592}
Waiting for round 592
Round 585
Round 586
Round 587
Round 588
Round 589
Round 590
Round 591
Round 592
OptIn from account: FVQEFNOSD25TDBTTTIU2I5KW5DHR6PADYMZESTOCQ2O3ME4OWXEI7OHVRY
Waiting for confirmation...

```

(continues on next page)

(continued from previous page)

```

Transaction YWXOAREFSUYID6QLWQHANTXK3NR2XOVTIQYKMD27F3VXJKP7CMYQ confirmed in round_
↳595.
OptIn to app-id: 29
Waiting for round 603
Round 596
Round 597
Round 598
Round 599
Round 600
Round 601
Round 602
Round 603
Call from account: FVQEFNOSD25TDBTTIU2I5KW5DHR6PADYMZESTOCQ2O3ME4OWXEI7OHVRY
Waiting for confirmation...
Transaction WNV4DTPEMVGUXNRZHMWNSCUU7AQJOCFTBKJT6NV2KN6THT4QGKNQ confirmed in round_
↳606.
Local state: {'voted': 'choiceA'}
Waiting for round 613
Round 607
Round 608
Round 609
Round 610
Round 611
Round 612
Round 613
Global state: {'RegBegin': 592, 'RegEnd': 602, 'VoteBegin': 603, 'VoteEnd': 613,
↳'choiceA': 1, 'Creator': '49y8gDrKSnm77cgRyFzYdlkw18SDVnKhhoiS6NVVH8U='}
The winner is: choiceA
Waiting for confirmation...
Transaction 535KBWJ7RQX4ISV763IUUICQWI6VERYBJ7J6X7HPMAMFNKJPSNPQ confirmed in round_
↳616.
Deleted app-id: 29
Waiting for confirmation...
Transaction Z56HDAJYARUC4PWGWQLCBA6TZYQOOLNOXY5XRM3IYUEEUCT5DRMA confirmed in round_
↳618.
Cleared app-id: 29

```

3.2.2 Asset

Asset is an implementation of a custom asset type using smart contracts. While Algorand has *ASAs*, in some blockchains the only way to create a custom asset is through smart contracts.

At creation, the creator specifies the total supply of the asset. Initially this supply is placed in a reserve and the creator is made an admin. Any admin can move funds from the reserve into the balance of any account that has opted into the application using the *mint* argument. Additionally, any admin can move funds from any account's balance into the reserve using the *burn* argument.

Accounts are free to transfer funds in their balance to any other account that has opted into the application. When an account opts out of the application, their balance is added to the reserve.

```

# This example is provided for informational purposes only and has not been audited_
↳for security.

from pyteal import *

```

(continues on next page)

(continued from previous page)

```

def approval_program():
    on_creation = Seq(
        [
            Assert(Txn.application_args.length() == Int(1)),
            App.globalPut(Bytes("total supply"), Btoi(Txn.application_args[0])),
            App.globalPut(Bytes("reserve"), Btoi(Txn.application_args[0])),
            App.localPut(Int(0), Bytes("admin"), Int(1)),
            App.localPut(Int(0), Bytes("balance"), Int(0)),
            Return(Int(1)),
        ]
    )

    is_admin = App.localGet(Int(0), Bytes("admin"))

    on_closeout = Seq(
        [
            App.globalPut(
                Bytes("reserve"),
                App.globalGet(Bytes("reserve"))
                + App.localGet(Int(0), Bytes("balance")),
            ),
            Return(Int(1)),
        ]
    )

    register = Seq([App.localPut(Int(0), Bytes("balance"), Int(0)), Return(Int(1))])

    # configure the admin status of the account Txn.accounts[1]
    # sender must be admin
    new_admin_status = Btoi(Txn.application_args[1])
    set_admin = Seq(
        [
            Assert(And(is_admin, Txn.application_args.length() == Int(2))),
            App.localPut(Int(1), Bytes("admin"), new_admin_status),
            Return(Int(1)),
        ]
    )
    # NOTE: The above set_admin code is carefully constructed. If instead we used the
    ↪ following code:
    # Seq([
    #     Assert(Txn.application_args.length() == Int(2)),
    #     App.localPut(Int(1), Bytes("admin"), new_admin_status),
    #     Return(is_admin)
    # ])
    # It would be vulnerable to the following attack: a sender passes in their own
    ↪ address as
    # Txn.accounts[1], so then the line App.localPut(Int(1), Bytes("admin"), new_
    ↪ admin_status)
    # changes the sender's admin status, meaning the final Return(is_admin) can
    ↪ return anything the
    # sender wants. This allows anyone to become an admin!

    # move assets from the reserve to Txn.accounts[1]
    # sender must be admin
    mint_amount = Btoi(Txn.application_args[1])
    mint = Seq(

```

(continues on next page)

(continued from previous page)

```

    [
        Assert(Txn.application_args.length() == Int(2)),
        Assert(mint_amount <= App.globalGet(Bytes("reserve"))),
        App.globalPut(
            Bytes("reserve"), App.globalGet(Bytes("reserve")) - mint_amount
        ),
        App.localPut(
            Int(1),
            Bytes("balance"),
            App.localGet(Int(1), Bytes("balance")) + mint_amount,
        ),
        Return(is_admin),
    ]
)

# transfer assets from the sender to Txn.accounts[1]
transfer_amount = Btoi(Txn.application_args[1])
transfer = Seq(
    [
        Assert(Txn.application_args.length() == Int(2)),
        Assert(transfer_amount <= App.localGet(Int(0), Bytes("balance"))),
        App.localPut(
            Int(0),
            Bytes("balance"),
            App.localGet(Int(0), Bytes("balance")) - transfer_amount,
        ),
        App.localPut(
            Int(1),
            Bytes("balance"),
            App.localGet(Int(1), Bytes("balance")) + transfer_amount,
        ),
        Return(Int(1)),
    ]
)

program = Cond(
    [Txn.application_id() == Int(0), on_creation],
    [Txn.on_completion() == OnComplete.DeleteApplication, Return(is_admin)],
    [Txn.on_completion() == OnComplete.UpdateApplication, Return(is_admin)],
    [Txn.on_completion() == OnComplete.CloseOut, on_closeout],
    [Txn.on_completion() == OnComplete.OptIn, register],
    [Txn.application_args[0] == Bytes("set admin"), set_admin],
    [Txn.application_args[0] == Bytes("mint"), mint],
    [Txn.application_args[0] == Bytes("transfer"), transfer],
)

return program

def clear_state_program():
    program = Seq(
        [
            App.globalPut(
                Bytes("reserve"),
                App.globalGet(Bytes("reserve"))
                + App.localGet(Int(0), Bytes("balance")),
            ),

```

(continues on next page)

(continued from previous page)

```

        Return(Int(1)),
    ]
)

return program

if __name__ == "__main__":
    with open("asset_approval.teal", "w") as f:
        compiled = compileTeal(approval_program(), mode=Mode.Application, version=2)
        f.write(compiled)

    with open("asset_clear_state.teal", "w") as f:
        compiled = compileTeal(clear_state_program(), mode=Mode.Application,
↪version=2)
        f.write(compiled)

```

3.2.3 Security Token

Security Token is an extension of the *Asset* example with more features and restrictions. There are two types of admins, *contract admins* and *transfer admins*.

Contract admins can delete the smart contract if the entire supply is in the reserve. They can promote accounts to transfer or contract admins. They can also *mint* and *burn* funds.

Transfer admins can impose maximum balance limitations on accounts, temporarily lock accounts, assign accounts to transfer groups, and impose transaction restrictions between transaction groups.

Both contract and transfer admins can pause trading of funds and freeze individual accounts.

Accounts can only transfer funds if trading is not paused, both the sender and receive accounts are not frozen or temporarily locked, transfer group restrictions are not in place between them, and the receiver's account does not have a maximum balance restriction that would be invalidated.

```

# This example is provided for informational purposes only and has not been audited_
↪for security.

from pyteal import *

def approval_program():
    on_creation = Seq(
        [
            Assert(Txn.application_args.length() == Int(1)),
            App.globalPut(Bytes("total supply"), Btoi(Txn.application_args[0])),
            App.globalPut(Bytes("reserve"), Btoi(Txn.application_args[0])),
            App.globalPut(Bytes("paused"), Int(0)),
            App.localPut(Int(0), Bytes("contract admin"), Int(1)),
            App.localPut(Int(0), Bytes("transfer admin"), Int(1)),
            App.localPut(Int(0), Bytes("balance"), Int(0)),
            Return(Int(1)),
        ]
    )

    is_contract_admin = App.localGet(Int(0), Bytes("contract admin"))
    is_transfer_admin = App.localGet(Int(0), Bytes("transfer admin"))

```

(continues on next page)

(continued from previous page)

```

is_any_admin = is_contract_admin.Or(is_transfer_admin)

can_delete = And(
    is_contract_admin,
    App.globalGet(Bytes("total supply")) == App.globalGet(Bytes("reserve")),
)

on_closeout = Seq(
    [
        App.globalPut(
            Bytes("reserve"),
            App.globalGet(Bytes("reserve"))
            + App.localGet(Int(0), Bytes("balance")),
        ),
        Return(Int(1)),
    ]
)

register = Seq([App.localPut(Int(0), Bytes("balance"), Int(0)), Return(Int(1))])

# pause all transfers
# sender must be any admin
new_pause_value = Btoi(Txn.application_args[1])
pause = Seq(
    [
        Assert(Txn.application_args.length() == Int(2)),
        App.globalPut(Bytes("paused"), new_pause_value),
        Return(is_any_admin),
    ]
)

# configure the admin status of the account Txn.accounts[1]
# sender must be contract admin
new_admin_type = Txn.application_args[1]
new_admin_status = Btoi(Txn.application_args[2])
set_admin = Seq(
    [
        Assert(
            And(
                is_contract_admin,
                Txn.application_args.length() == Int(3),
                Or(
                    new_admin_type == Bytes("contract admin"),
                    new_admin_type == Bytes("transfer admin"),
                ),
                Txn.accounts.length() == Int(1),
            )
        ),
        App.localPut(Int(1), new_admin_type, new_admin_status),
        Return(Int(1)),
    ]
)

# NOTE: The above set_admin code is carefully constructed. If instead we used the
following code:
# Seq([
#     Assert(And(
#         Txn.application_args.length() == Int(3),

```

(continues on next page)

(continued from previous page)

```

#         Or(new_admin_type == Bytes("contract admin"), new_admin_type == Bytes(
↪ "transfer admin")),
#         Txn.accounts.length() == Int(1)
#     )),
#     App.localPut(Int(1), new_admin_type, new_admin_status),
#     Return(is_contract_admin)
# ])
# It would be vulnerable to the following attack: a sender passes in their own_
↪ address as
# Txn.accounts[1], so then the line App.localPut(Int(1), new_admin_type, new_
↪ admin_status)
# changes the sender's admin status, meaning the final Return(is_contract_admin)_
↪ can return
# anything the sender wants. This allows anyone to become an admin!

# freeze Txn.accounts[1]
# sender must be any admin
new_freeze_value = Btoi(Txn.application_args[1])
freeze = Seq(
    [
        Assert(
            And(
                Txn.application_args.length() == Int(2),
                Txn.accounts.length() == Int(1),
            )
        ),
        App.localPut(Int(1), Bytes("frozen"), new_freeze_value),
        Return(is_any_admin),
    ]
)

# modify the max balance of Txn.accounts[1]
# if max_balance_value is 0, will delete the existing max balance limitation on_
↪ the account
# sender must be transfer admin
max_balance_value = Btoi(Txn.application_args[1])
max_balance = Seq(
    [
        Assert(
            And(
                Txn.application_args.length() == Int(2),
                Txn.accounts.length() == Int(1),
            )
        ),
        If(
            max_balance_value == Int(0),
            App.localDel(Int(1), Bytes("max balance")),
            App.localPut(Int(1), Bytes("max balance"), max_balance_value),
        ),
        Return(is_transfer_admin),
    ]
)

# lock Txn.accounts[1] until a UNIX timestamp
# sender must be transfer admin
lock_until_value = Btoi(Txn.application_args[1])
lock_until = Seq(

```

(continues on next page)

(continued from previous page)

```

    [
        Assert(
            And(
                Txn.application_args.length() == Int(2),
                Txn.accounts.length() == Int(1),
            )
        ),
        If(
            lock_until_value == Int(0),
            App.localDel(Int(1), Bytes("lock until")),
            App.localPut(Int(1), Bytes("lock until"), lock_until_value),
        ),
        Return(is_transfer_admin),
    ]
)

set_transfer_group = Seq(
    [
        Assert(
            And(
                Txn.application_args.length() == Int(3),
                Txn.accounts.length() == Int(1),
            )
        ),
        App.localPut(
            Int(1), Bytes("transfer group"), Btoi(Txn.application_args[2])
        ),
    ]
)

def getRuleKey(sendGroup, receiveGroup):
    return Concat(Bytes("rule"), Itob(sendGroup), Itob(receiveGroup))

lock_transfer_key = getRuleKey(
    Btoi(Txn.application_args[2]), Btoi(Txn.application_args[3])
)
lock_transfer_until = Btoi(Txn.application_args[4])
lock_transfer_group = Seq(
    [
        Assert(Txn.application_args.length() == Int(5)),
        If(
            lock_transfer_until == Int(0),
            App.globalDel(lock_transfer_key),
            App.globalPut(lock_transfer_key, lock_transfer_until),
        ),
    ]
)

# sender must be transfer admin
transfer_group = Seq(
    [
        Assert(Txn.application_args.length() > Int(2)),
        Cond(
            [Txn.application_args[1] == Bytes("set"), set_transfer_group],
            [Txn.application_args[1] == Bytes("lock"), lock_transfer_group],
        ),
        Return(is_transfer_admin),
    ]
)

```

(continues on next page)

(continued from previous page)

```

    ]
)

# move assets from the reserve to Txn.accounts[1]
# sender must be contract admin
mint_amount = Btoi(Txn.application_args[1])
mint = Seq(
    [
        Assert(
            And(
                Txn.application_args.length() == Int(2),
                Txn.accounts.length() == Int(1),
                mint_amount <= App.globalGet(Bytes("reserve")),
            )
        ),
        App.globalPut(
            Bytes("reserve"), App.globalGet(Bytes("reserve")) - mint_amount
        ),
        App.localPut(
            Int(1),
            Bytes("balance"),
            App.localGet(Int(1), Bytes("balance")) + mint_amount,
        ),
        Return(is_contract_admin),
    ]
)

# move assets from Txn.accounts[1] to the reserve
# sender must be contract admin
burn_amount = Btoi(Txn.application_args[1])
burn = Seq(
    [
        Assert(
            And(
                Txn.application_args.length() == Int(2),
                Txn.accounts.length() == Int(1),
                burn_amount <= App.localGet(Int(1), Bytes("balance")),
            )
        ),
        App.globalPut(
            Bytes("reserve"), App.globalGet(Bytes("reserve")) + burn_amount
        ),
        App.localPut(
            Int(1),
            Bytes("balance"),
            App.localGet(Int(1), Bytes("balance")) - burn_amount,
        ),
        Return(is_contract_admin),
    ]
)

# transfer assets from the sender to Txn.accounts[1]
transfer_amount = Btoi(Txn.application_args[1])
receiver_max_balance = App.localGetEx(Int(1), App.id(), Bytes("max balance"))
transfer = Seq(
    [
        Assert(

```

(continues on next page)

(continued from previous page)

```

        And(
            Txn.application_args.length() == Int(2),
            Txn.accounts.length() == Int(1),
            transfer_amount <= App.localGet(Int(0), Bytes("balance")),
        )
    ),
    receiver_max_balance,
    If(
        Or(
            App.globalGet(Bytes("paused")),
            App.localGet(Int(0), Bytes("frozen")),
            App.localGet(Int(1), Bytes("frozen")),
            App.localGet(Int(0), Bytes("lock until"))
            >= Global.latest_timestamp(),
            App.localGet(Int(1), Bytes("lock until"))
            >= Global.latest_timestamp(),
            App.globalGet(
                getRuleKey(
                    App.localGet(Int(0), Bytes("transfer group")),
                    App.localGet(Int(1), Bytes("transfer group")),
                )
            )
            >= Global.latest_timestamp(),
            And(
                receiver_max_balance.hasValue(),
                receiver_max_balance.value()
                < App.localGet(Int(1), Bytes("balance")) + transfer_amount,
            ),
        ),
        Return(Int(0)),
    ),
    App.localPut(
        Int(0),
        Bytes("balance"),
        App.localGet(Int(0), Bytes("balance")) - transfer_amount,
    ),
    App.localPut(
        Int(1),
        Bytes("balance"),
        App.localGet(Int(1), Bytes("balance")) + transfer_amount,
    ),
    Return(Int(1)),
]
)

program = Cond(
    [Txn.application_id() == Int(0), on_creation],
    [Txn.on_completion() == OnComplete.DeleteApplication, Return(can_delete)],
    [
        Txn.on_completion() == OnComplete.UpdateApplication,
        Return(is_contract_admin),
    ],
    [Txn.on_completion() == OnComplete.CloseOut, on_closeout],
    [Txn.on_completion() == OnComplete.OptIn, register],
    [Txn.application_args[0] == Bytes("pause"), pause],
    [Txn.application_args[0] == Bytes("set admin"), set_admin],
    [Txn.application_args[0] == Bytes("freeze"), freeze],

```

(continues on next page)

(continued from previous page)

```

        [Txn.application_args[0] == Bytes("max balance"), max_balance],
        [Txn.application_args[0] == Bytes("lock until"), lock_until],
        [Txn.application_args[0] == Bytes("transfer group"), transfer_group],
        [Txn.application_args[0] == Bytes("mint"), mint],
        [Txn.application_args[0] == Bytes("burn"), burn],
        [Txn.application_args[0] == Bytes("transfer"), transfer],
    )

    return program

def clear_state_program():
    program = Seq(
        [
            App.globalPut(
                Bytes("reserve"),
                App.globalGet(Bytes("reserve"))
                + App.localGet(Int(0), Bytes("balance")),
            ),
            Return(Int(1)),
        ]
    )

    return program

if __name__ == "__main__":
    with open("security_token_approval.teal", "w") as f:
        compiled = compileTeal(approval_program(), mode=Mode.Application, version=2)
        f.write(compiled)

    with open("security_token_clear_state.teal", "w") as f:
        compiled = compileTeal(clear_state_program(), mode=Mode.Application,
↪version=2)
        f.write(compiled)

```

Data Types and Constants

A PyTeal expression has one of the following two data types:

- `TealType.uint64`, 64 bit unsigned integer
- `TealType.bytes`, a slice of bytes

For example, all the transaction arguments (e.g. `Arg(0)`) are of type `TealType.bytes`. The first valid round of current transaction (`Txn.first_valid()`) is typed `TealType.uint64`.

4.1 Integers

`Int(n)` creates a `TealType.uint64` constant, where $n \geq 0$ and $n < 2^{64}$.

4.2 Bytes

A byte slice is a binary string. There are several ways to encode a byte slice in PyTeal:

4.2.1 UTF-8

Byte slices can be created from UTF-8 encoded strings. For example:

```
Bytes("hello world")
```

4.2.2 Base16

Byte slices can be created from a [RFC 4648#section-8](#) base16 encoded binary string, e.g. `"0xA21212EF"` or `"A21212EF"`. For example:

```
Bytes("base16", "0xA21212EF")
Bytes("base16", "A21212EF") # "0x" is optional
```

4.2.3 Base32

Byte slices can be created from a [RFC 4648#section-6](#) base32 encoded binary string with or without padding, e.g. "7Z5PWO2C6LFNQFGHWKSK5H47IQP5OJW2M3HA2QPXTY3WTNP5NU2MHBW27M".

```
Bytes("base32", "7Z5PWO2C6LFNQFGHWKSK5H47IQP5OJW2M3HA2QPXTY3WTNP5NU2MHBW27M")
```

4.2.4 Base64

Byte slices can be created from a [RFC 4648#section-4](#) base64 encoded binary string, e.g. "Zm9vYmE=".

```
Bytes("base64", "Zm9vYmE=")
```

4.3 Type Checking

All PyTeal expressions are type checked at construction time, for example, running the following code triggers a `TealTypeError`:

```
Int(0) < Arg(0)
```

Since `<` (overloaded Python operator, see [Arithmetic Operations](#) for more details) requires both operands of type `TealType.uint64`, while `Arg(0)` is of type `TealType.bytes`.

4.4 Conversion

Converting a value to its corresponding value in the other data type is supported by the following two operators:

- `Itob(n)`: generate a `TealType.bytes` value from a `TealType.uint64` value `n`
- `Btoi(b)`: generate a `TealType.uint64` value from a `TealType.bytes` value `b`

Note: These operations are **not** meant to convert between human-readable strings and numbers. `Itob` produces a big-endian 8-byte encoding of an unsigned integer, not a human readable string. For example, `Itob(Int(1))` will produce the string `"\x00\x00\x00\x00\x00\x00\x00\x01"` not the string `"1"`.

Arithmetic Operations

An arithmetic expression is an expression that results in a `TealType.uint64` value. In PyTeal, arithmetic expressions include integer and boolean operators (booleans are the integers `0` or `1`). The table below summarized all arithmetic expressions in PyTeal.

Operator	Overloaded	Semantics	Example
<code>Lt(a, b)</code>	<code>a < b</code>	<i>1</i> if <i>a</i> is less than <i>b</i> , <i>0</i> otherwise	<code>Int(1) < Int(5)</code>
<code>Gt(a, b)</code>	<code>a > b</code>	<i>1</i> if <i>a</i> is greater than <i>b</i> , <i>0</i> otherwise	<code>Int(1) > Int(5)</code>
<code>Le(a, b)</code>	<code>a <= b</code>	<i>1</i> if <i>a</i> is no greater than <i>b</i> , <i>0</i> otherwise	<code>Int(1) <= Int(5)</code>
<code>Ge(a, b)</code>	<code>a >= b</code>	<i>1</i> if <i>a</i> is no less than <i>b</i> , <i>0</i> otherwise	<code>Int(1) >= Int(5)</code>
<code>Add(a, b)</code>	<code>a + b</code>	<i>a + b</i> , error (panic) if overflow	<code>Int(1) + Int(5)</code>
<code>Minus(a, b)</code>	<code>a - b</code>	<i>a - b</i> , error if underflow	<code>Int(5) - Int(1)</code>
<code>Mul(a, b)</code>	<code>a * b</code>	<i>a * b</i> , error if overflow	<code>Int(2) * Int(3)</code>
<code>Div(a, b)</code>	<code>a / b</code>	<i>a / b</i> , error if divided by zero	<code>Int(3) / Int(2)</code>
<code>Mod(a, b)</code>	<code>a % b</code>	<i>a % b</i> , modulo operation	<code>Int(7) % Int(3)</code>
<code>Exp(a, b)</code>	<code>a ** b</code>	<i>a ** b</i> , exponent operation	<code>Int(7) ** Int(3)</code>
<code>Eq(a, b)</code>	<code>a == b</code>	<i>1</i> if <i>a</i> equals <i>b</i> , <i>0</i> otherwise	<code>Int(7) == Int(7)</code>
<code>Neq(a, b)</code>	<code>a != b</code>	<i>0</i> if <i>a</i> equals <i>b</i> , <i>1</i> otherwise	<code>Int(7) != Int(7)</code>
<code>And(a, b)</code>		<i>1</i> if <i>a</i> > <i>0</i> && <i>b</i> > <i>0</i> , <i>0</i> otherwise	<code>And(Int(1), Int(1))</code>
<code>Or(a, b)</code>		<i>1</i> if <i>a</i> > <i>0</i> <i>b</i> > <i>0</i> , <i>0</i> otherwise	<code>Or(Int(1), Int(0))</code>
<code>Not(a)</code>		<i>1</i> if <i>a</i> equals <i>0</i> , <i>0</i> otherwise	<code>Not(Int(0))</code>
<code>BitwiseAnd(a, b)</code>	<code>a & b</code>	<i>a & b</i> , bitwise and operation	<code>Int(1) & Int(3)</code>
<code>BitwiseOr(a, b)</code>	<code>a b</code>	<i>a b</i> , bitwise or operation	<code>Int(2) Int(5)</code>
<code>BitwiseXor(a, b)</code>	<code>a ^ b</code>	<i>a ^ b</i> , bitwise xor operation	<code>Int(3) ^ Int(7)</code>
<code>BitwiseNot(a)</code>	<code>~a</code>	<i>~a</i> , bitwise complement operation	<code>~Int(1)</code>

Most of the above operations take two `TealType.uint64` values as inputs. In addition, `Eq(a, b)` (`==`) and `Neq(a, b)` (`!=`) also work for byte slices. For example, `Arg(0) == Arg(1)` and `Arg(0) != Arg(1)` are valid PyTeal expressions.

Both `And` and `Or` also support more than 2 arguments when called as functions:

- `And(a, b, ...)`

- `Or(a, b, ...)`

The associativity and precedence of the overloaded Python arithmetic operators are the same as the [original python operators](#). For example:

- `Int(1) + Int(2) + Int(3)` is equivalent to `Add(Add(Int(1), Int(2)), Int(3))`
- `Int(1) + Int(2) * Int(3)` is equivalent to `Add(Int(1), Mul(Int(2), Int(3)))`

5.1 Byteslice Arithmetic

Byteslice arithmetic is available for Teal V4 and above. Byteslice arithmetic operators allow up to 512-bit arithmetic. In PyTeal, byteslice arithmetic expressions include `TealType.Bytes` values as arguments (with the exception of `BytesZero`) and must be 64 bytes or less. The table below summarizes the byteslice arithmetic operations in PyTeal.

Operator	Return Type	Example	Example Result
<code>BytesLt(a, b)</code>	<code>TealType.uint64</code>	<code>BytesLt(Bytes("base16", "0xFF"), Bytes("base16", "0xFE"))</code>	0
<code>BytesGt(a, b)</code>	<code>TealType.uint64</code>	<code>BytesGt(Bytes("base16", "0xFF"), Bytes("base16", "0xFE"))</code>	1
<code>BytesLe(a, b)</code>	<code>TealType.uint64</code>	<code>BytesLe(Bytes("base16", "0xFF"), Bytes("base16", "0xFE"))</code>	0
<code>BytesGe(a, b)</code>	<code>TealType.uint64</code>	<code>BytesGe(Bytes("base16", "0xFF"), Bytes("base16", "0xFE"))</code>	1
<code>BytesEq(a, b)</code>	<code>TealType.uint64</code>	<code>BytesEq(Bytes("base16", "0xFF"), Bytes("base16", "0xFF"))</code>	1
<code>BytesNeq(a, b)</code>	<code>TealType.uint64</code>	<code>BytesNeq(Bytes("base16", "0xFF"), Bytes("base16", "0xFF"))</code>	0
<code>BytesAdd(a, b)</code>	<code>TealType.Bytes</code>	<code>BytesAdd(Bytes("base16", "0xFF"), Bytes("base16", "0xFE"))</code>	0x01FD
<code>BytesMinus(a, b)</code>	<code>TealType.Bytes</code>	<code>BytesMinus(Bytes("base16", "0xFF"), Bytes("base16", "0xFE"))</code>	0x01
<code>BytesMul(a, b)</code>	<code>TealType.Bytes</code>	<code>BytesMul(Bytes("base16", "0xFF"), Bytes("base16", "0xFE"))</code>	0xFD02
<code>BytesDiv(a, b)</code>	<code>TealType.Bytes</code>	<code>BytesDiv(Bytes("base16", "0xFF"), Bytes("base16", "0x11"))</code>	0x0F
<code>BytesMod(a, b)</code>	<code>TealType.Bytes</code>	<code>BytesMod(Bytes("base16", "0xFF"), Bytes("base16", "0x12"))</code>	0x03
<code>BytesAnd(a, b)</code>	<code>TealType.Bytes</code>	<code>BytesAnd(Bytes("base16", "0xBEEF"), Bytes("base16", "0x1337"))</code>	0x1227
<code>BytesOr(a, b)</code>	<code>TealType.Bytes</code>	<code>BytesOr(Bytes("base16", "0xBEEF"), Bytes("base16", "0x1337"))</code>	0xBFFF
<code>BytesXor(a, b)</code>	<code>TealType.Bytes</code>	<code>BytesXor(Bytes("base16", "0xBEEF"), Bytes("base16", "0x1337"))</code>	0xADD8
<code>BytesNot(a)</code>	<code>TealType.Bytes</code>	<code>BytesNot(Bytes("base16", "0xFF00"))</code>	0x00FF
<code>BytesZero(a)</code>	<code>TealType.Bytes</code>	<code>BytesZero(Int(4))</code>	0x00000000

Currently, byteslice arithmetic operations are not overloaded, and must be explicitly called.

5.2 Bit and Byte Operations

In addition to the standard arithmetic operators above, PyTeal also supports operations that manipulate the individual bits and bytes of PyTeal values.

To use these operations, you'll need to provide an index specifying which bit or byte to access. These indexes have different meanings depending on whether you are manipulating integers or byte slices:

- For integers, bit indexing begins with low-order bits. For example, the bit at index 4 of the integer 16 (000...0001000 in binary) is 1. Every other index has a bit value of 0. Any index less than 64 is valid, regardless of the integer's value.

Byte indexing is not supported for integers.

- For byte strings, bit indexing begins at the first bit. For example, the bit at index 0 of the base16 byte string 0xf0 (11110000 in binary) is 1. Any index less than 4 has a bit value of 1, and any index 4 or greater has a bit value of 0. Any index less than 8 times the length of the byte string is valid.

Likewise, byte indexing begins at the first byte of the string. For example, the byte at index 0 of that the base16 string 0xff00 (1111111100000000 in binary) is 255 (11111111 in binary), and the byte at index 1 is 0. Any index less than the length of the byte string is valid.

5.2.1 Bit Manipulation

The `GetBit` expression can extract individual bit values from integers and byte strings. For example,

```
GetBit(Int(16), Int(0)) # get the 0th bit of 16, produces 0
GetBit(Int(16), Int(4)) # get the 4th bit of 16, produces 1
GetBit(Int(16), Int(63)) # get the 63rd bit of 16, produces 0
GetBit(Int(16), Int(64)) # get the 64th bit of 16, invalid index

GetBit(Bytes("base16", "0xf0"), Int(0)) # get the 0th bit of 0xf0, produces 1
GetBit(Bytes("base16", "0xf0"), Int(7)) # get the 7th bit of 0xf0, produces 0
GetBit(Bytes("base16", "0xf0"), Int(8)) # get the 8th bit of 0xf0, invalid index
```

Additionally, the `SetBit` expression can modify individual bit values from integers and byte strings. For example,

```
SetBit(Int(0), Int(4), Int(1)) # set the 4th bit of 0 to 1, produces 16
SetBit(Int(4), Int(0), Int(1)) # set the 0th bit of 4 to 1, produces 5
SetBit(Int(4), Int(0), Int(0)) # set the 0th bit of 4 to 0, produces 4

SetBit(Bytes("base16", "0x00"), Int(0), Int(1)) # set the 0th bit of 0x00 to 1,
↳ produces 0x80
SetBit(Bytes("base16", "0x00"), Int(3), Int(1)) # set the 3rd bit of 0x00 to 1,
↳ produces 0x10
SetBit(Bytes("base16", "0x00"), Int(7), Int(1)) # set the 7th bit of 0x00 to 1,
↳ produces 0x01
```

5.2.2 Byte Manipulation

In addition to manipulating bits, individual bytes in byte strings can be manipulated.

The `GetByte` expression can extract individual bytes from byte strings. For example,

```
GetByte(Bytes("base16", "0xff00"), Int(0)) # get the 0th byte of 0xff00, produces 255
GetByte(Bytes("base16", "0xff00"), Int(1)) # get the 1st byte of 0xff00, produces 0
GetByte(Bytes("base16", "0xff00"), Int(2)) # get the 2nd byte of 0xff00, invalid index

GetByte(Bytes("abc"), Int(0)) # get the 0th byte of "abc", produces 97 (ASCII 'a')
GetByte(Bytes("abc"), Int(1)) # get the 1st byte of "abc", produces 98 (ASCII 'b')
GetByte(Bytes("abc"), Int(2)) # get the 2nd byte of "abc", produces 99 (ASCII 'c')
```

Additionally, the `SetByte` expression can modify individual bytes in byte strings. For example,

```
SetByte(Bytes("base16", "0xff00"), Int(0), Int(0)) # set the 0th byte of 0xff00 to 0,
↳ produces 0x0000
SetByte(Bytes("base16", "0xff00"), Int(0), Int(128)) # set the 0th byte of 0xff00 to
↳ 128, produces 0x8000

SetByte(Bytes("abc"), Int(0), Int(98)) # set the 0th byte of "abc" to 98 (ASCII 'b'),
↳ produces "bbc"
SetByte(Bytes("abc"), Int(1), Int(66)) # set the 1st byte of "abc" to 66 (ASCII 'B'),
↳ produces "aBc"
```


TEAL byte slices are similar to strings and can be manipulated in the same way.

6.1 Length

The length of a byte slice can be obtained using the *Len* expression. For example:

```
Len(Bytes("")) # will produce 0
Len(Bytes("algorand")) # will produce 8
```

6.2 Concatenation

Byte slices can be combined using the *Concat* expression. This expression takes at least two arguments and produces a new byte slice consisting of each argument, one after another. For example:

```
Concat(Bytes("a"), Bytes("b"), Bytes("c")) # will produce "abc"
```

6.3 Substring Extraction

Byte slices can be extracted from other byte slices using the *Substring* and *Extract* expressions. These expressions are extremely similar, except one specifies a substring by start and end indexes, while the other uses a start index and length. Use whichever makes sense for your application.

6.3.1 Substring

The *Substring* expression can extract part of a byte slice given start and end indices. For example:

```
Substring(Bytes("algorand"), Int(2), Int(8)) # will produce "gorand"
```

6.3.2 Extract

Note: Extract is only available in TEAL version 5 or higher.

The *Extract* expression can extract part of a byte slice given the start index and length. For example:

```
Extract(Bytes("algorand"), Int(2), Int(6)) # will produce "gorand"
```

6.4 Manipulating Individual Bits and Bytes

The individual bits and bytes in a byte string can be extracted and changed. See *Bit and Byte Operations* for more information.

Transaction Fields and Global Parameters

PyTeal smart contracts can access properties of the current transaction and the state of the blockchain when they are running.

7.1 Transaction Fields

Information about the current transaction being evaluated can be obtained using the `Txn` object using the PyTeal expressions shown below.

Since numerous transaction fields exist, the fields are logically organized into tables by transaction type.

7.1.1 Fields by Transaction Type

Common Fields

Operator	Type	Min TEAL Version	Notes
<i>Txn.type()</i>	TealType.bytes	2	
<i>Txn.type_enum()</i>	TealType.uint64	2	see table below
<i>Txn.sender()</i>	TealType.bytes	2	32 byte address
<i>Txn.fee()</i>	TealType.uint64	2	in microAlgos
<i>Txn.first_valid()</i>	TealType.uint64	2	round number
<i>Txn.last_valid()</i>	TealType.uint64	2	round number
<i>Txn.note()</i>	TealType.bytes	2	transaction note in bytes
<i>Txn.lease()</i>	TealType.bytes	2	transaction lease in bytes
<i>Txn.group_index()</i>	TealType.uint64	2	position of this transaction within a transaction group, starting at 0
<i>Txn.tx_id()</i>	TealType.bytes	2	the computed ID for this transaction, 32 bytes
<i>Txn.rekey_to()</i>	TealType.bytes	2	32 byte address

Application Call

Operator	Type	Min TEAL Version	Notes
<code>Txn.application_id()</code>	TealType. uint64	2	
<code>Txn.on_completion()</code>	TealType. uint64	2	
<code>Txn.approval_program</code>	TealType. bytes	2	
<code>Txn.global_num_uints()</code>	TealType. uint64	3	Maximum global integers in app schema
<code>Txn.global_num_bytes()</code>	TealType. uint64	3	Maximum global byte strings in app schema
<code>Txn.local_num_uints()</code>	TealType. uint64	3	Maximum local integers in app schema
<code>Txn.local_num_bytes()</code>	TealType. uint64	3	Maximum local byte strings in app schema
<code>Txn.accounts</code>	TealType. bytes[]	2	Array of application accounts
<code>Txn.assets</code>	TealType. uint64[]	3	Array of application assets
<code>Txn.applications</code>	TealType. uint64[]	3	Array of applications
<code>Txn.clear_state_program</code>	TealType. bytes()	2	
<code>Txn.extra_program_pages</code>	TealType. uint64	4	Number of extra program pages for app
<code>Txn.application_args</code>	TealType. bytes[]	2	Array of application arguments
<code>Txn.created_application_id()</code>	TealType. uint64	5	The ID of the newly created application in this transaction. In v5, only valid on inner transactions. >= v6 works with top-level and inner transactions.
<code>Txn.logs</code>	TealType. bytes[]	5	Array of application logged items. In v5, only valid on inner transactions. >= v6 works with top-level and inner transactions.
<code>Txn.last_log()</code>	TealType. bytes[]	6	The last message emitted. Empty bytes if none were emitted. Application mode only.

Asset Config

Operator	Type	Min TEAL Version	Notes
<code>Txn.config_asset()</code>	<code>TealType.uint64</code>	2	ID of asset being configured
<code>Txn.config_asset_total_supply()</code>	<code>TealType.uint64</code>	2	
<code>Txn.config_asset_decimal_places()</code>	<code>TealType.uint64</code>	2	
<code>Txn.config_asset_default_frozen()</code>	<code>TealType.uint64</code>	2	
<code>Txn.config_asset_unit_name()</code>	<code>TealType.bytes</code>	2	
<code>Txn.config_asset_name()</code>	<code>TealType.bytes</code>	2	
<code>Txn.config_asset_url()</code>	<code>TealType.bytes</code>	2	
<code>Txn.config_asset_metadata_hash()</code>	<code>TealType.bytes</code>	2	
<code>Txn.config_asset_manage_address()</code>	<code>TealType.bytes</code>	2	32 byte address
<code>Txn.config_asset_reserve_address()</code>	<code>TealType.bytes</code>	2	32 byte address
<code>Txn.config_asset_freeze_address()</code>	<code>TealType.bytes</code>	2	32 byte address
<code>Txn.config_asset_clawback_address()</code>	<code>TealType.bytes</code>	2	32 byte address
<code>Txn.created_asset_id()</code>	<code>TealType.uint64</code>	5	The ID of the newly created asset in this transaction. In v5, only valid on inner transactions. >= v6 works with top-level and inner transactions.

Asset Freeze

Operator	Type	Min TEAL Version	Notes
<code>Txn.freeze_asset()</code>	<code>TealType.uint64</code>	2	
<code>Txn.freeze_asset_account()</code>	<code>TealType.bytes</code>	2	32 byte address
<code>Txn.freeze_asset_frozen()</code>	<code>TealType.uint64</code>	2	

Asset Transfer

Operator	Type	Min TEAL Version	Notes
<code>Txn.xfer_asset()</code>	<code>TealType.uint64</code>	2	ID of asset being transferred
<code>Txn.asset_amount()</code>	<code>TealType.uint64</code>	2	value in Asset's units
<code>Txn.asset_sender()</code>	<code>TealType.bytes</code>	2	32 byte address, causes clawback of all value if sender is the clawback
<code>Txn.asset_receiver()</code>	<code>TealType.bytes</code>	2	32 byte address
<code>Txn.asset_close_to()</code>	<code>TealType.bytes</code>	2	32 byte address

Key Registration

Operator	Type	Min TEAL Version	Notes
<code>Txn.vote_pk()</code>	<code>TealType.bytes</code>	2	32 byte address
<code>Txn.selection_pk()</code>	<code>TealType.bytes</code>	2	32 byte address
<code>Txn.state_proof_pk</code>	<code>TealType.bytes</code>	6	64 byte state proof public key commitment.
<code>Txn.vote_first()</code>	<code>TealType.uint64</code>	2	
<code>Txn.vote_last()</code>	<code>TealType.uint64</code>	2	
<code>Txn.vote_key_dilution()</code>	<code>TealType.uint64</code>	2	
<code>Txn.nonparticipation()</code>	<code>TealType.uint64</code>	5	Marks an account nonparticipating for rewards

Payment

Operator	Type	Min TEAL Version	Notes
<code>Txn.receiver()</code>	<code>TealType.bytes</code>	2	32 byte address
<code>Txn.amount()</code>	<code>TealType.uint64</code>	2	in microAlgos
<code>Txn.close_remainder_to()</code>	<code>TealType.bytes</code>	2	32 byte address

7.1.2 Transaction Types

The `Txn.type_enum()` values can be checked using the `TxnType` enum:

Value	Numerical Value	Type String	Description
<code>TxnType.Unknown</code>	0	unknown	unknown type, invalid
<code>TxnType.Payment</code>	1	pay	payment
<code>TxnType.KeyRegistration</code>	2	keyreg	key registration
<code>TxnType.AssetConfig</code>	3	acfg	asset config
<code>TxnType.AssetTransfer</code>	4	axfer	asset transfer
<code>TxnType.AssetFreeze</code>	5	afrz	asset freeze
<code>TxnType.ApplicationCall</code>	6	appl	application call

7.1.3 Transaction Array Fields

Some of the exposed transaction fields are arrays with the type `TealType.uint64[]` or `TealType.bytes[]`. These fields are `Txn.application_args`, `Txn.assets`, `Txn.accounts`, `Txn.applications`, and `InnerTxn.logs`.

The length of these array fields can be found using the `.length()` method, and individual items can be accessed using bracket notation. For example:

```
Txn.application_args.length() # get the number of application arguments in the
↳ transaction
Txn.application_args[0] # get the first application argument
Txn.application_args[1] # get the second application argument

# as of TEAL v5, PyTeal expressions can be used to dynamically index into array
↳ properties as well
Txn.application_args[Txn.application_args.length() - Int(1)] # get the last
↳ application argument
```

Special case: `Txn.accounts` and `Txn.applications`

The `Txn.accounts` and `Txn.applications` arrays are special cases. Normal arrays in PyTeal are 0-indexed, but these are 1-indexed with special values at index 0.

For the accounts array, `Txn.accounts[0]` is always equivalent to `Txn.sender()`.

For the applications array, `Txn.applications[0]` is always equivalent to `Txn.application_id()`.

IMPORTANT: Since these arrays are 1-indexed, their lengths are handled differently. For example, if `Txn.accounts.length()` or `Txn.applications.length()` is 2, then indexes 0, 1, and 2 will be present. In fact, the index 0 will always evaluate to the special values above, even when `length()` is 0.

7.2 Atomic Transfer Groups

Atomic Transfers are irreducible batch transactions that allow groups of transactions to be submitted at one time. If any of the transactions fail, then all the transactions will fail. PyTeal allows programs to access information about the transactions in an atomic transfer group using the `Gtxn` object. This object acts like a list of `TxnObject`, meaning all of the above transaction fields on `Txn` are available on the elements of `Gtxn`. For example:

```
Gtxn[0].sender() # get the sender of the first transaction in the atomic transfer
↳ group
Gtxn[1].receiver() # get the receiver of the second transaction in the atomic
↳ transfer group
```

(continues on next page)

(continued from previous page)

```
# as of TEAL v3, PyTeal expressions can be used to dynamically index into Gtxn as well
Gtxn[Txn.group_index() - Int(1)].sender() # get the sender of the previous_
↳ transaction in the atomic transfer group
```

`Gtxn` is zero-indexed and the maximum size of an atomic transfer group is 16. The size of the current transaction group is available as `Global.group_size()`. A standalone transaction will have a group size of 1.

To find the current transaction's index in the transfer group, use `Txn.group_index()`. If the current transaction is standalone, its group index will be 0.

7.3 Inner Transactions

Note: Inner transactions are only available in TEAL version 5 or higher.

Inner transactions can be created and submitted with expressions from the `InnerTxnBuilder` class. The properties of the most recently submitted inner transaction can be accessed using the `InnerTxn` object. This object is an instance of `TxnObject`, meaning all of the above transaction fields on `Txn` are available on `InnerTxn` as well.

7.4 Global Parameters

Information about the current state of the blockchain can be obtained using the following `Global` expressions:

Operator	Type	Min TEAL Version	Notes
<code>Global.min_txn_fee()</code>	<code>TealType.uint64</code>	2	in microAlgos
<code>Global.min_balance()</code>	<code>TealType.uint64</code>	2	in mircoAlgos
<code>Global.max_txn_life()</code>	<code>TealType.uint64</code>	2	number of rounds
<code>Global.zero_address()</code>	<code>TealType.bytes</code>	2	32 byte address of all zero bytes
<code>Global.group_size()</code>	<code>TealType.uint64</code>	2	number of txns in this atomic transaction group, at least 1
<code>Global.logic_sig_version()</code>	<code>TealType.uint64</code>	2	the maximum supported TEAL version
<code>Global.round()</code>	<code>TealType.uint64</code>	2	the current round number
<code>Global.latest_timestamp()</code>	<code>TealType.uint64</code>	2	the latest confirmed block UNIX timestamp
<code>Global.current_application_id()</code>	<code>TealType.uint64</code>	2	the ID of the current application executing
<code>Global.creator_address()</code>	<code>TealType.bytes</code>	3	32 byte address of the creator of the current application
<code>Global.current_application_address()</code>	<code>TealType.bytes</code>	5	32 byte address of the current application controlled account
<code>Global.group_id()</code>	<code>TealType.bytes</code>	5	32 byte ID of the current transaction group

Cryptographic Primitives

Algorand Smart Contracts support 4 cryptographic primitives, including 3 cryptographic hash functions and 1 digital signature verification. Each of these cryptographic primitives is associated with a cost, which is a number indicating its relative performance overhead comparing with simple TEAL operations such as addition and subtraction. Simple TEAL opcodes have cost *1*, and more advanced cryptographic operations have a larger cost. Below is how you express cryptographic primitives in PyTeal:

Operator	Cost	Description
Sha256(e)	35	<i>SHA-256</i> hash function, produces 32 bytes
Keccak256(e)	130	<i>Keccak-256</i> hash function, produces 32 bytes
Sha512_256(e)	45	<i>SHA-512/256</i> hash function, produces 32 bytes
Ed25519Verify(d, s, p)	1900*	1 if <i>s</i> is the signature of <i>d</i> signed by private key <i>p</i> , else 0

* Ed25519Verify is only available in signature mode.

Note the cost amount is accurate for version 2 of TEAL and higher.

These cryptographic primitives cover the most used ones in blockchains and cryptocurrencies. For example, Bitcoin uses *SHA-256* for creating Bitcoin addresses; Algorand uses *ed25519* signature scheme for authorization and uses *SHA-512/256* hash function for creating contract account addresses from TEAL bytecode.

Scratch Space

Scratch space is a temporary place to store values for later use in your program. It is temporary because any changes to scratch space do not persist beyond the current transaction. Scratch space can be used in both Application and Signature mode.

Scratch space consists of 256 scratch slots, each capable of storing one integer or byte slice. When using the *ScratchVar* class to work with scratch space, a slot is automatically assigned to each variable.

9.1 Writing and Reading

To write to scratch space, first create a *ScratchVar* object and pass in the *TealType* of the values that you will store there. It is possible to create a *ScratchVar* that can store both integers and byte slices by passing no arguments to the *ScratchVar* constructor, but note that no type checking takes place in this situation. It is also possible to manually specify which slot ID the compiler should assign the scratch slot to in the TEAL code. If no slot ID is specified, the compiler will assign it to any available slot.

To write or read values, use the corresponding *ScratchVar.store* or *ScratchVar.load* methods.

For example:

```
myvar = ScratchVar(TealType.uint64) # assign a scratch slot in any available slot
program = Seq([
    myvar.store(Int(5)),
    Assert(myvar.load() == Int(5))
])
anotherVar = ScratchVar(TealType.bytes, 4) # assign this scratch slot to slot #4
```

Loading Values from Group Transactions

Since TEAL version 4 and above, programs can load values from transactions within an atomic group transaction. For instance, you can import values from the scratch space of another application call, and you can access the generated ID of a new application or asset. These operations are only permitted in application mode.

10.1 Accessing IDs of New Apps and Assets

The generated ID of an asset or application from a creation transaction in the current atomic group can be accessed using the `GeneratedID` expression. The specified transaction index may be a Python int or a PyTeal expression that must be evaluated to a uint64 at runtime. The transaction index must be less than the index of the current transaction and the maximum allowed group size (16).

For example:

```
GeneratedID(0) # retrieves the ID from the 0th transaction in current group
GeneratedID(Int(10)) # retrieves the ID from the 10th transaction in group
```

Note that if the index is a Python int, it is interpreted as an immediate value (uint8) and will be translated to a TEAL `gaids op`. Otherwise, it will be translated to a TEAL `gaids op`.

10.2 Loading Scratch Slots

The scratch value from another transaction in the current atomic group can be accessed using the `ImportScratchValue` expression. The transaction index may be a Python int or a PyTeal expression that must be evaluated to a uint64 at runtime, and the scratch slot ID to load from must be a Python int. The transaction index must be less than the index of the current transaction and the maximum allowed group size (16), and the slot ID must be less than the maximum number of scratch slots (256).

For example, assume an atomic transaction group contains app calls to the following applications, where App A is called from the first transaction (index 0) and App B is called from the second or later transaction. Then the greeting value will be successfully passed between the two contracts.

App A:

```
# App is called at transaction index 0
greeting = ScratchVar(TealType.bytes, 20) # this variable will live in scratch slot 20
program = Seq([
    If(Txn.sender() == App.globalGet(Bytes("creator"))).
    Then(greeting.store(Bytes("hi creator!"))).
    Else(greeting.store(Bytes("hi user!"))),
    Return(Int(1))
])
```

App B:

```
greetingFromPreviousApp = ImportScratchValue(0, 20) # loading scratch slot 20 from
↳ the transaction at index 0
program = Seq([
    # not shown: make sure that the transaction at index 0 is an app call to App A
    App.globalPut(Bytes("greeting from prev app"), greetingFromPreviousApp),
    Return(Int(1))
])
```

Note that if the index is a Python int, it is interpreted as an immediate value (uint8) and will be translated to a TEAL gload op. Otherwise, it will be translated to a TEAL gloads op.

PyTeal provides several control flow expressions to create programs.

11.1 Exiting the Program: Approve and Reject

Note: The `Approve` and `Reject` expressions are only available in TEAL version 4 or higher. Prior to this, `Return(Int(1))` is equivalent to `Approve()` and `Return(Int(0))` is equivalent to `Reject()`.

The `Approve` and `Reject` expressions cause the program to immediately exit. If `Approve` is used, then the execution is marked as successful, and if `Reject` is used, then the execution is marked as unsuccessful.

These expressions also work inside *subroutines*.

11.2 Chaining Expressions: Seq

The `Seq` expression can be used to create a sequence of multiple expressions. It's arguments are the expressions to include in the sequence, either as a variable number of arguments, or as a single list

For example:

```
Seq(  
    App.globalPut(Bytes("creator"), Txn.sender()),  
    Return(Int(1))  
)
```

A `Seq` expression will take on the value of its last expression. Additionally, all expressions in a `Seq` expression, except the last one, must not return anything (e.g. evaluate to `TealType.none`). This restriction is in place because intermediate values must not add things to the TEAL stack. As a result, the following is an invalid sequence:

Listing 1: Invalid Seq expression

```
Seq(  
    Txn.sender(),  
    Return(Int(1))  
)
```

If you must include an operation that returns a value in the earlier part of a sequence, you can wrap the value in a *Pop* expression to discard it. For example,

```
Seq(  
    Pop(Txn.sender()),  
    Return(Int(1))  
)
```

11.3 Simple Branching: If

In an *If* expression,

```
If(test-expr, then-expr, else-expr)
```

the *test-expr* is always evaluated and needs to be typed `TealType.uint64`. If it results in a value greater than 0, then the *then-expr* is evaluated. Otherwise, *else-expr* is evaluated. Note that *then-expr* and *else-expr* must evaluate to the same type (e.g. both `TealType.uint64`).

You may also invoke an *If* expression without an *else-expr*:

```
If(test-expr, then-expr)
```

In this case, *then-expr* must be typed `TealType.none`.

There is also an alternate way to write an *If* expression that makes reading complex statements easier to read.

```
If(test-expr)  
    .Then(then-expr)  
    .ElseIf(test-expr)  
    .Then(then-expr)  
    .Else(else-expr)
```

11.4 Checking Conditions: Assert

The *Assert* expression can be used to ensure that conditions are met before continuing the program. The syntax for *Assert* is:

```
Assert(test-expr)
```

If *test-expr* is always evaluated and must be typed `TealType.uint64`. If *test-expr* results in a value greater than 0, the program continues. Otherwise, the program immediately exits and indicates that it encountered an error.

Example:

```
Assert(Txn.type_enum() == TxnType.Payment)
```

The above example will cause the program to immediately fail with an error if the transaction type is not a payment.

11.5 Chaining Tests: Cond

A *Cond* expression chains a series of tests to select a result expression. The syntax of *Cond* is:

```
Cond([test-expr-1, body-1],
      [test-expr-2, body-2],
      . . . )
```

Each *test-expr* is evaluated in order. If it produces 0, the paired *body* is ignored, and evaluation proceeds to the next *test-expr*. As soon as a *test-expr* produces a true value (> 0), its *body* is evaluated to produce the value for this *Cond* expression. If none of *test-expr*s evaluates to a true value, the *Cond* expression will be evaluated to *err*, a TEAL opcode that causes the runtime panic.

In a *Cond* expression, each *test-expr* needs to be typed `TealType.uint64`. A *body* could be typed either `TealType.uint64` or `TealType.bytes`. However, all *body*s must have the same data type. Otherwise, a `TealTypeError` is triggered.

Example:

```
Cond([Global.group_size() == Int(5), bid],
      [Global.group_size() == Int(4), redeem],
      [Global.group_size() == Int(1), wrapup])
```

This PyTeal code branches on the size of the atomic transaction group.

11.6 Looping: While

Note: This expression is only available in TEAL version 4 or higher.

The *While* expression can be used to create simple loops in PyTeal. The syntax of *While* is:

```
While(loop-condition).Do(loop-body)
```

The *loop-condition* expression must evaluate to `TealType.uint64`, and the *loop-body* expression must evaluate to `TealType.none`.

The *loop-body* expression will continue to execute as long as *loop-condition* produces a true value (> 0).

For example, the following code uses *ScratchVar* to iterate through every transaction in the current group and sum up all of their fees.

```
totalFees = ScratchVar(TealType.uint64)
i = ScratchVar(TealType.uint64)

Seq([
    i.store(Int(0)),
    totalFees.store(Int(0)),
    While(i.load() < Global.group_size()).Do(Seq([
```

(continues on next page)

(continued from previous page)

```

        totalFees.store(totalFees.load() + Gtxn[i.load()].fee()),
        i.store(i.load() + Int(1))
    )))
]

```

11.7 Looping: For

Note: This expression is only available in TEAL version 4 or higher.

Similar to `While`, the `For` expression can also be used to create loops in PyTeal. The syntax of `For` is:

```
For(loop-start, loop-condition, loop-step).Do(loop-body)
```

The `loop-start`, `loop-step`, and `loop-body` expressions must evaluate to `TealType.none`, and the `loop-condition` expression must evaluate to `TealType.uint64`.

When a `For` expression is executed, `loop-start` is executed first. Then the expressions `loop-condition`, `loop-body`, and `loop-step` will continue to execute in order as long as `loop-condition` produces a true value (> 0).

For example, the following code uses `ScratchVar` to iterate through every transaction in the current group and sum up all of their fees. The code here is functionally equivalent to the `While` loop example above.

```

totalFees = ScratchVar(TealType.uint64)
i = ScratchVar(TealType.uint64)

Seq([
    totalFees.store(Int(0)),
    For(i.store(Int(0)), i.load() < Global.group_size(), i.store(i.load() + Int(1))).
    ↪Do(
        totalFees.store(totalFees.load() + Gtxn[i.load()].fee())
    )
])

```

11.8 Exiting Loops: Continue and Break

The expressions `Continue` and `Break` can be used to exit `While` and `For` loops in different ways.

When `Continue` is present in the loop body, it instructs the program to skip the remainder of the loop body. The loop may continue to execute as long as its condition remains true.

For example, the code below iterates through every transaction in the current group and counts how many are payments, using the `Continue` expression.

```

numPayments = ScratchVar(TealType.uint64)
i = ScratchVar(TealType.uint64)

Seq([
    numPayments.store(Int(0)),
    For(i.store(Int(0)), i.load() < Global.group_size(), i.store(i.load() + Int(1))).
    ↪Do(Seq([

```

(continues on next page)

(continued from previous page)

```

        If (Gtxn[i.load()].type_enum() != TxnType.Payment)
        .Then(Continue()),
        numPayments.store(numPayments.load() + Int(1))
    )))
])

```

When `Break` is present in the loop body, it instructs the program to completely exit the current loop. The loop will not continue to execute, even if its condition remains true.

For example, the code below finds the index of the first payment transaction in the current group, using the `Break` expression.

```

firstPaymentIndex = ScratchVar(TealType.uint64)
i = ScratchVar(TealType.uint64)

Seq([
    # store a default value in case no payment transactions are found
    firstPaymentIndex.store(Global.group_size()),
    For(i.store(Int(0)), i.load() < Global.group_size(), i.store(i.load() + Int(1))).
    ↪Do(
        If(Gtxn[i.load()].type_enum() == TxnType.Payment)
        .Then(Seq([
            firstPaymentIndex.store(i.load()),
            Break()
        ]))
    ),
    # assert that a payment was found
    Assert(firstPaymentIndex.load() < Global.group_size())
])

```

11.9 Subroutines

Note: Subroutines are only available in TEAL version 4 or higher.

A subroutine is section of code that can be called multiple times from within a program. Subroutines are PyTeal's equivalent to functions. Subroutines can accept any number of arguments, and these arguments must be PyTeal expressions. Additionally, a subroutine may return a single value, or no value.

11.9.1 Creating Subroutines

To create a subroutine, apply the `Subroutine` function decorator to a Python function which implements the subroutine. This decorator takes one argument, which is the return type of the subroutine. `TealType.none` indicates that the subroutine does not return a value, and any other type (e.g. `TealType.uint64` or `TealType.bytes`) indicates the return type of the single value the subroutine returns.

For example,

```

@Subroutine(TealType.uint64)
def isEven(i):
    return i % Int(2) == Int(0)

```

11.9.2 Calling Subroutines

To call a subroutine, simply call it like a normal Python function and pass in its arguments. For example,

```
App.globalPut(Bytes("value_is_even"), isEven(Int(10)))
```

11.9.3 Recursion

Recursion with subroutines is also possible. For example, the subroutine below also checks if its argument is even, but uses recursion to do so.

```
@Subroutine(TealType.uint64)
def recursiveIsEven(i):
    return (
        If(i == Int(0))
        .Then(Int(1))
        .ElseIf(i == Int(1))
        .Then(Int(0))
        .Else(recursiveIsEven(i - Int(2)))
    )
```

11.9.4 Exiting Subroutines

The `Return` expression can be used to explicitly return from a subroutine.

If the subroutine does not return a value, `Return` should be called with no arguments. For example, the subroutine below asserts that the first payment transaction in the current group has a fee of 0:

```
@Subroutine(TealType.none)
def assertFirstPaymentHasZeroFee():
    i = ScratchVar(TealType.uint64)

    return Seq([
        For(i.store(Int(0)), i.load() < Global.group_size(), i.store(i.load() +
↪Int(1))) .Do(
            If(Gtxn[i.load()].type_enum() == TxnType.Payment)
            .Then(Seq([
                Assert(Gtxn[i.load()].fee() == Int(0)),
                Return()
            ]))
        ),
        # no payments found
        Err()
    ])
1)
```

Otherwise if the subroutine does return a value, that value should be the argument to the `Return` expression. For example, the subroutine below checks whether the current group contains a payment transaction:

```
@Subroutine(TealType.uint64)
def hasPayment():
    i = ScratchVar(TealType.uint64)

    return Seq([
        For(i.store(Int(0)), i.load() < Global.group_size(), i.store(i.load() +
↪Int(1))) .Do(
```

(continues on next page)

(continued from previous page)

```
        If (Gtxn[i].load()).type_enum() == TxnType.Payment)
            .Then (Return (Int (1)))
    ),
    Return (Int (0))
]
```

Return can also be called from the main program. In this case, a single integer argument should be provided, which is the success value for the current execution. A true value (> 0) is equivalent to *Approve*, and a false value is equivalent to *Reject*.

State Access and Manipulation

PyTeal can be used to write [Stateful Algorand Smart Contracts](#) as well. Stateful contracts, also known as applications, can access and manipulate state on the Algorand blockchain.

State consists of key-value pairs, where keys are byte slices and values can be integers or byte slices. There are multiple types of state that an application can use.

12.1 State Operation Table

Context	Write	Read	Delete	Check If Exists
Current App Global	<code>App.globalPut</code>	<code>App.globalGet</code>	<code>App.globalDel</code>	<code>App.globalGetEx</code>
Current App Local	<code>App.localPut</code>	<code>App.localGet</code>	<code>App.localDel</code>	<code>App.localGetEx</code>
Other App Global		<code>App.globalGetEx</code>		<code>App.globalGetEx</code>
Other App Local		<code>App.localGetEx</code>		<code>App.localGetEx</code>

12.2 Global State

Global state consists of key-value pairs that are stored in the application's global context. It can be manipulated as follows:

12.2.1 Writing Global State

To write to global state, use the `App.globalPut` function. The first argument is the key to write to, and the second argument is the value to write. For example:

```
App.globalPut(Bytes("status"), Bytes("active")) # write a byte slice
App.globalPut(Bytes("total supply"), Int(100)) # write a uint64
```

12.2.2 Reading Global State

To read from global state, use the `App.globalGet` function. The only argument it takes is the key to read from. For example:

```
App.globalGet(Bytes("status"))
App.globalGet(Bytes("total supply"))
```

If you try to read from a key that does not exist in your app's global state, the integer `0` is returned.

12.2.3 Deleting Global State

To delete a key from global state, use the `App.globalDel` function. The only argument it takes is the key to delete. For example:

```
App.globalDel(Bytes("status"))
App.globalDel(Bytes("total supply"))
```

If you try to delete a key that does not exist in your app's global state, nothing happens.

12.3 Local State

Local state consists of key-value pairs that are stored in a unique context for each account that has opted into your application. As a result, you will need to specify an account when manipulating local state. This is done by passing in the address of an account. In order to read or manipulate an account's local state, that account must be presented in the `Txn.accounts` array.

Note: The `Txn.accounts` array does not behave like a normal array. It's actually a 1-indexed array with a special value at index `0`, the sender's account. See *Special case: `Txn.accounts` and `Txn.applications`* for more details.

12.3.1 Writing Local State

To write to the local state of an account, use the `App.localPut` function. The first argument is the address of the account to write to, the second argument is the key to write to, and the third argument is the value to write. For example:

```
App.localPut(Txn.sender(), Bytes("role"), Bytes("admin")) # write a byte slice to the
↪ sender's account
App.localPut(Txn.sender(), Bytes("balance"), Int(10)) # write a uint64 to the sender
↪ 's account
App.localPut(Txn.accounts[1], Bytes("balance"), Int(10)) # write a uint64 to Txn.
↪ account[1]
```

Note: It is only possible to write to the local state of an account if that account has opted into your application. If the account has not opted in, the program will fail with an error. The function `App.optedIn` can be used to check if an account has opted into an app.

12.3.2 Reading Local State

To read from the local state of an account, use the `App.localGet` function. The first argument is the address of the account to read from, and the second argument is the key to read. For example:

```
App.localGet(Txn.sender(), Bytes("role")) # read from the sender's account
App.localGet(Txn.sender(), Bytes("balance")) # read from the sender's account
App.localGet(Txn.accounts[1], Bytes("balance")) # read from Txn.accounts[1]
```

If you try to read from a key that does not exist in your app's global state, the integer 0 is returned.

12.3.3 Deleting Local State

To delete a key from local state of an account, use the `App.localDel` function. The first argument is the address of the corresponding account, and the second argument is the key to delete. For example:

```
App.localDel(Txn.sender(), Bytes("role")) # delete "role" from the sender's account
App.localDel(Txn.sender(), Bytes("balance")) # delete "balance" from the sender's
↪account
App.localDel(Txn.accounts[1], Bytes("balance")) # delete "balance" from Txn.
↪accounts[1]
```

If you try to delete a key that does not exist in the account's local state, nothing happens.

12.4 External State

The above functions allow an app to read and write state in its own context. Additionally, it's possible for applications to read state written by other applications. This is possible using the `App.globalGetEx` and `App.localGetEx` functions.

Unlike the other state access functions, `App.globalGetEx` and `App.localGetEx` return a `MaybeValue`. This value cannot be used directly, but has methods `MaybeValue.hasValue()` and `MaybeValue.value()`. If the key being accessed exists in the context of the app being read, `hasValue()` will return 1 and `value()` will return its value. Otherwise, `hasValue()` and `value()` will return 0.

Note: Even though the `MaybeValue` returned by `App.globalGetEx` and `App.localGetEx` cannot be used directly, it **must** be included in the application before `hasValue()` and `value()` are called on it. You will probably want to use `Seq` to do this.

Since these functions are the only way to check whether a key exists, it can be useful to use them in the current application's context too.

12.4.1 External Global

To read a value from the global state of another application, use the `App.globalGetEx` function.

In order to use this function you need to pass in an integer that represents an application to read from. This integer corresponds to an actual application ID that appears in the `Txn.applications` array.

Note: The `Txn.applications` array does not behave like a normal array. It's actually a 1-indexed array with a special value at index 0, the current application's ID. See *Special case: Txn.accounts and Txn.applications* for more details.

Now that you have an integer that represents an application to read from, pass this as the first argument to `App.globalGetEx`, and pass the key to read as the second argument. For example:

```

# get "status" from the global context of Txn.applications[0] (the current app)
# if "status" has not been set, returns "none"
myStatus = App.globalGetEx(Txn.applications[0], Bytes("status"))

program = Seq([
    myStatus,
    If(myStatus.hasValue(), myStatus.value(), Bytes("none"))
])

# get "status" from the global context of Txn.applications[1]
# if "status" has not been set, returns "none"
otherStatus = App.globalGetEx(Txn.applications[1], Bytes("status"))
program = Seq([
    otherStatus,
    If(otherStatus.hasValue(), otherStatus.value(), Bytes("none"))
])

# get "total supply" from the global context of Txn.applications[1]
# if "total supply" has not been set, returns the default value of 0
otherSupply = App.globalGetEx(Txn.applications[1], Bytes("total supply"))
program = Seq([
    otherSupply,
    otherSupply.value()
])

```

12.4.2 External Local

To read a value from an account's local state for another application, use the `App.localGetEx` function.

The first argument is the address of the account to read from (in the same format as `App.localGet`), the second argument is the ID of the application to read from, and the third argument is the key to read.

Note: The second argument is the actual ID of the application to read from, not an index into `Txn.applications`. This means that you can read from any application that the account has opted into, not just applications included in `Txn.applications`. The ID 0 is still a special value that refers to the ID of the current application, but you could also use `Global.current_application_id()` or `Txn.application_id()` to refer to the current application.

For example:

```

# get "role" from the local state of Txn.accounts[0] (the sender) for the current app
# if "role" has not been set, returns "none"
myAppSenderRole = App.localGetEx(Txn.accounts[0], Int(0), Bytes("role"))
program = Seq([
    myAppSenderRole,
    If(myAppSenderRole.hasValue(), myAppSenderRole.value(), Bytes("none"))
])

# get "role" from the local state of Txn.accounts[1] for the current app
# if "role" has not been set, returns "none"
myAppOtherAccountRole = App.localGetEx(Txn.accounts[1], Int(0), Bytes("role"))
program = Seq([
    myAppOtherAccountRole,
    If(myAppOtherAccountRole.hasValue(), myAppOtherAccountRole.value(), Bytes("none"))
])

```

(continues on next page)

(continued from previous page)

```
# get "role" from the local state of Txn.accounts[0] (the sender) for the app with ID ↪
↪31
# if "role" has not been set, returns "none"
otherAppSenderRole = App.localGetEx(Txn.accounts[0], Int(31), Bytes("role"))
program = Seq([
    otherAppSenderRole,
    If(otherAppSenderRole.hasValue(), otherAppSenderRole.value(), Bytes("none"))
])

# get "role" from the local state of Txn.accounts[1] for the app with ID 31
# if "role" has not been set, returns "none"
otherAppOtherAccountRole = App.localGetEx(Txn.accounts[1], Int(31), Bytes("role"))
program = Seq([
    otherAppOtherAccountRole,
    If(otherAppOtherAccountRole.hasValue(), otherAppOtherAccountRole.value(), Bytes(
↪"none"))
])
```


CHAPTER 13

Asset Information

In addition to *manipulating state on the blockchain*, stateful smart contracts can also look up information about assets and account balances.

13.1 Algo Balances

The *Balance* expression can be used to look up an account's balance in microAlgos (1 Algo = 1,000,000 microAlgos). For example,

```
senderBalance = Balance(Txn.sender()) # get the balance of the sender
account1Balance = Balance(Txn.accounts[1]) # get the balance of Txn.accounts[1]
```

The *MinBalance* expression can be used to find an account's **minimum balance**. This amount is also in microAlgos. For example,

```
senderMinBalance = MinBalance(Txn.sender()) # get the minimum balance of the sender
↳by passing the account address (bytes)
account1MinBalance = MinBalance(Txn.accounts[1]) # get the minimum balance of Txn.
↳accounts[1] by passing the account address (bytes)
```

Additionally, *Balance* and *MinBalance* can be used together to calculate how many Algos an account can spend without closing. For example,

```
senderSpendableBalance = Balance(Txn.sender()) - MinBalance(Txn.sender()) # calculate
↳how many Algos the sender can spend
account1SpendableBalance = Balance(Txn.accounts[1]) - MinBalance(Txn.accounts[1]) #
↳calculate how many Algos Txn.accounts[1] can spend
```

13.2 Asset Holdings

In addition to Algos, the Algorand blockchain also supports additional on-chain assets called [Algorand Standard Assets \(ASAs\)](#). The *AssetHolding* group of expressions can be used to look up information about the ASAs that an account holds.

Similar to *external state expressions*, these expression return a *MaybeValue*. This value cannot be used directly, but has methods *MaybeValue.hasValue()* and *MaybeValue.value()*.

If the account has opted into the asset being looked up, *hasValue()* will return 1 and *value()* will return the value being looked up (either the asset's balance or frozen status). Otherwise, *hasValue()* and *value()* will return 0.

13.2.1 Balances

The *AssetHolding.balance* expression can be used to look up how many units of an asset an account holds. For example,

```
# get the balance of the sender for asset `Txn.assets[0]`
# if the account is not opted into that asset, returns 0
senderAssetBalance = AssetHolding.balance(Txn.sender(), Txn.assets[0])
program = Seq([
    senderAssetBalance,
    senderAssetBalance.value()
])

# get the balance of Txn.accounts[1] for asset `Txn.assets[1]`
# if the account is not opted into that asset, exit with an error
account1AssetBalance = AssetHolding.balance(Txn.accounts[1], Txn.assets[1])
program = Seq([
    account1AssetBalance,
    Assert(account1AssetBalance.hasValue()),
    account1AssetBalance.value()
])
```

13.2.2 Frozen

The *AssetHolding.frozen* expression can be used to check if an asset is frozen for an account. A value of 1 indicates frozen and 0 indicates not frozen. For example,

```
# get the frozen status of the sender for asset `Txn.assets[0]`
# if the account is not opted into that asset, returns 0
senderAssetFrozen = AssetHolding.frozen(Txn.sender(), Txn.assets[0])
program = Seq([
    senderAssetFrozen,
    senderAssetFrozen.value()
])

# get the frozen status of Txn.accounts[1] for asset `Txn.assets[1]`
# if the account is not opted into that asset, exit with an error
account1AssetFrozen = AssetHolding.frozen(Txn.accounts[1], Txn.assets[1])
program = Seq([
    account1AssetFrozen,
    Assert(account1AssetFrozen.hasValue()),
```

(continues on next page)

(continued from previous page)

```

    account1AssetFrozen.value()
  })

```

13.3 Asset Parameters

Every ASA has parameters that contain information about the asset and how it behaves. These parameters can be read by TEAL applications for any asset in the `Txn.assets` array.

The *AssetParam* group of expressions are used to access asset parameters. Like `AssetHolding`, these expressions return a *MaybeValue*.

The `hasValue()` method will return 0 only if the asset being looked up does not exist (i.e. the ID in `Txn.assets` does not represent an asset).

For optional parameters that are not set, `hasValue()` will still return 1 and `value()` will return a zero-length byte string (all optional parameters are `TealType.bytes`).

The different parameters that can be accessed are summarized by the table below. More information about each parameter can be found on the [Algorand developer website](#).

Expression	Type	Description
<code>AssetParam.total()</code>	<code>TealType.uint64</code>	The total number of units of the asset.
<code>AssetParam.decimals()</code>	<code>TealType.uint64</code>	The number of decimals the asset should be formatted with.
<code>AssetParam.defaultFrozen()</code>	<code>TealType.uint64</code>	Whether the asset is frozen by default.
<code>AssetParam.unitName()</code>	<code>TealType.bytes</code>	The name of the asset's units.
<code>AssetParam.name()</code>	<code>TealType.bytes</code>	The name of the asset.
<code>AssetParam.url()</code>	<code>TealType.bytes</code>	A URL associated with the asset.
<code>AssetParam.metadataHash()</code>	<code>TealType.bytes</code>	A 32-byte hash associated with the asset.
<code>AssetParam.manager()</code>	<code>TealType.bytes</code>	The address of the asset's manager account.
<code>AssetParam.reserve()</code>	<code>TealType.bytes</code>	The address of the asset's reserve account.
<code>AssetParam.freeze()</code>	<code>TealType.bytes</code>	The address of the asset's freeze account.
<code>AssetParam.clawback()</code>	<code>TealType.bytes</code>	The address of the asset's clawback account.

Here's an example that uses an asset parameter:

```

# get the total number of units for asset `Txn.assets[0]`
# if the asset is invalid, exit with an error
assetTotal = AssetParam.total(Txn.assets[0])

program = Seq([
    assetTotal,

```

(continues on next page)

(continued from previous page)

```
    Assert(assetTotal.hasValue()),  
    assetTotal.value()  
  ])
```

CHAPTER 14

TEAL Versions

Each version of PyTeal compiles contracts for a specific version of TEAL. Newer versions of TEAL introduce new opcodes and transaction fields, so PyTeal must be updated to support these new features. Below is a table which shows the relationship between TEAL and PyTeal versions.

TEAL Version	PyTeal Version
1	$\leq 0.5.4$
2	$\geq 0.6.0$
3	$\geq 0.7.0$
4	$\geq 0.8.0$
5	$\geq 0.9.0$
6	$\geq 0.10.0$

In order to support TEAL v2, PyTeal v0.6.0 breaks backward compatibility with v0.5.4. PyTeal programs written for PyTeal version 0.5.4 and below will not compile properly and most likely will display an error of the form `AttributeError: * object has no attribute 'teal'`.

WARNING: before updating PyTeal to a version which generates TEAL v2 contracts and fixing the programs to use the global function `compileTeal` rather than the class method `.teal()`, make sure your program abides by the TEAL safety guidelines <https://developer.algorand.org/docs/reference/teal/guidelines/>. Changing a v1 TEAL program to a v2 TEAL program without any code changes is insecure because v2 TEAL programs allow rekeying. Specifically, you must add a check that the `RekeyTo` property of any transaction is set to the zero address when updating an older PyTeal program from v0.5.4 and below.

CHAPTER 15

PyTeal Package

`pyteal.Txn = <pyteal.TxnObject object>`

The current transaction being evaluated. This is an instance of *TxnObject*.

`pyteal.Gtxn = <pyteal.TxnGroup object>`

The current group of transactions being evaluated. This is an instance of *TxnGroup*.

`pyteal.InnerTxn = <pyteal.TxnObject object>`

The most recently submitted inner transaction. This is an instance of *TxnObject*.

class `pyteal.Expr`

Bases: `abc.ABC`

Abstract base class for PyTeal expressions.

And (*other*: `pyteal.Expr`) → `pyteal.Expr`

Take the logical And of this expression and another one.

This expression must evaluate to uint64.

This is the same as using *And()* with two arguments.

Or (*other*: `pyteal.Expr`) → `pyteal.Expr`

Take the logical Or of this expression and another one.

This expression must evaluate to uint64.

This is the same as using *Or()* with two arguments.

getDefinitionTrace () → `List[str]`

has_return () → `bool`

Check if this expression always returns from the current subroutine or program.

type_of () → `pyteal.TealType`

Get the return type of this expression.

class `pyteal.LeafExpr`

Bases: `pyteal.Expr`

Leaf expression base class.

has_return()

Check if this expression always returns from the current subroutine or program.

class `pyteal.Addr` (*address: str*)

Bases: `pyteal.LeafExpr`

An expression that represents an Algorand address.

__init__ (*address: str*) → None

Create a new Addr expression.

Parameters **address** – A string containing a valid base32 Algorand address

type_of()

Get the return type of this expression.

class `pyteal.Bytes` (*arg1: Union[str, bytes, bytearray], arg2: str = None*)

Bases: `pyteal.LeafExpr`

An expression that represents a byte string.

__init__ (*arg1: Union[str, bytes, bytearray], arg2: str = None*) → None

Create a new byte string.

Depending on the encoding, there are different arguments to pass:

For UTF-8 strings: Pass the string as the only argument. For example, `Bytes("content")`.

For raw bytes or bytearray objects: Pass the bytes or bytearray as the only argument. For example, `Bytes(b"content")`.

For base16, base32, or base64 strings: Pass the base as the first argument and the string as the second argument. For example, `Bytes("base16", "636F6E74656E74")`, `Bytes("base32", "ORFDPQ6ARJK")`, `Bytes("base64", "Y29udGVudA==")`.

Special case for base16: The prefix “0x” may be present in a base16 byte string. For example, `Bytes("base16", "0x636F6E74656E74")`.

type_of()

Get the return type of this expression.

class `pyteal.Int` (*value: int*)

Bases: `pyteal.LeafExpr`

An expression that represents a uint64.

__init__ (*value: int*) → None

Create a new uint64.

Parameters **value** – The integer value this uint64 will represent. Must be a positive value less than 2^{64} .

type_of()

Get the return type of this expression.

class `pyteal.EnumInt` (*name: str*)

Bases: `pyteal.LeafExpr`

An expression that represents uint64 enum values.

__init__ (*name: str*) → None

Create an expression to reference a uint64 enum value.

Parameters **name** – The name of the enum value.

```

type_of()
    Get the return type of this expression.

class pyteal.MethodSignature(methodName: str)
    Bases: pyteal.LeafExpr

    An expression that represents an ABI method selector

    __init__(methodName: str) → None
        Create a new method selector for ABI method call.

        Parameters methodName – A string containing a valid ABI method signature

    type_of() → pyteal.TealType
        Get the return type of this expression.

class pyteal.Arg(index: Union[int, pyteal.Expr])
    Bases: pyteal.LeafExpr

    An expression to get an argument when running in signature verification mode.

    __init__(index: Union[int, pyteal.Expr]) → None
        Get an argument for this program.

        Should only be used in signature verification mode. For application mode arguments, see TxnObject.application\_args.

        Parameters index – The index of the argument to get. The index must be between 0 and 255 inclusive. Starting in TEAL v5, the index may be a PyTeal expression that evaluates to uint64.

    type_of()
        Get the return type of this expression.

class pyteal.TxnType
    Bases: object

    Enum of all possible transaction types.

    ApplicationCall = <pyteal.EnumInt object>
    AssetConfig = <pyteal.EnumInt object>
    AssetFreeze = <pyteal.EnumInt object>
    AssetTransfer = <pyteal.EnumInt object>
    KeyRegistration = <pyteal.EnumInt object>
    Payment = <pyteal.EnumInt object>
    Unknown = <pyteal.EnumInt object>

class pyteal.TxnField(id: int, name: str, type: pyteal.TealType, is_array: bool, min_version: int)
    Bases: enum.Enum

    An enumeration.

    accounts = (28, 'Accounts', <TealType.bytes: 1>, True, 2)
    amount = (8, 'Amount', <TealType.uint64: 0>, False, 2)
    application_args = (26, 'ApplicationArgs', <TealType.bytes: 1>, True, 2)
    application_id = (24, 'ApplicationID', <TealType.uint64: 0>, False, 2)
    applications = (50, 'Applications', <TealType.uint64: 0>, True, 3)

```

```
approval_program = (30, 'ApprovalProgram', <TealType.bytes: 1>, False, 2)
asset_amount = (18, 'AssetAmount', <TealType.uint64: 0>, False, 2)
asset_close_to = (21, 'AssetCloseTo', <TealType.bytes: 1>, False, 2)
asset_receiver = (20, 'AssetReceiver', <TealType.bytes: 1>, False, 2)
asset_sender = (19, 'AssetSender', <TealType.bytes: 1>, False, 2)
assets = (48, 'Assets', <TealType.uint64: 0>, True, 3)
clear_state_program = (31, 'ClearStateProgram', <TealType.bytes: 1>, False, 2)
close_remainder_to = (9, 'CloseRemainderTo', <TealType.bytes: 1>, False, 2)
config_asset = (33, 'ConfigAsset', <TealType.uint64: 0>, False, 2)
config_asset_clawback = (44, 'ConfigAssetClawback', <TealType.bytes: 1>, False, 2)
config_asset_decimals = (35, 'ConfigAssetDecimals', <TealType.uint64: 0>, False, 2)
config_asset_default_frozen = (36, 'ConfigAssetDefaultFrozen', <TealType.uint64: 0>, False, 2)
config_asset_freeze = (43, 'ConfigAssetFreeze', <TealType.bytes: 1>, False, 2)
config_asset_manager = (41, 'ConfigAssetManager', <TealType.bytes: 1>, False, 2)
config_asset_metadata_hash = (40, 'ConfigAssetMetadataHash', <TealType.bytes: 1>, False, 2)
config_asset_name = (38, 'ConfigAssetName', <TealType.bytes: 1>, False, 2)
config_asset_reserve = (42, 'ConfigAssetReserve', <TealType.bytes: 1>, False, 2)
config_asset_total = (34, 'ConfigAssetTotal', <TealType.uint64: 0>, False, 2)
config_asset_unit_name = (37, 'ConfigAssetUnitName', <TealType.bytes: 1>, False, 2)
config_asset_url = (39, 'ConfigAssetURL', <TealType.bytes: 1>, False, 2)
created_application_id = (61, 'CreatedApplicationID', <TealType.uint64: 0>, False, 5)
created_asset_id = (60, 'CreatedAssetID', <TealType.uint64: 0>, False, 5)
extra_program_pages = (56, 'ExtraProgramPages', <TealType.uint64: 0>, False, 4)
fee = (1, 'Fee', <TealType.uint64: 0>, False, 2)
first_valid = (2, 'FirstValid', <TealType.uint64: 0>, False, 2)
first_valid_time = (3, 'FirstValidTime', <TealType.uint64: 0>, False, 2)
freeze_asset = (45, 'FreezeAsset', <TealType.uint64: 0>, False, 2)
freeze_asset_account = (46, 'FreezeAssetAccount', <TealType.bytes: 1>, False, 2)
freeze_asset_frozen = (47, 'FreezeAssetFrozen', <TealType.uint64: 0>, False, 2)
global_num_byte_slices = (53, 'GlobalNumByteSlice', <TealType.uint64: 0>, False, 3)
global_num_uints = (52, 'GlobalNumUint', <TealType.uint64: 0>, False, 3)
group_index = (22, 'GroupIndex', <TealType.uint64: 0>, False, 2)
last_log = (62, 'LastLog', <TealType.bytes: 1>, False, 6)
last_valid = (4, 'LastValid', <TealType.uint64: 0>, False, 2)
lease = (6, 'Lease', <TealType.bytes: 1>, False, 2)
local_num_byte_slices = (55, 'LocalNumByteSlice', <TealType.uint64: 0>, False, 3)
```



```

local_num_uints = (54, 'LocalNumUint', <TealType.uint64: 0>, False, 3)
logs = (58, 'Logs', <TealType.bytes: 1>, True, 5)
nonparticipation = (57, 'Nonparticipation', <TealType.uint64: 0>, False, 5)
note = (5, 'Note', <TealType.bytes: 1>, False, 2)
num_accounts = (2, 'NumAccounts', <TealType.uint64: 0>, False, 2)
num_app_args = (27, 'NumAppArgs', <TealType.uint64: 0>, False, 2)
num_applications = (51, 'NumApplications', <TealType.uint64: 0>, False, 3)
num_assets = (49, 'NumAssets', <TealType.uint64: 0>, False, 3)
num_logs = (59, 'NumLogs', <TealType.uint64: 0>, False, 5)
on_completion = (25, 'OnCompletion', <TealType.uint64: 0>, False, 2)
receiver = (7, 'Receiver', <TealType.bytes: 1>, False, 2)
rekey_to = (32, 'RekeyTo', <TealType.bytes: 1>, False, 2)
selection_pk = (11, 'SelectionPK', <TealType.bytes: 1>, False, 2)
sender = (0, 'Sender', <TealType.bytes: 1>, False, 2)
state_proof_pk = (63, 'StateProofPK', <TealType.bytes: 1>, False, 6)
tx_id = (23, 'TxID', <TealType.bytes: 1>, False, 2)
type = (15, 'Type', <TealType.bytes: 1>, False, 2)
type_enum = (16, 'TypeEnum', <TealType.uint64: 0>, False, 2)
type_of() → pyteal.TealType
vote_first = (12, 'VoteFirst', <TealType.uint64: 0>, False, 2)
vote_key_dilution = (14, 'VoteKeyDilution', <TealType.uint64: 0>, False, 2)
vote_last = (13, 'VoteLast', <TealType.uint64: 0>, False, 2)
vote_pk = (10, 'VotePK', <TealType.bytes: 1>, False, 2)
xfer_asset = (17, 'XferAsset', <TealType.uint64: 0>, False, 2)

```

class `pyteal.TxnExpr` (*op: pyteal.Op, name: str, field: pyteal.TxnField*)
 Bases: `pyteal.LeafExpr`

An expression that accesses a transaction field from the current transaction.

type_of()
 Get the return type of this expression.

class `pyteal.TxnAExpr` (*staticOp: pyteal.Op, dynamicOp: Optional[pyteal.Op], name: str, field: pyteal.TxnField, index: Union[int, pyteal.Expr]*)
 Bases: `pyteal.LeafExpr`

An expression that accesses a transaction array field from the current transaction.

type_of()
 Get the return type of this expression.

class `pyteal.TxnArray` (*txnObject: pyteal.TxnObject, accessField: pyteal.TxnField, lengthField: pyteal.TxnField*)
 Bases: `pyteal.Array`

Represents a transaction array field.

`__getitem__ (index: Union[int, pyteal.Expr]) → pyteal.TxnExpr`
Get the value at a given index in this array.

`length () → pyteal.TxnExpr`
Get the length of the array.

class `pyteal.TxnObject` (`makeTxnExpr`: Callable[[`pyteal.TxnField`], `pyteal.TxnExpr`], `makeTxnExpr`: Callable[[`pyteal.TxnField`, Union[int, `pyteal.Expr`]], `pyteal.TxnExpr`])

Bases: `object`

Represents a transaction and its fields.

accounts

The accounts array in an `ApplicationCall` transaction.

Type `TxnArray`

`amount () → pyteal.TxnExpr`

Get the amount of the transaction in micro Algos.

Only set when `type_enum ()` is `TxnType.Payment`.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#amount>

application_args

Application call arguments array.

Type `TxnArray`

`application_id () → pyteal.TxnExpr`

Get the application ID from the `ApplicationCall` portion of the current transaction.

Only set when `type_enum ()` is `TxnType.ApplicationCall`.

applications

The applications array in an `ApplicationCall` transaction.

Type `TxnArray`

Requires TEAL version 3 or higher.

`approval_program () → pyteal.TxnExpr`

Get the approval program.

Only set when `type_enum ()` is `TxnType.ApplicationCall`.

`asset_amount () → pyteal.TxnExpr`

Get the amount of the asset being transferred, measured in the asset's units.

Only set when `type_enum ()` is `TxnType.AssetTransfer`.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#assetamount>

`asset_close_to () → pyteal.TxnExpr`

Get the closeout address of the asset transfer.

Only set when `type_enum ()` is `TxnType.AssetTransfer`.

For more information, see https://developer.algorand.org/docs/reference/transactions/#assetclose_to

`asset_receiver () → pyteal.TxnExpr`

Get the recipient of the asset transfer.

Only set when `type_enum ()` is `TxnType.AssetTransfer`.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#assetreceiver>

asset_sender () → pyteal.TxnExpr

Get the 32 byte address of the subject of clawback.

Only set when *type_enum()* is *TxnType.AssetTransfer*.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#assetsender>

assets

The foreign asset array in an ApplicationCall transaction.

Type *TxnArray*

Requires TEAL version 3 or higher.

clear_state_program () → pyteal.TxnExpr

Get the clear state program.

Only set when *type_enum()* is *TxnType.ApplicationCall*.

close_remainder_to () → pyteal.TxnExpr

Get the 32 byte address of the CloseRemainderTo field.

Only set when *type_enum()* is *TxnType.Payment*.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#closeremainderto>

config_asset () → pyteal.TxnExpr

Get the asset ID in asset config transaction.

Only set when *type_enum()* is *TxnType.AssetConfig*.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#configasset>

config_asset_clawback () → pyteal.TxnExpr

Get the 32 byte asset clawback address.

Only set when *type_enum()* is *TxnType.AssetConfig*.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#clawbackaddr>

config_asset_decimals () → pyteal.TxnExpr

Get the number of digits to display after the decimal place when displaying the asset.

Only set when *type_enum()* is *TxnType.AssetConfig*.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#decimals>

config_asset_default_frozen () → pyteal.TxnExpr

Check if the asset's slots are frozen by default or not.

Only set when *type_enum()* is *TxnType.AssetConfig*.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#defaultfrozen>

config_asset_freeze () → pyteal.TxnExpr

Get the 32 byte asset freeze address.

Only set when *type_enum()* is *TxnType.AssetConfig*.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#freezeaddr>

config_asset_manager () → pyteal.TxnExpr

Get the 32 byte asset manager address.

Only set when *type_enum()* is *TxnType.AssetConfig*.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#manageraddr>

config_asset_metadata_hash() → `pyteal.TxnExpr`
Get the 32 byte commitment to some unspecified asset metadata.
Only set when `type_enum()` is `TxnType.AssetConfig`.
For more information, see <https://developer.algorand.org/docs/reference/transactions/#metadatabash>

config_asset_name() → `pyteal.TxnExpr`
Get the asset name.
Only set when `type_enum()` is `TxnType.AssetConfig`.
For more information, see <https://developer.algorand.org/docs/reference/transactions/#assetname>

config_asset_reserve() → `pyteal.TxnExpr`
Get the 32 byte asset reserve address.
Only set when `type_enum()` is `TxnType.AssetConfig`.
For more information, see <https://developer.algorand.org/docs/reference/transactions/#reserveaddr>

config_asset_total() → `pyteal.TxnExpr`
Get the total number of units of this asset created.
Only set when `type_enum()` is `TxnType.AssetConfig`.
For more information, see <https://developer.algorand.org/docs/reference/transactions/#total>

config_asset_unit_name() → `pyteal.TxnExpr`
Get the unit name of the asset.
Only set when `type_enum()` is `TxnType.AssetConfig`.
For more information, see <https://developer.algorand.org/docs/reference/transactions/#unitname>

config_asset_url() → `pyteal.TxnExpr`
Get the asset URL.
Only set when `type_enum()` is `TxnType.AssetConfig`.
For more information, see <https://developer.algorand.org/docs/reference/transactions/#url>

created_application_id() → `pyteal.TxnExpr`
Get the application ID allocated by the creation of an application.
Only set when `type_enum()` is `TxnType.ApplicationCall` and this is an app creation call.
Requires TEAL version 5 or higher.

- v5 - Only works on inner transactions.
- >= v6 - Works on top-level and inner transactions.

created_asset_id() → `pyteal.TxnExpr`
Get the asset ID allocated by the creation of an ASA.
Only set when `type_enum()` is `TxnType.AssetConfig` and this is an asset creation transaction.
Requires TEAL version 5 or higher.

- v5 - Only works on inner transactions.
- >= v6 - Works on top-level and inner transactions.

extra_program_pages() → `pyteal.TxnExpr`
Get the number of additional pages for each of the application's approval and clear state programs.
1 additional page means 2048 more total bytes, or 1024 for each program.

Only set when `type_enum()` is `TxnType.ApplicationCall` and this is an app creation call.

Requires TEAL version 4 or higher.

fee() → `pyteal.TxnExpr`

Get the transaction fee in micro Algos.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#fee>

first_valid() → `pyteal.TxnExpr`

Get the first valid round number.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#firstvalid>

freeze_asset() → `pyteal.TxnExpr`

Get the asset ID being frozen or un-frozen.

Only set when `type_enum()` is `TxnType.AssetFreeze`.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#freezeasset>

freeze_asset_account() → `pyteal.TxnExpr`

Get the 32 byte address of the account whose asset slot is being frozen or un-frozen.

Only set when `type_enum()` is `TxnType.AssetFreeze`.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#freezeaccount>

freeze_asset_frozen() → `pyteal.TxnExpr`

Get the new frozen value for the asset.

Only set when `type_enum()` is `TxnType.AssetFreeze`.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#assetfrozen>

global_num_byte_slices() → `pyteal.TxnExpr`

Get the schema count of global state byte slices in an application creation call.

Only set when `type_enum()` is `TxnType.ApplicationCall` and this is an app creation call.

Requires TEAL version 3 or higher.

global_num_uints() → `pyteal.TxnExpr`

Get the schema count of global state integers in an application creation call.

Only set when `type_enum()` is `TxnType.ApplicationCall` and this is an app creation call.

Requires TEAL version 3 or higher.

group_index() → `pyteal.TxnExpr`

Get the position of the transaction within the atomic transaction group.

A stand-alone transaction is implicitly element 0 in a group of 1.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#group>

last_log() → `pyteal.TxnExpr`

A convenience method for getting the last logged message from a transaction.

Only application calls may log a message. Returns an empty string if no messages were logged.

Only set when `type_enum()` is `TxnType.ApplicationCall`.

Requires TEAL version 6 or higher.

last_valid() → `pyteal.TxnExpr`

Get the last valid round number.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#lastvalid>

lease () → pyteal.TxnExpr
Get the transaction lease.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#lease>

local_num_byte_slices () → pyteal.TxnExpr
Get the schema count of local state byte slices in an application creation call.

Only set when *type_enum()* is *TxnType.ApplicationCall* and this is an app creation call.
Requires TEAL version 3 or higher.

local_num_uints () → pyteal.TxnExpr
Get the schema count of local state integers in an application creation call.

Only set when *type_enum()* is *TxnType.ApplicationCall* and this is an app creation call.
Requires TEAL version 3 or higher.

logs
The log messages emitted by an application call.

Type *TxnArray*

Requires TEAL version 5 or higher.

- v5 - Only works on inner transactions.
- >= v6 - Works on top-level and inner transactions.

nonparticipation () → pyteal.TxnExpr
Marks an account nonparticipating for rewards.

Only set when *type_enum()* is *TxnType.KeyRegistration*.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#nonparticipation>
Requires TEAL version 5 or higher.

note () → pyteal.TxnExpr
Get the transaction note.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#note>

on_completion () → pyteal.TxnExpr
Get the on completion action from the ApplicationCall portion of the transaction.

Only set when *type_enum()* is *TxnType.ApplicationCall*.

receiver () → pyteal.TxnExpr
Get the 32 byte address of the receiver.

Only set when *type_enum()* is *TxnType.Payment*.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#receiver>

rekey_to () → pyteal.TxnExpr
Get the sender's new 32 byte AuthAddr.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#rekeyto>

selection_pk () → pyteal.TxnExpr
Get the VRF public key.

Only set when *type_enum()* is *TxnType.KeyRegistration*.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#selectionpk>

sender () → pyteal.TxnExpr

Get the 32 byte address of the sender.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#sender>

state_proof_pk () → pyteal.TxnExpr

Get the state proof public key commitment from a transaction.

Requires TEAL version 6 or higher.

tx_id () → pyteal.TxnExpr

Get the 32 byte computed ID for the transaction.

type () → pyteal.TxnExpr

Get the type of this transaction as a byte string.

In most cases it is preferable to use `type_enum()` instead.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#type>

type_enum () → pyteal.TxnExpr

Get the type of this transaction.

See `TxnType` for possible values.

vote_first () → pyteal.TxnExpr

Get the first round that the participation key is valid.

Only set when `type_enum()` is `TxnType.KeyRegistration`.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#votefirst>

vote_key_dilution () → pyteal.TxnExpr

Get the dilution for the 2-level participation key.

Only set when `type_enum()` is `TxnType.KeyRegistration`.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#votekeydilution>

vote_last () → pyteal.TxnExpr

Get the last round that the participation key is valid.

Only set when `type_enum()` is `TxnType.KeyRegistration`.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#votelast>

vote_pk () → pyteal.TxnExpr

Get the root participation public key.

Only set when `type_enum()` is `TxnType.KeyRegistration`.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#votePk>

xfer_asset () → pyteal.TxnExpr

Get the ID of the asset being transferred.

Only set when `type_enum()` is `TxnType.AssetTransfer`.

For more information, see <https://developer.algorand.org/docs/reference/transactions/#xferasset>

class pyteal.GtxnExpr (txnIndex: Union[int, pyteal.Expr], field: pyteal.TxnField)

Bases: `pyteal.TxnExpr`

An expression that accesses a transaction field from a transaction in the current group.

```
class pyteal.GtxnaExpr (txnIndex: Union[int, pyteal.Expr], field: pyteal.TxnField, index: Union[int, pyteal.Expr])
    Bases: pyteal.TxnaExpr
```

An expression that accesses a transaction array field from a transaction in the current group.

```
class pyteal.TxnGroup
    Bases: object
```

Represents a group of transactions.

```
    __getitem__ (txnIndex: Union[int, pyteal.Expr]) → pyteal.TxnObject
```

```
class pyteal.GeneratedID (txnIndex: Union[int, pyteal.Expr])
    Bases: pyteal.LeafExpr
```

An expression to obtain the ID of an asset or application created by another transaction in the current group.

```
    __init__ (txnIndex: Union[int, pyteal.Expr]) → None
```

Create an expression to extract the created ID from a transaction in the current group.

Requires TEAL version 4 or higher. This operation is only permitted in application mode.

Parameters

- **txnIndex** – The index of the transaction from which the created ID should be obtained.
- **index may be a Python int, or it may be a PyTeal expression that evaluates at (This)–**
- **If it's an expression, it must evaluate to a uint64. In all cases, the index(runtime.)–**
- **be less than the index of the current transaction. (must)–**

```
    type_of ()
```

Get the return type of this expression.

```
class pyteal.ImportScratchValue (txnIndex: Union[int, pyteal.Expr], slotId: Union[int, pyteal.Expr])
    Bases: pyteal.LeafExpr
```

An expression to load a scratch value created by another transaction in the current group

```
    __init__ (txnIndex: Union[int, pyteal.Expr], slotId: Union[int, pyteal.Expr]) → None
```

Create an expression to load a scratch space slot from a transaction in the current group.

Requires TEAL version 4 or higher. This operation is only permitted in application mode.

Parameters

- **txnIndex** – The index of the transaction from which the created ID should be obtained. This index may be a Python int, or it may be a PyTeal expression that evaluates at runtime. If it's an expression, it must evaluate to a uint64. In all cases, the index must be less than the index of the current transaction.
- **slotId** – The index of the scratch slot that should be loaded. This index may be a Python int, or it may be a PyTeal expression that evaluates at runtime. If it's an expression, it must evaluate to a uint64. In all cases, the index must be in the range [0, 256).

```
    type_of ()
```

Get the return type of this expression.

```
class pyteal.Global (field: pyteal.GlobalField)
    Bases: pyteal.LeafExpr
```


An expression that accesses a global property.

classmethod caller_app_address() → pyteal.Global

Get the address of the app that submitted the InnerTransaction that triggered this app to execute.

If not called from another app, this will return the ZeroAddress

Requires TEAL version 6 or higher.

classmethod caller_app_id() → pyteal.Global

Get the id of the app that submitted the InnerTransaction that triggered this app to execute.

If not called from another app, this will return 0

Requires TEAL version 6 or higher.

classmethod creator_address() → pyteal.Global

Address of the creator of the current application.

Fails during Signature mode. Requires TEAL version 3 or higher.

classmethod current_application_address() → pyteal.Global

Get the address of that the current application controls.

Fails during Signature mode. Requires TEAL version 5 or higher.

classmethod current_application_id() → pyteal.Global

Get the ID of the current application executing.

Fails during Signature mode.

classmethod group_id() → pyteal.Global

Get the ID of the current transaction group.

If the current transaction is not part of a group, this will return 32 zero bytes.

Requires TEAL version 5 or higher.

classmethod group_size() → pyteal.Global

Get the number of transactions in this atomic transaction group.

This will be at least 1.

classmethod latest_timestamp() → pyteal.Global

Get the latest confirmed block UNIX timestamp.

Fails if negative.

classmethod logic_sig_version() → pyteal.Global

Get the maximum supported TEAL version.

classmethod max_txn_life() → pyteal.Global

Get the maximum number of rounds a transaction can have.

classmethod min_balance() → pyteal.Global

Get the minumum balance in micro Algos.

classmethod min_txn_fee() → pyteal.Global

Get the minumum transaction fee in micro Algos.

classmethod opcode_budget() → pyteal.Global

Get the remaining opcode execution budget

Requires TEAL version 6 or higher.

classmethod round() → pyteal.Global

Get the current round number.

type_of()

Get the return type of this expression.

classmethod zero_address() → `pyteal.Global`

Get the 32 byte zero address.

class `pyteal.GlobalField`(*id: int, name: str, type: pyteal.TealType, min_version: int*)

Bases: `enum.Enum`

An enumeration.

`caller_app_address = (14, 'CallerApplicationAddress', <TealType.bytes: 1>, 6)`

`caller_app_id = (13, 'CallerApplicationID', <TealType.uint64: 0>, 6)`

`creator_address = (9, 'CreatorAddress', <TealType.bytes: 1>, 3)`

`current_app_address = (10, 'CurrentApplicationAddress', <TealType.bytes: 1>, 5)`

`current_app_id = (8, 'CurrentApplicationID', <TealType.uint64: 0>, 2)`

`group_id = (11, 'GroupID', <TealType.bytes: 1>, 5)`

`group_size = (4, 'GroupSize', <TealType.uint64: 0>, 2)`

`latest_timestamp = (7, 'LatestTimestamp', <TealType.uint64: 0>, 2)`

`logic_sig_version = (5, 'LogicSigVersion', <TealType.uint64: 0>, 2)`

`max_txn_life = (2, 'MaxTxnLife', <TealType.uint64: 0>, 2)`

`min_balance = (1, 'MinBalance', <TealType.uint64: 0>, 2)`

`min_txn_fee = (0, 'MinTxnFee', <TealType.uint64: 0>, 2)`

`opcode_budget = (12, 'OpcodeBudget', <TealType.uint64: 0>, 6)`

`round = (6, 'Round', <TealType.uint64: 0>, 2)`

type_of() → `pyteal.TealType`

`zero_address = (3, 'ZeroAddress', <TealType.bytes: 1>, 2)`

class `pyteal.App`(*field: pyteal.AppField, args*)

Bases: `pyteal.LeafExpr`

An expression related to applications.

classmethod globalDel(*key: pyteal.Expr*) → `pyteal.App`

Delete a key from the global state of the current application.

Parameters **key** – The key to delete from the global application state. Must evaluate to bytes.

classmethod globalGet(*key: pyteal.Expr*) → `pyteal.App`

Read from the global state of the current application.

Parameters **key** – The key to read from the global application state. Must evaluate to bytes.

classmethod globalGetEx(*app: pyteal.Expr, key: pyteal.Expr*) → `pyteal.MaybeValue`

Read from the global state of an application.

Parameters

- **app** – An index into `Txn.ForeignApps` that corresponds to the application to read from, must be evaluated to `uint64` (or, since v4, an application id that appears in `Txn.ForeignApps` or is the `CurrentApplicationID`, must be evaluated to `uint64`).
- **key** – The key to read from the global application state. Must evaluate to bytes.

classmethod globalPut (*key: pyteal.Expr, value: pyteal.Expr*) → *pyteal.App*

Write to the global state of the current application.

Parameters

- **key** – The key to write in the global application state. Must evaluate to bytes.
- **value** – The value to write in the global application state. Can evaluate to any type.

classmethod id () → *pyteal.Global*

Get the ID of the current running application.

This is the same as *Global.current_application_id()*.

classmethod localDel (*account: pyteal.Expr, key: pyteal.Expr*) → *pyteal.App*

Delete a key from an account's local state for the current application.

Parameters

- **account** – An index into *Txn.Accounts* that corresponds to the account to check, must be evaluated to *uint64* (or, since v4, an account address that appears in *Txn.Accounts* or is *Txn.Sender*, must be evaluated to bytes).
- **key** – The key to delete from the account's local state. Must evaluate to bytes.

classmethod localGet (*account: pyteal.Expr, key: pyteal.Expr*) → *pyteal.App*

Read from an account's local state for the current application.

Parameters

- **account** – An index into *Txn.Accounts* that corresponds to the account to check, must be evaluated to *uint64* (or, since v4, an account address that appears in *Txn.Accounts* or is *Txn.Sender*, must be evaluated to bytes).
- **key** – The key to read from the account's local state. Must evaluate to bytes.

classmethod localGetEx (*account: pyteal.Expr, app: pyteal.Expr, key: pyteal.Expr*) → *pyteal.MaybeValue*

Read from an account's local state for an application.

Parameters

- **account** – An index into *Txn.Accounts* that corresponds to the account to check, must be evaluated to *uint64* (or, since v4, an account address that appears in *Txn.Accounts* or is *Txn.Sender*, must be evaluated to bytes).
- **app** – An index into *Txn.ForeignApps* that corresponds to the application to read from, must be evaluated to *uint64* (or, since v4, an application id that appears in *Txn.ForeignApps* or is the *CurrentApplicationID*, must be evaluated to *int*).
- **key** – The key to read from the account's local state. Must evaluate to bytes.

classmethod localPut (*account: pyteal.Expr, key: pyteal.Expr, value: pyteal.Expr*) → *pyteal.App*

Write to an account's local state for the current application.

Parameters

- **account** – An index into *Txn.Accounts* that corresponds to the account to check, must be evaluated to *uint64* (or, since v4, an account address that appears in *Txn.Accounts* or is *Txn.Sender*, must be evaluated to bytes).
- **key** – The key to write in the account's local state. Must evaluate to bytes.
- **value** – The value to write in the account's local state. Can evaluate to any type.

classmethod **optedIn** (*account*: *pyteal.Expr*, *app*: *pyteal.Expr*) → *pyteal.App*

Check if an account has opted in for an application.

Parameters

- **account** – An index into *Txn.Accounts* that corresponds to the account to check, must be evaluated to *uint64* (or, since v4, an account address that appears in *Txn.Accounts* or is *Txn.Sender*, must be evaluated to *bytes*).
- **app** – An index into *Txn.ForeignApps* that corresponds to the application to read from, must be evaluated to *uint64* (or, since v4, an application id that appears in *Txn.ForeignApps* or is the *CurrentApplicationID*, must be evaluated to *int*).

type_of ()

Get the return type of this expression.

class *pyteal.AppField* (*op*: *pyteal.Op*, *type*: *pyteal.TealType*)

Bases: *enum.Enum*

Enum of app fields used to create *App* objects.

get_op () → *pyteal.Op*

globalDel = (<*Op.app_global_del*: *OpType*(value='app_global_del', mode=<*Mode.Application*:

globalGet = (<*Op.app_global_get*: *OpType*(value='app_global_get', mode=<*Mode.Application*:

globalGetEx = (<*Op.app_global_get_ex*: *OpType*(value='app_global_get_ex', mode=<*Mode.App*:

globalPut = (<*Op.app_global_put*: *OpType*(value='app_global_put', mode=<*Mode.Application*:

localDel = (<*Op.app_local_del*: *OpType*(value='app_local_del', mode=<*Mode.Application*:

localGet = (<*Op.app_local_get*: *OpType*(value='app_local_get', mode=<*Mode.Application*:

localGetEx = (<*Op.app_local_get_ex*: *OpType*(value='app_local_get_ex', mode=<*Mode.Appli*:

localPut = (<*Op.app_local_put*: *OpType*(value='app_local_put', mode=<*Mode.Application*:

optedIn = (<*Op.app_opted_in*: *OpType*(value='app_opted_in', mode=<*Mode.Application*: 2>

type_of () → *pyteal.TealType*

class *pyteal.OnComplete*

Bases: *object*

An enum of values that *TxnObject.on_completion()* may return.

ClearState = <*pyteal.EnumInt object*>

CloseOut = <*pyteal.EnumInt object*>

DeleteApplication = <*pyteal.EnumInt object*>

NoOp = <*pyteal.EnumInt object*>

OptIn = <*pyteal.EnumInt object*>

UpdateApplication = <*pyteal.EnumInt object*>

class *pyteal.AppParam*

Bases: *object*

classmethod **address** (*app*: *pyteal.Expr*) → *pyteal.MaybeValue*

Get the escrow address for the application.

Parameters **app** – An index into *Txn.ForeignApps* that correspond to the application to check. Must evaluate to *uint64*.

classmethod approvalProgram (*app: pyteal.Expr*) → *pyteal.MaybeValue*

Get the bytecode of Approval Program for the application.

Parameters *app* – An index into Txn.ForeignApps that correspond to the application to check.
Must evaluate to uint64.

classmethod clearStateProgram (*app: pyteal.Expr*) → *pyteal.MaybeValue*

Get the bytecode of Clear State Program for the application.

Parameters *app* – An index into Txn.ForeignApps that correspond to the application to check.
Must evaluate to uint64.

classmethod creator (*app: pyteal.Expr*) → *pyteal.MaybeValue*

Get the creator address for the application.

Parameters *app* – An index into Txn.ForeignApps that correspond to the application to check.
Must evaluate to uint64.

classmethod extraProgramPages (*app: pyteal.Expr*) → *pyteal.MaybeValue*

Get the number of Extra Program Pages of code space for the application.

Parameters *app* – An index into Txn.ForeignApps that correspond to the application to check.
Must evaluate to uint64.

classmethod globalNumByteSlice (*app: pyteal.Expr*) → *pyteal.MaybeValue*

Get the number of byte array values allowed in Global State for the application.

Parameters *app* – An index into Txn.ForeignApps that correspond to the application to check.
Must evaluate to uint64.

classmethod globalNumUnit (*app: pyteal.Expr*) → *pyteal.MaybeValue*

Get the number of uint64 values allowed in Global State for the application.

Parameters *app* – An index into Txn.ForeignApps that correspond to the application to check.
Must evaluate to uint64.

classmethod localNumByteSlice (*app: pyteal.Expr*) → *pyteal.MaybeValue*

Get the number of byte array values allowed in Local State for the application.

Parameters *app* – An index into Txn.ForeignApps that correspond to the application to check.
Must evaluate to uint64.

classmethod localNumUnit (*app: pyteal.Expr*) → *pyteal.MaybeValue*

Get the number of uint64 values allowed in Local State for the application.

Parameters *app* – An index into Txn.ForeignApps that correspond to the application to check.
Must evaluate to uint64.

class *pyteal.AssetHolding*

Bases: *object*

classmethod balance (*account: pyteal.Expr, asset: pyteal.Expr*) → *pyteal.MaybeValue*

Get the amount of an asset held by an account.

Parameters

- **account** – An index into Txn.Accounts that corresponds to the account to check, must be evaluated to uint64 (or, since v4, an account address that appears in Txn.Accounts or is Txn.Sender, must be evaluated to bytes).
- **asset** – The ID of the asset to get, must be evaluated to uint64 (or, since v4, a Txn.ForeignAssets offset).

classmethod frozen (*account: pyteal.Expr, asset: pyteal.Expr*) → *pyteal.MaybeValue*

Check if an asset is frozen for an account.

A value of 1 indicates frozen and 0 indicates not frozen.

Parameters

- **account** – An index into Txn.Accounts that corresponds to the account to check, must be evaluated to uint64 (or, since v4, an account address that appears in Txn.Accounts or is Txn.Sender, must be evaluated to bytes).
- **asset** – The ID of the asset to get, must be evaluated to uint64 (or, since v4, a Txn.ForeignAssets offset).

class pyteal.AssetParam

Bases: *object*

classmethod clawback (*asset: pyteal.Expr*) → *pyteal.MaybeValue*

Get the clawback address for an asset.

Parameters asset – An index into Txn.ForeignAssets that corresponds to the asset to check, must be evaluated to uint64 (or since v4, an asset ID that appears in Txn.ForeignAssets).

classmethod creator (*asset: pyteal.Expr*) → *pyteal.MaybeValue*

Get the creator address for an asset.

Parameters asset – An index into Txn.ForeignAssets that corresponds to the asset to check. Must evaluate to uint64.

classmethod decimals (*asset: pyteal.Expr*) → *pyteal.MaybeValue*

Get the number of decimals for an asset.

Parameters asset – An index into Txn.ForeignAssets that corresponds to the asset to check, must be evaluated to uint64 (or since v4, an asset ID that appears in Txn.ForeignAssets).

classmethod defaultFrozen (*asset: pyteal.Expr*) → *pyteal.MaybeValue*

Check if an asset is frozen by default.

Parameters asset – An index into Txn.ForeignAssets that corresponds to the asset to check, must be evaluated to uint64 (or since v4, an asset ID that appears in Txn.ForeignAssets).

classmethod freeze (*asset: pyteal.Expr*) → *pyteal.MaybeValue*

Get the freeze address for an asset.

Parameters asset – An index into Txn.ForeignAssets that corresponds to the asset to check, must be evaluated to uint64 (or since v4, an asset ID that appears in Txn.ForeignAssets).

classmethod manager (*asset: pyteal.Expr*) → *pyteal.MaybeValue*

Get the manager address for an asset.

Parameters asset – An index into Txn.ForeignAssets that corresponds to the asset to check, must be evaluated to uint64 (or since v4, an asset ID that appears in Txn.ForeignAssets).

classmethod metadataHash (*asset: pyteal.Expr*) → *pyteal.MaybeValue*

Get the arbitrary commitment for an asset.

If set, this will be 32 bytes long.

Parameters asset – An index into Txn.ForeignAssets that corresponds to the asset to check, must be evaluated to uint64 (or since v4, an asset ID that appears in Txn.ForeignAssets).

classmethod name (*asset: pyteal.Expr*) → *pyteal.MaybeValue*

Get the name of an asset.

Parameters *asset* – An index into Txn.ForeignAssets that corresponds to the asset to check, must be evaluated to uint64 (or since v4, an asset ID that appears in Txn.ForeignAssets).

classmethod *reserve* (*asset: pyteal.Expr*) → pyteal.MaybeValue

Get the reserve address for an asset.

Parameters *asset* – An index into Txn.ForeignAssets that corresponds to the asset to check, must be evaluated to uint64 (or since v4, an asset ID that appears in Txn.ForeignAssets).

classmethod *total* (*asset: pyteal.Expr*) → pyteal.MaybeValue

Get the total number of units of an asset.

Parameters *asset* – An index into Txn.ForeignAssets that corresponds to the asset to check, must be evaluated to uint64 (or since v4, an asset ID that appears in Txn.ForeignAssets).

classmethod *unitName* (*asset: pyteal.Expr*) → pyteal.MaybeValue

Get the unit name of an asset.

Parameters *asset* – An index into Txn.ForeignAssets that corresponds to the asset to check, must be evaluated to uint64 (or since v4, an asset ID that appears in Txn.ForeignAssets).

classmethod *url* (*asset: pyteal.Expr*) → pyteal.MaybeValue

Get the URL of an asset.

Parameters *asset* – An index into Txn.ForeignAssets that corresponds to the asset to check, must be evaluated to uint64 (or since v4, an asset ID that appears in Txn.ForeignAssets).

class *pyteal.AccountParam*

Bases: object

classmethod *authAddr* (*acct: pyteal.Expr*) → pyteal.MaybeValue

Get the authorizing address for an account. If the account is not rekeyed, the empty address is returned.

Parameters *acct* – An index into Txn.accounts that corresponds to the application to check or an address available at runtime. May evaluate to uint64 or an address.

classmethod *balance* (*acct: pyteal.Expr*) → pyteal.MaybeValue

Get the current balance in microalgos an account.

Parameters *acct* – An index into Txn.accounts that corresponds to the application to check or an address available at runtime. May evaluate to uint64 or an address.

classmethod *minBalance* (*acct: pyteal.Expr*) → pyteal.MaybeValue

Get the minimum balance in microalgos for an account.

Parameters *acct* – An index into Txn.accounts that corresponds to the application to check or an address available at runtime. May evaluate to uint64 or an address.

class *pyteal.InnerTxnBuilder*

Bases: object

This class represents expressions used to create, modify, and submit inner transactions.

Inner transactions are transactions which applications can dynamically create. Each inner transaction will appear as a transaction inside of the current transaction being executed.

As of TEAL version 5, only the transaction types *TxnType.Payment*, *TxnType.AssetTransfer*, *TxnType.AssetConfig*, and *TxnType.AssetFreeze* are allowed. Additionally, not all fields are allowed to be set. For example, it is not currently allowed to set the *rekeyTo* field of an inner transaction.

classmethod *Begin* () → pyteal.Expr

Begin preparation of a new inner transaction.

This new inner transaction is initialized with its sender to the application address (*Global.current_application_address*); fee to the minimum allowable, taking into account *MinTxnFee* and credit from overpaying in earlier transactions; *FirstValid/LastValid* to the values in the top-level transaction, and all other fields to zero values.

Requires TEAL version 5 or higher. This operation is only permitted in application mode.

classmethod `Next ()` → `pyteal.Expr`

Begin preparation of a new inner transaction (in the same transaction group).

This new inner transaction is initialized with its sender to the application address (*Global.current_application_address*); fee to the minimum allowable, taking into account *MinTxnFee* and credit from overpaying in earlier transactions; *FirstValid/LastValid* to the values in the top-level transaction, and all other fields to zero values.

Requires TEAL version 6 or higher. This operation is only permitted in application mode.

classmethod `SetField (field: pyteal.TxnField, value: Union[pyteal.Expr, List[pyteal.Expr]])` → `pyteal.Expr`

Set a field of the current inner transaction.

InnerTxnBuilder.Begin must be called before setting any fields on an inner transaction.

Note: For non-array field (e.g., note), setting it twice will overwrite the original value. While for array field (e.g., accounts), setting it multiple times will append the values.

Requires TEAL version 5 or higher. This operation is only permitted in application mode.

Parameters

- **field** – The field to set on the inner transaction.
- **value** – The value to that the field should take. This must evaluate to a type that is compatible with the field being set.

classmethod `SetFields (fields: Dict[pyteal.TxnField, Union[pyteal.Expr, List[pyteal.Expr]]])` → `pyteal.Expr`

Set multiple fields of the current inner transaction.

InnerTxnBuilder.Begin must be called before setting any fields on an inner transaction.

Note: For non-array field (e.g., note), setting it twice will overwrite the original value. While for array field (e.g., accounts), setting it multiple times will append the values.

Requires TEAL version 5 or higher. This operation is only permitted in application mode.

Parameters fields – A dictionary whose keys are fields to set and whose values are the value each field should take. Each value must evaluate to a type that is compatible with the field being set.

classmethod `Submit ()` → `pyteal.Expr`

Execute the current inner transaction.

InnerTxnBuilder.Begin and *InnerTxnBuilder.SetField* must be called before submitting an inner transaction.

This will fail if 256 inner transactions have already been executed, or if the inner transaction itself fails. Upon failure, the current program will immediately exit and fail as well.

If the inner transaction is successful, then its effects can be immediately observed by this program with stateful expressions such as *Balance*. Additionally, the fields of the most recently submitted inner transaction can be examined using the *InnerTxn* object. If the inner transaction creates an asset, the new asset ID can be found by looking at *InnerTxn.created_asset_id()*.

Requires TEAL version 5 or higher. This operation is only permitted in application mode.

```
class pyteal.InnerTxnAction
```

```
Bases: enum.Enum
```

An enumeration.

```
Begin = <Op.itxn_begin: OpType(value='itxn_begin', mode=<Mode.Application: 2>, min_v
```

```
Next = <Op.itxn_next: OpType(value='itxn_next', mode=<Mode.Application: 2>, min_vers
```

```
Submit = <Op.itxn_submit: OpType(value='itxn_submit', mode=<Mode.Application: 2>, mi
```

```
class pyteal.GitxnExpr(txnIndex: int, field: pyteal.TxnField)
```

```
Bases: pyteal.TxnExpr
```

An expression that accesses an inner transaction field from an inner transaction in the last inner group.

```
class pyteal.GitxnaExpr(txnIndex: int, field: pyteal.TxnField, index: Union[int, pyteal.Expr])
```

```
Bases: pyteal.TxnaExpr
```

An expression that accesses an inner transaction array field from an inner transaction in the last inner group.

```
class pyteal.InnerTxnGroup
```

```
Bases: object
```

Represents a group of inner transactions.

```
__getitem__(txnIndex: int) → pyteal.TxnObject
```

```
class pyteal.Array
```

```
Bases: abc.ABC
```

Represents a variable length array of objects.

```
__getitem__(index: int)
```

Get the value at a given index in this array.

```
length() → pyteal.Expr
```

Get the length of the array.

```
class pyteal.Tmpl(op: pyteal.Op, type: pyteal.TealType, name: str)
```

```
Bases: pyteal.LeafExpr
```

Template expression for creating placeholder values.

```
classmethod Addr(placeholder: str)
```

Create a new Addr template.

Parameters placeholder – The name to use for this template variable. Must start with *TMPL_* and only consist of uppercase alphanumeric characters and underscores.

```
classmethod Bytes(placeholder: str)
```

Create a new Bytes template.

Parameters placeholder – The name to use for this template variable. Must start with *TMPL_* and only consist of uppercase alphanumeric characters and underscores.

```
classmethod Int(placeholder: str)
```

Create a new Int template.

Parameters placeholder – The name to use for this template variable. Must start with *TMPL_* and only consist of uppercase alphanumeric characters and underscores.

```
type_of()
```

Get the return type of this expression.

class `pyteal.Nonce` (*base: str, nonce: str, child: pyteal.Expr*)

Bases: `pyteal.Expr`

A meta expression only used to change the hash of a TEAL program.

__init__ (*base: str, nonce: str, child: pyteal.Expr*) → None

Create a new Nonce.

The Nonce expression behaves exactly like the child expression passed into it, except it uses the provided nonce string to alter its structure in a way that does not affect execution.

Parameters

- **base** – The base of the nonce. Must be one of utf8, base16, base32, or base64.
- **nonce** – An arbitrary nonce string that conforms to base.
- **child** – The expression to wrap.

has_return ()

Check if this expression always returns from the current subroutine or program.

type_of ()

Get the return type of this expression.

class `pyteal.UnaryExpr` (*op: pyteal.Op, inputType: pyteal.TealType, outputType: pyteal.TealType, arg: pyteal.Expr*)

Bases: `pyteal.Expr`

An expression with a single argument.

has_return ()

Check if this expression always returns from the current subroutine or program.

type_of ()

Get the return type of this expression.

`pyteal.Btoi` (*arg: pyteal.Expr*) → `pyteal.UnaryExpr`

Convert a byte string to a uint64.

`pyteal.Itob` (*arg: pyteal.Expr*) → `pyteal.UnaryExpr`

Convert a uint64 string to a byte string.

`pyteal.Len` (*arg: pyteal.Expr*) → `pyteal.UnaryExpr`

Get the length of a byte string.

`pyteal.BitLen` (*arg: pyteal.Expr*) → `pyteal.UnaryExpr`

Get the index of the highest nonzero bit in an integer.

If the argument is 0, 0 will be returned.

If the argument is a byte array, it is interpreted as a big-endian unsigned integer.

Requires TEAL version 4 or higher.

`pyteal.Sha256` (*arg: pyteal.Expr*) → `pyteal.UnaryExpr`

Get the SHA-256 hash of a byte string.

`pyteal.Sha512_256` (*arg: pyteal.Expr*) → `pyteal.UnaryExpr`

Get the SHA-512/256 hash of a byte string.

`pyteal.Keccak256` (*arg: pyteal.Expr*) → `pyteal.UnaryExpr`

Get the KECCAK-256 hash of a byte string.

`pyteal.Not (arg: pyteal.Expr) → pyteal.UnaryExpr`

Get the logical inverse of a uint64.

If the argument is 0, then this will produce 1. Otherwise this will produce 0.

`pyteal.BitwiseNot (arg: pyteal.Expr) → pyteal.UnaryExpr`

Get the bitwise inverse of a uint64.

Produces \sim arg.

`pyteal.Sqrt (arg: pyteal.Expr) → pyteal.UnaryExpr`

Get the integer square root of a uint64.

This will return the largest integer X such that $X^2 \leq \text{arg}$.

Requires TEAL version 4 or higher.

`pyteal.Pop (arg: pyteal.Expr) → pyteal.UnaryExpr`

Pop a value from the stack.

`pyteal.Balance (account: pyteal.Expr) → pyteal.UnaryExpr`

Get the balance of a user in microAlgos.

Argument must be an index into Txn.Accounts that corresponds to the account to read from, must be evaluated to uint64 (or, since v4, an account address that appears in Txn.Accounts or is Txn.Sender).

This operation is only permitted in application mode.

`pyteal.MinBalance (account: pyteal.Expr) → pyteal.UnaryExpr`

Get the minimum balance of a user in microAlgos.

For more information about minimum balances, see: <https://developer.algorand.org/docs/features/accounts/#minimum-balance>

Argument must be an index into Txn.Accounts that corresponds to the account to read from, must be evaluated to uint64 (or, since v4, an account address that appears in Txn.Accounts or is Txn.Sender).

Requires TEAL version 3 or higher. This operation is only permitted in application mode.

class `pyteal.BinaryExpr (op: pyteal.Op, inputType: Union[pyteal.TealType, Tuple[pyteal.TealType, pyteal.TealType]], outputType: pyteal.TealType, argLeft: pyteal.Expr, argRight: pyteal.Expr)`

Bases: `pyteal.Expr`

An expression with two arguments.

has_return ()

Check if this expression always returns from the current subroutine or program.

type_of ()

Get the return type of this expression.

`pyteal.Add (left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`

Add two numbers.

Produces left + right.

Parameters

- **left** – Must evaluate to uint64.
- **right** – Must evaluate to uint64.

`pyteal.Minus (left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`

Subtract two numbers.

Produces left - right.

Parameters

- **left** – Must evaluate to uint64.
- **right** – Must evaluate to uint64.

`pyteal.Mul (left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`
Multiply two numbers.

Produces `left * right`.

Parameters

- **left** – Must evaluate to uint64.
- **right** – Must evaluate to uint64.

`pyteal.Div (left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`
Divide two numbers.

Produces `left / right`.

Parameters

- **left** – Must evaluate to uint64.
- **right** – Must evaluate to uint64.

`pyteal.Mod (left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`
Modulo expression.

Produces `left % right`.

Parameters

- **left** – Must evaluate to uint64.
- **right** – Must evaluate to uint64.

`pyteal.Exp (a: pyteal.Expr, b: pyteal.Expr) → pyteal.BinaryExpr`
Exponential expression.

Produces `a ** b`.

Requires TEAL version 4 or higher.

Parameters

- **a** – Must evaluate to uint64.
- **b** – Must evaluate to uint64.

`pyteal.Divw (hi: pyteal.Expr, lo: pyteal.Expr, y: pyteal.Expr) → pyteal.TernaryExpr`
Performs wide division by interpreting *hi* and *lo* as a uint128 value.

Requires TEAL version 6 or higher.

Parameters

- **hi** – Quotient's high 64 bits. Must evaluate to uint64.
- **lo** – Quotient's low 64 bits. Must evaluate to uint64.
- **y** – Divisor. Must evaluate to uint64.

`pyteal.BitwiseAnd (left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`
Bitwise and expression.

Produces `left & right`.

Parameters

- **left** – Must evaluate to uint64.
- **right** – Must evaluate to uint64.

`pyteal.BitwiseOr(left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`

Bitwise or expression.

Produces $\text{left} \mid \text{right}$.

Parameters

- **left** – Must evaluate to uint64.
- **right** – Must evaluate to uint64.

`pyteal.BitwiseXor(left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`

Bitwise xor expression.

Produces $\text{left} \wedge \text{right}$.

Parameters

- **left** – Must evaluate to uint64.
- **right** – Must evaluate to uint64.

`pyteal.ShiftLeft(a: pyteal.Expr, b: pyteal.Expr) → pyteal.BinaryExpr`

Bitwise left shift expression.

Produces $a \ll b$. This is equivalent to a times 2^b , modulo 2^{64} .

Requires TEAL version 4 or higher.

Parameters

- **a** – Must evaluate to uint64.
- **b** – Must evaluate to uint64.

`pyteal.ShiftRight(a: pyteal.Expr, b: pyteal.Expr) → pyteal.BinaryExpr`

Bitwise right shift expression.

Produces $a \gg b$. This is equivalent to a divided by 2^b .

Requires TEAL version 4 or higher.

Parameters

- **a** – Must evaluate to uint64.
- **b** – Must evaluate to uint64.

`pyteal.Eq(left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`

Equality expression.

Checks if $\text{left} == \text{right}$.

Parameters

- **left** – A value to check.
- **right** – The other value to check. Must evaluate to the same type as left.

`pyteal.Neq(left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`

Difference expression.

Checks if $\text{left} != \text{right}$.

Parameters

- **left** – A value to check.
- **right** – The other value to check. Must evaluate to the same type as left.

`pyteal.Lt (left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`

Less than expression.

Checks if left < right.

Parameters

- **left** – Must evaluate to uint64.
- **right** – Must evaluate to uint64.

`pyteal.Le (left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`

Less than or equal to expression.

Checks if left <= right.

Parameters

- **left** – Must evaluate to uint64.
- **right** – Must evaluate to uint64.

`pyteal.Gt (left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`

Greater than expression.

Checks if left > right.

Parameters

- **left** – Must evaluate to uint64.
- **right** – Must evaluate to uint64.

`pyteal.Ge (left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`

Greater than or equal to expression.

Checks if left >= right.

Parameters

- **left** – Must evaluate to uint64.
- **right** – Must evaluate to uint64.

`pyteal.GetBit (value: pyteal.Expr, index: pyteal.Expr) → pyteal.BinaryExpr`

Get the bit value of an expression at a specific index.

The meaning of index differs if value is an integer or a byte string.

- For integers, bit indexing begins with low-order bits. For example, `GetBit(Int(16), Int(4))` yields 1. Any other valid index would yield a bit value of 0. Any integer less than 64 is a valid index.
- For byte strings, bit indexing begins at the first byte. For example, `GetBit(Bytes("base16", "0xf0"), Int(0))` yields 1. Any index less than 4 would yield 1, and any valid index 4 or greater would yield 0. Any integer less than `8*Len(value)` is a valid index.

Requires TEAL version 3 or higher.

Parameters

- **value** – The value containing bits. Can evaluate to any type.
- **index** – The index of the bit to extract. Must evaluate to uint64.

`pyteal.GetByte (value: pyteal.Expr, index: pyteal.Expr) → pyteal.BinaryExpr`
Extract a single byte as an integer from a byte string.

Similar to `GetBit`, indexing begins at the first byte. For example, `GetByte(Bytes("base16", "0xff0000"), Int(0))` yields 255. Any other valid index would yield 0.

Requires TEAL version 3 or higher.

Parameters

- **value** – The value containing the bytes. Must evaluate to bytes.
- **index** – The index of the byte to extract. Must evaluate to an integer less than `Len(value)`.

`pyteal.Ed25519Verify (data: pyteal.Expr, sig: pyteal.Expr, key: pyteal.Expr) → pyteal.TernaryExpr`
Verify the ed25519 signature of the concatenation (“ProgData” + `hash_of_current_program` + `data`).

Parameters

- **data** – The data signed by the public key. Must evaluate to bytes.
- **sig** – The proposed 64-byte signature of the concatenation (“ProgData” + `hash_of_current_program` + `data`). Must evaluate to bytes.
- **key** – The 32 byte public key that produced the signature. Must evaluate to bytes.

`pyteal.Substring (string: pyteal.Expr, start: pyteal.Expr, end: pyteal.Expr) → pyteal.Expr`
Take a substring of a byte string.

Produces a new byte string consisting of the bytes starting at `start` up to but not including `end`.

This expression is similar to `Extract`, except this expression uses start and end indexes, while `Extract` uses a start index and length.

Requires TEAL version 2 or higher.

Parameters

- **string** – The byte string.
- **start** – The starting index for the substring. Must be an integer less than or equal to `Len(string)`.
- **end** – The ending index for the substring. Must be an integer greater or equal to `start`, but less than or equal to `Len(string)`.

`pyteal.Extract (string: pyteal.Expr, start: pyteal.Expr, length: pyteal.Expr) → pyteal.Expr`
Extract a section of a byte string.

Produces a new byte string consisting of the bytes starting at `start` up to but not including `start + length`.

This expression is similar to `Substring`, except this expression uses a start index and length, while `Substring` uses start and end indexes.

Requires TEAL version 5 or higher.

Parameters

- **string** – The byte string.
- **start** – The starting index for the extraction. Must be an integer less than or equal to `Len(string)`.
- **length** – The number of bytes to extract. Must be an integer such that `start + length ≤ Len(string)`.

`pyteal.Suffix` (*string*: `pyteal.Expr`, *start*: `pyteal.Expr`) → `pyteal.Expr`

Take a suffix of a byte string.

Produces a new byte string consisting of the suffix of the byte string starting at *start*

This expression is similar to *Substring* and *Extract*, except this expression only uses a start index.

Requires TEAL version 5 or higher.

Parameters

- **string** – The byte string.
- **start** – The starting index for the suffix. Must be an integer less than or equal to `Len(string)`.

`pyteal.SetBit` (*value*: `pyteal.Expr`, *index*: `pyteal.Expr`, *newBitValue*: `pyteal.Expr`) → `pyteal.TernaryExpr`

Set the bit value of an expression at a specific index.

The meaning of index differs if *value* is an integer or a byte string.

- For integers, bit indexing begins with low-order bits. For example, `SetBit(Int(0), Int(4), Int(1))` yields the integer 16 (2^4). Any integer less than 64 is a valid index.
- For byte strings, bit indexing begins at the first byte. For example, `SetBit(Bytes("base16", "0x00"), Int(7), Int(1))` yields the byte string 0x01. Any integer less than $8 * \text{Len}(\text{value})$ is a valid index.

Requires TEAL version 3 or higher.

Parameters

- **value** – The value containing bits. Can evaluate to any type.
- **index** – The index of the bit to set. Must evaluate to `uint64`.
- **newBitValue** – The new bit value to set. Must evaluate to the integer 0 or 1.

`pyteal.SetByte` (*value*: `pyteal.Expr`, *index*: `pyteal.Expr`, *newByteValue*: `pyteal.Expr`) → `pyteal.TernaryExpr`

Set a single byte in a byte string from an integer value.

Similar to `SetBit`, indexing begins at the first byte. For example, `SetByte(Bytes("base16", "0x000000"), Int(0), Int(255))` yields the byte string 0xff0000.

Requires TEAL version 3 or higher.

Parameters

- **value** – The value containing the bytes. Must evaluate to bytes.
- **index** – The index of the byte to set. Must evaluate to an integer less than `Len(value)`.
- **newByteValue** – The new byte value to set. Must evaluate to an integer less than 256.

class `pyteal.NaryExpr` (*op*: `pyteal.Op`, *inputType*: `pyteal.TealType`, *outputType*: `pyteal.TealType`, *args*: `Sequence[pyteal.Expr]`)

Bases: `pyteal.Expr`

N-ary expression base class.

This type of expression takes an arbitrary number of arguments.

has_return ()

Check if this expression always returns from the current subroutine or program.

type_of ()

Get the return type of this expression.

`pyteal.And(*args) → pyteal.NaryExpr`

Logical and expression.

Produces 1 if all arguments are nonzero. Otherwise produces 0.

All arguments must be PyTeal expressions that evaluate to uint64, and there must be at least one argument.

Example

```
And(Txn.amount() == Int(500), Txn.fee() <= Int(10))
```

`pyteal.Or(*args) → pyteal.NaryExpr`

Logical or expression.

Produces 1 if any argument is nonzero. Otherwise produces 0.

All arguments must be PyTeal expressions that evaluate to uint64, and there must be at least one argument.

`pyteal.Concat(*args) → pyteal.NaryExpr`

Concatenate byte strings.

Produces a new byte string consisting of the contents of each of the passed in byte strings joined together.

All arguments must be PyTeal expressions that evaluate to bytes, and there must be at least one argument.

Example

```
Concat(Bytes("hello"), Bytes(" "), Bytes("world"))
```

class `pyteal.WideRatio` (*numeratorFactors: List[pyteal.Expr], denominatorFactors: List[pyteal.Expr]*)

Bases: `pyteal.Expr`

A class used to calculate expressions of the form $(N_1 * N_2 * N_3 * \dots) / (D_1 * D_2 * D_3 * \dots)$

Use this class if all inputs to the expression are uint64s, the output fits in a uint64, and all intermediate values fit in a uint128.

__init__ (*numeratorFactors: List[pyteal.Expr], denominatorFactors: List[pyteal.Expr]*) → None

Create a new WideRatio expression with the given numerator and denominator factors.

This will calculate $(N_1 * N_2 * N_3 * \dots) / (D_1 * D_2 * D_3 * \dots)$, where each N_i represents an element in `numeratorFactors` and each D_i represents an element in `denominatorFactors`.

Requires TEAL version 5 or higher.

Parameters

- **numeratorFactors** – The factors in the numerator of the ratio. This list must have at least 1 element. If this list has exactly 1 element, then `denominatorFactors` must have more than 1 element (otherwise basic division should be used).
- **denominatorFactors** – The factors in the denominator of the ratio. This list must have at least 1 element.

has_return ()

Check if this expression always returns from the current subroutine or program.

type_of ()

Get the return type of this expression.

```
class pyteal.If (cond: pyteal.Expr, thenBranch: pyteal.Expr = None, elseBranch: pyteal.Expr = None)
    Bases: pyteal.Expr
```

Simple two-way conditional expression.

```
Else (elseBranch: pyteal.Expr)
```

```
ElseIf (cond)
```

```
Then (thenBranch: pyteal.Expr)
```

```
__init__ (cond: pyteal.Expr, thenBranch: pyteal.Expr = None, elseBranch: pyteal.Expr = None) → None
    Create a new If expression.
```

When this If expression is executed, the condition will be evaluated, and if it produces a true value, thenBranch will be executed and used as the return value for this expression. Otherwise, elseBranch will be executed and used as the return value, if it is provided.

Parameters

- **cond** – The condition to check. Must evaluate to uint64.
- **thenBranch** – Expression to evaluate if the condition is true.
- **elseBranch** (*optional*) – Expression to evaluate if the condition is false. Must evaluate to the same type as thenBranch, if provided. Defaults to None.

```
has_return ()
```

Check if this expression always returns from the current subroutine or program.

```
type_of ()
```

Get the return type of this expression.

```
class pyteal.Cond (*argv)
```

Bases: *pyteal.Expr*

A chainable branching expression that supports an arbitrary number of conditions.

```
__init__ (*argv)
    Create a new Cond expression.
```

At least one argument must be provided, and each argument must be a list with two elements. The first element is a condition which evaluates to uint64, and the second is the body of the condition, which will execute if that condition is true. All condition bodies must have the same return type. During execution, each condition is tested in order, and the first condition to evaluate to a true value will cause its associated body to execute and become the value for this Cond expression. If no condition evaluates to a true value, the Cond expression produces an error and the TEAL program terminates.

Example

```
Cond([Global.group_size() == Int(5), bid],
     [Global.group_size() == Int(4), redeem],
     [Global.group_size() == Int(1), wrapup])
```

```
has_return ()
```

Check if this expression always returns from the current subroutine or program.

```
type_of ()
```

Get the return type of this expression.

class `pyteal.Seq(*exprs)`

Bases: `pyteal.Expr`

A control flow expression to represent a sequence of expressions.

__init__ (**exprs*)

Create a new Seq expression.

The new Seq expression will take on the return value of the final expression in the sequence.

Parameters *exprs* – The expressions to include in this sequence. All expressions that are not the final one in this list must not return any values.

Example

```
Seq([
    App.localPut(Bytes("key"), Bytes("value")),
    Int(1)
])
```

has_return ()

Check if this expression always returns from the current subroutine or program.

type_of ()

Get the return type of this expression.

class `pyteal.Assert(cond: pyteal.Expr)`

Bases: `pyteal.Expr`

A control flow expression to verify that a condition is true.

__init__ (*cond*: `pyteal.Expr`) → None

Create an assert statement that raises an error if the condition is false.

Parameters *cond* – The condition to check. Must evaluate to a uint64.

has_return ()

Check if this expression always returns from the current subroutine or program.

type_of ()

Get the return type of this expression.

class `pyteal.Err`

Bases: `pyteal.Expr`

Expression that causes the program to immediately fail when executed.

has_return ()

Check if this expression always returns from the current subroutine or program.

type_of ()

Get the return type of this expression.

class `pyteal.Return(value: pyteal.Expr = None)`

Bases: `pyteal.Expr`

Return a value from the current execution context.

__init__ (*value*: `pyteal.Expr` = None) → None

Create a new Return expression.

If called from the main program, this will immediately exit the program and the value returned will be the program's success value (must be a uint64, 0 indicates failure, 1 or greater indicates success).

If called from within a subroutine, this will return from the current subroutine with either no value if the subroutine does not produce a return value, or the given return value if it does produce a return value.

has_return()

Check if this expression always returns from the current subroutine or program.

type_of()

Get the return type of this expression.

pyteal.Approve() → *pyteal.Expr*

Immediately exit the program and mark the execution as successful.

pyteal.Reject() → *pyteal.Expr*

Immediately exit the program and mark the execution as unsuccessful.

class pyteal.Subroutine (*returnType: pyteal.TealType, name: str = None*)

Bases: object

Used to create a PyTeal subroutine from a Python function.

This class is meant to be used as a function decorator. For example:

```
@Subroutine(TealType.uint64)
def mySubroutine(a: Expr, b: Expr) -> Expr:
    return a + b

program = Seq([
    App.globalPut(Bytes("key"), mySubroutine(Int(1), Int(2))),
    Approve(),
])
```

__init__ (*returnType: pyteal.TealType, name: str = None*) → None

Define a new subroutine with the given return type.

Parameters returnType – The type that the return value of this subroutine must conform to. *TealType.none* indicates that this subroutine does not return any value.

class pyteal.SubroutineDefinition (*implementation: Callable[[...], pyteal.Expr], returnType: pyteal.TealType, nameStr: str = None*)

Bases: object

argumentCount () → int

getDeclaration () → *pyteal.SubroutineDeclaration*

invoke (*args: List[pyteal.Expr]*) → *pyteal.SubroutineCall*

name () → str

nextSubroutineId = 0

class pyteal.SubroutineDeclaration (*subroutine: pyteal.SubroutineDefinition, body: pyteal.Expr*)

Bases: *pyteal.Expr*

has_return ()

Check if this expression always returns from the current subroutine or program.

type_of ()

Get the return type of this expression.

class pyteal.SubroutineCall (*subroutine: pyteal.SubroutineDefinition, args: List[pyteal.Expr]*)

Bases: *pyteal.Expr*

has_return()

Check if this expression always returns from the current subroutine or program.

type_of()

Get the return type of this expression.

class `pyteal.SubroutineFnWrapper` (*fnImplementation: Callable[[...], pyteal.Expr], returnType: pyteal.TealType, name: str = None*)

Bases: object

has_return()

name() → str

type_of()

class `pyteal.ScratchSlot` (*requestedSlotId: int = None*)

Bases: object

Represents the allocation of a scratch space slot.

__init__ (*requestedSlotId: int = None*)

Initializes a scratch slot with a particular id

Parameters

- **requestedSlotId** (*optional*) – A scratch slot id that the compiler must store the value.
- **id may be a Python int in the range [0–256) (This) –**

load (*type: pyteal.TealType = <TealType.anytype: 2>*) → `pyteal.ScratchLoad`

Get an expression to load a value from this slot.

Parameters type (*optional*) – The type being loaded from this slot, if known. Defaults to `TealType.anytype`.

nextSlotId = 256

store (*value: pyteal.Expr = None*) → `pyteal.Expr`

Get an expression to store a value in this slot.

Parameters

- **value** (*optional*) – The value to store in this slot. If not included, the last value on
- **stack will be stored. NOTE** (*the*) – storing the last value on the stack breaks the typical
- **of PyTeal, only use if you know what you're doing.** (*semantics*) –

class `pyteal.ScratchLoad` (*slot: pyteal.ScratchSlot, type: pyteal.TealType = <TealType.anytype: 2>*)

Bases: `pyteal.Expr`

Expression to load a value from scratch space.

__init__ (*slot: pyteal.ScratchSlot, type: pyteal.TealType = <TealType.anytype: 2>*)

Create a new `ScratchLoad` expression.

Parameters

- **slot** – The slot to load the value from.
- **type** (*optional*) – The type being loaded from this slot, if known. Defaults to `TealType.anytype`.

has_return()

Check if this expression always returns from the current subroutine or program.

type_of()

Get the return type of this expression.

class `pyteal.ScratchStore` (*slot: pyteal.ScratchSlot, value: pyteal.Expr*)

Bases: `pyteal.Expr`

Expression to store a value in scratch space.

__init__ (*slot: pyteal.ScratchSlot, value: pyteal.Expr*)

Create a new ScratchStore expression.

Parameters

- **slot** – The slot to store the value in.
- **value** – The value to store.

has_return()

Check if this expression always returns from the current subroutine or program.

type_of()

Get the return type of this expression.

class `pyteal.ScratchStackStore` (*slot: pyteal.ScratchSlot*)

Bases: `pyteal.Expr`

Expression to store a value from the stack in scratch space.

NOTE: This expression breaks the typical semantics of PyTeal, only use if you know what you're doing.

__init__ (*slot: pyteal.ScratchSlot*)

Create a new ScratchStackStore expression.

Parameters **slot** – The slot to store the value in.

has_return()

Check if this expression always returns from the current subroutine or program.

type_of()

Get the return type of this expression.

class `pyteal.ScratchVar` (*type: pyteal.TealType = <TealType.anytype: 2>, slotId: int = None*)

Bases: `object`

Interface around Scratch space, similar to get/put local/global state

Example

```
myvar = ScratchVar(TealType.uint64)
Seq([
    myvar.store(Int(5)),
    Assert(myvar.load() == Int(5))
])
```

__init__ (*type: pyteal.TealType = <TealType.anytype: 2>, slotId: int = None*)

Create a new ScratchVar with an optional type.

Parameters

- **type** (*optional*) – The type that this variable can hold. An error will be thrown if an expression with an incompatible type is stored in this variable. Defaults to `TealType.anytype`.
- **slotId** (*optional*) – A scratch slot id that the compiler must store the value. This id may be a Python int in the range [0-256).

load () → `pyteal.ScratchLoad`

Load value from Scratch Space

storage_type () → `pyteal.TealType`

Get the type of expressions that can be stored in this `ScratchVar`.

store (*value: pyteal.Expr*) → `pyteal.Expr`

Store value in Scratch Space

Parameters value – The value to store. Must conform to this `ScratchVar`'s type.

class `pyteal.MaybeValue` (*op: pyteal.Op, type: pyteal.TealType, *, immediate_args: List[Union[str, int]] = None, args: List[pyteal.Expr] = None*)

Bases: `pyteal.MultiValue`

Represents a get operation returning a value that may not exist.

__init__ (*op: pyteal.Op, type: pyteal.TealType, *, immediate_args: List[Union[str, int]] = None, args: List[pyteal.Expr] = None*)

Create a new `MaybeValue`.

Parameters

- **op** – The operation that returns values.
- **type** – The type of the returned value.
- **immediate_args** (*optional*) – Immediate arguments for the op. Defaults to `None`.
- **args** (*optional*) – Stack arguments for the op. Defaults to `None`.

hasValue () → `pyteal.ScratchLoad`

Check if the value exists.

This will return 1 if the value exists, otherwise 0.

slotOk

Get the scratch slot that stores `hasValue`.

Note: This is mainly added for backwards compatability and normally shouldn't be used directly in `pyteal` code.

slotValue

Get the scratch slot that stores the value or the zero value for the type if the value doesn't exist.

Note: This is mainly added for backwards compatability and normally shouldn't be used directly in `pyteal` code.

value () → `pyteal.ScratchLoad`

Get the value.

If the value exists, it will be returned. Otherwise, the zero value for this type will be returned (i.e. either 0 or an empty byte string, depending on the type).

class `pyteal.MultiValue` (*op: pyteal.Op, types: List[pyteal.TealType], *, immediate_args: List[Union[str, int]] = None, args: List[pyteal.Expr] = None*)

Bases: `pyteal.LeafExpr`

Represents an operation that returns more than one value

`__init__` (*op*: *pyteal.Op*, *types*: *List[pyteal.TealType]*, *, *immediate_args*: *List[Union[str, int]]* = *None*, *args*: *List[pyteal.Expr]* = *None*)
Create a new MultiValue.

Parameters

- **op** – The operation that returns values.
- **types** – The types of the returned values.
- **immediate_args** (*optional*) – Immediate arguments for the op. Defaults to None.
- **args** (*optional*) – Stack arguments for the op. Defaults to None.

outputReducer (*reducer*: *Callable[[...], pyteal.Expr]*) → *pyteal.Expr*

type_of ()

Get the return type of this expression.

`pyteal.BytesAdd` (*left*: *pyteal.Expr*, *right*: *pyteal.Expr*) → *pyteal.BinaryExpr*

Add two numbers as bytes.

Produces left + right, where left and right are interpreted as big-endian unsigned integers. Arguments must not exceed 64 bytes.

Requires TEAL version 4 or higher.

Parameters

- **left** – Must evaluate to bytes.
- **right** – Must evaluate to bytes.

`pyteal.BytesMinus` (*left*: *pyteal.Expr*, *right*: *pyteal.Expr*) → *pyteal.BinaryExpr*

Subtract two numbers as bytes.

Produces left - right, where left and right are interpreted as big-endian unsigned integers. Arguments must not exceed 64 bytes.

Requires TEAL version 4 or higher.

Parameters

- **left** – Must evaluate to bytes.
- **right** – Must evaluate to bytes.

`pyteal.BytesDiv` (*left*: *pyteal.Expr*, *right*: *pyteal.Expr*) → *pyteal.BinaryExpr*

Divide two numbers as bytes.

Produces left / right, where left and right are interpreted as big-endian unsigned integers. Arguments must not exceed 64 bytes.

Panics if right is 0.

Requires TEAL version 4 or higher.

Parameters

- **left** – Must evaluate to bytes.
- **right** – Must evaluate to bytes.

`pyteal.BytesMul` (*left*: *pyteal.Expr*, *right*: *pyteal.Expr*) → *pyteal.BinaryExpr*

Multiply two numbers as bytes.

Produces left * right, where left and right are interpreted as big-endian unsigned integers. Arguments must not exceed 64 bytes.

Requires TEAL version 4 or higher.

Parameters

- **left** – Must evaluate to bytes.
- **right** – Must evaluate to bytes.

`pyteal.BytesMod (left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`

Modulo expression with bytes as arguments.

Produces $\text{left} \% \text{right}$, where left and right are interpreted as big-endian unsigned integers. Arguments must not exceed 64 bytes.

Panics if right is 0.

Requires TEAL version 4 or higher.

Parameters

- **left** – Must evaluate to bytes.
- **right** – Must evaluate to bytes.

`pyteal.BytesAnd (left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`

Bitwise and expression with bytes as arguments.

Produces $\text{left} \& \text{right}$. Left and right are zero-left extended to the greater of their lengths. Arguments must not exceed 64 bytes.

Requires TEAL version 4 or higher.

Parameters

- **left** – Must evaluate to bytes.
- **right** – Must evaluate to bytes.

`pyteal.BytesOr (left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`

Bitwise or expression with bytes as arguments.

Produces $\text{left} | \text{right}$. Left and right are zero-left extended to the greater of their lengths. Arguments must not exceed 64 bytes.

Requires TEAL version 4 or higher.

Parameters

- **left** – Must evaluate to bytes.
- **right** – Must evaluate to bytes.

`pyteal.BytesXor (left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`

Bitwise xor expression with bytes as arguments.

Produces $\text{left} \wedge \text{right}$. Left and right are zero-left extended to the greater of their lengths. Arguments must not exceed 64 bytes.

Requires TEAL version 4 or higher.

Parameters

- **left** – Must evaluate to bytes.
- **right** – Must evaluate to bytes.

`pyteal.BytesEq` (*left: pyteal.Expr, right: pyteal.Expr*) → `pyteal.BinaryExpr`

Equality expression with bytes as arguments.

Checks if `left == right`, where `left` and `right` are interpreted as big-endian unsigned integers. Arguments must not exceed 64 bytes.

Requires TEAL version 4 or higher.

Parameters

- **left** – Must evaluate to bytes.
- **right** – Must evaluate to bytes.

`pyteal.BytesNeq` (*left: pyteal.Expr, right: pyteal.Expr*) → `pyteal.BinaryExpr`

Difference expression with bytes as arguments.

Checks if `left != right`, where `left` and `right` are interpreted as big-endian unsigned integers. Arguments must not exceed 64 bytes.

Requires TEAL version 4 or higher.

Parameters

- **left** – Must evaluate to bytes.
- **right** – Must evaluate to bytes.

`pyteal.BytesLt` (*left: pyteal.Expr, right: pyteal.Expr*) → `pyteal.BinaryExpr`

Less than expression with bytes as arguments.

Checks if `left < right`, where `left` and `right` are interpreted as big-endian unsigned integers. Arguments must not exceed 64 bytes.

Requires TEAL version 4 or higher.

Parameters

- **left** – Must evaluate to bytes.
- **right** – Must evaluate to bytes.

`pyteal.BytesLe` (*left: pyteal.Expr, right: pyteal.Expr*) → `pyteal.BinaryExpr`

Less than or equal to expression with bytes as arguments.

Checks if `left <= right`, where `left` and `right` are interpreted as big-endian unsigned integers. Arguments must not exceed 64 bytes.

Requires TEAL version 4 or higher.

Parameters

- **left** – Must evaluate to bytes.
- **right** – Must evaluate to bytes.

`pyteal.BytesGt` (*left: pyteal.Expr, right: pyteal.Expr*) → `pyteal.BinaryExpr`

Greater than expression with bytes as arguments.

Checks if `left > right`, where `left` and `right` are interpreted as big-endian unsigned integers. Arguments must not exceed 64 bytes.

Requires TEAL version 4 or higher.

Parameters

- **left** – Must evaluate to bytes.

- **right** – Must evaluate to bytes.

`pyteal.BytesGe (left: pyteal.Expr, right: pyteal.Expr) → pyteal.BinaryExpr`
Greater than or equal to expression with bytes as arguments.

Checks if `left >= right`, where `left` and `right` are interpreted as big-endian unsigned integers. Arguments must not exceed 64 bytes.

Requires TEAL version 4 or higher.

Parameters

- **left** – Must evaluate to bytes.
- **right** – Must evaluate to bytes.

`pyteal.BytesNot (arg: pyteal.Expr) → pyteal.UnaryExpr`
Get the bitwise inverse of bytes.

Produces `~arg`. Argument must not exceed 64 bytes.

Requires TEAL version 4 or higher.

`pyteal.BytesSqrt (arg: pyteal.Expr) → pyteal.UnaryExpr`
Get the bytes square root of bytes.

This will return the largest integer `X` such that `X^2 <= arg`.

Requires TEAL version 6 or higher.

`pyteal.BytesZero (arg: pyteal.Expr) → pyteal.UnaryExpr`
Get a byte-array of a specified length, containing all zero bytes.

Argument must evaluate to `uint64`.

Requires TEAL version 4 or higher.

`pyteal.ExtractUint16 (string: pyteal.Expr, offset: pyteal.Expr) → pyteal.BinaryExpr`
Extract 2 bytes (16 bits) and convert them to an integer.

The bytes starting at `offset` up to but not including `offset + 2` will be interpreted as a big-endian unsigned integer.

If `offset + 2` exceeds `Len(string)`, the program fails.

Requires TEAL version 5 or higher.

Parameters

- **string** – The bytestring to extract from. Must evaluate to bytes.
- **offset** – The offset in the bytestring to start extracting. Must evaluate to `uint64`.

`pyteal.ExtractUint32 (string: pyteal.Expr, offset: pyteal.Expr) → pyteal.BinaryExpr`
Extract 4 bytes (32 bits) and convert them to an integer.

The bytes starting at `offset` up to but not including `offset + 4` will be interpreted as a big-endian unsigned integer.

If `offset + 4` exceeds `Len(string)`, the program fails.

Requires TEAL version 5 or higher.

Parameters

- **string** – The bytestring to extract from. Must evaluate to bytes.
- **offset** – The offset in the bytestring to start extracting. Must evaluate to `uint64`.

`pyteal.ExtractUint64 (string: pyteal.Expr, offset: pyteal.Expr) → pyteal.BinaryExpr`

Extract 8 bytes (64 bits) and convert them to an integer.

The bytes starting at `offset` up to but not including `offset + 8` will be interpreted as a big-endian unsigned integer.

If `offset + 8` exceeds `Len(string)`, the program fails.

Requires TEAL version 5 or higher.

Parameters

- **string** – The bytestring to extract from. Must evaluate to bytes.
- **offset** – The offset in the bytestring to start extracting. Must evaluate to uint64.

`pyteal.Log (message: pyteal.Expr) → pyteal.UnaryExpr`

Write a message to log state of the current application.

This will fail if called more than `MaxLogCalls` times in a program (32 as of TEAL v5), or if the sum of the lengths of all logged messages in a program exceeds 1024 bytes.

Parameters message – The message to write. Must evaluate to bytes.

Requires TEAL version 5 or higher.

class `pyteal.While (cond: pyteal.Expr)`

Bases: `pyteal.Expr`

While expression.

Do (`doBlock: pyteal.Expr`)

`__init__ (cond: pyteal.Expr) → None`

Create a new While expression.

When this While expression is executed, the condition will be evaluated, and if it produces a true value, `doBlock` will be executed and return to the start of the expression execution. Otherwise, no branch will be executed.

Parameters cond – The condition to check. Must evaluate to uint64.

`has_return ()`

Check if this expression always returns from the current subroutine or program.

`type_of ()`

Get the return type of this expression.

class `pyteal.For (start: pyteal.Expr, cond: pyteal.Expr, step: pyteal.Expr)`

Bases: `pyteal.Expr`

For expression.

Do (`doBlock: pyteal.Expr`)

`__init__ (start: pyteal.Expr, cond: pyteal.Expr, step: pyteal.Expr) → None`

Create a new For expression.

When this For expression is executed, the condition will be evaluated, and if it produces a true value, `doBlock` will be executed and return to the start of the expression execution. Otherwise, no branch will be executed.

Parameters

- **start** – Expression setting the variable's initial value
- **cond** – The condition to check. Must evaluate to uint64.

- **step** – Expression to update the variable’s value.

has_return()

Check if this expression always returns from the current subroutine or program.

type_of()

Get the return type of this expression.

class pyteal.Break

Bases: *pyteal.Expr*

A break expression

__init__() → None

Create a new break expression.

This operation is only permitted in a loop.

has_return()

Check if this expression always returns from the current subroutine or program.

type_of()

Get the return type of this expression.

class pyteal.Continue

Bases: *pyteal.Expr*

A continue expression

__init__() → None

Create a new continue expression.

This operation is only permitted in a loop.

has_return()

Check if this expression always returns from the current subroutine or program.

type_of()

Get the return type of this expression.

class pyteal.Op

Bases: *enum.Enum*

Enum of program opcodes.

acct_params_get = OpType(value='acct_params_get', mode=<Mode.Application: 2>, min_ver

add = OpType(value='+', mode=<Mode.Application|Signature: 3>, min_version=2)

addr = OpType(value='addr', mode=<Mode.Application|Signature: 3>, min_version=2)

addw = OpType(value='addw', mode=<Mode.Application|Signature: 3>, min_version=2)

app_global_del = OpType(value='app_global_del', mode=<Mode.Application: 2>, min_versi

app_global_get = OpType(value='app_global_get', mode=<Mode.Application: 2>, min_versi

app_global_get_ex = OpType(value='app_global_get_ex', mode=<Mode.Application: 2>, min

app_global_put = OpType(value='app_global_put', mode=<Mode.Application: 2>, min_versi

app_local_del = OpType(value='app_local_del', mode=<Mode.Application: 2>, min_version

app_local_get = OpType(value='app_local_get', mode=<Mode.Application: 2>, min_version

app_local_get_ex = OpType(value='app_local_get_ex', mode=<Mode.Application: 2>, min_v

app_local_put = OpType(value='app_local_put', mode=<Mode.Application: 2>, min_version

```

app_opted_in = OpType(value='app_opted_in', mode=<Mode.Application: 2>, min_version=2)
app_params_get = OpType(value='app_params_get', mode=<Mode.Application: 2>, min_version=2)
arg = OpType(value='arg', mode=<Mode.Signature: 1>, min_version=2)
args = OpType(value='args', mode=<Mode.Signature: 1>, min_version=5)
assert_ = OpType(value='assert', mode=<Mode.Application|Signature: 3>, min_version=3)
asset_holding_get = OpType(value='asset_holding_get', mode=<Mode.Application: 2>, min_version=2)
asset_params_get = OpType(value='asset_params_get', mode=<Mode.Application: 2>, min_version=2)
b = OpType(value='b', mode=<Mode.Application|Signature: 3>, min_version=2)
b_add = OpType(value='b+', mode=<Mode.Application|Signature: 3>, min_version=4)
b_and = OpType(value='b&', mode=<Mode.Application|Signature: 3>, min_version=4)
b_div = OpType(value='b/', mode=<Mode.Application|Signature: 3>, min_version=4)
b_eq = OpType(value='b==', mode=<Mode.Application|Signature: 3>, min_version=4)
b_ge = OpType(value='b>=', mode=<Mode.Application|Signature: 3>, min_version=4)
b_gt = OpType(value='b>', mode=<Mode.Application|Signature: 3>, min_version=4)
b_le = OpType(value='b<=', mode=<Mode.Application|Signature: 3>, min_version=4)
b_lt = OpType(value='b<', mode=<Mode.Application|Signature: 3>, min_version=4)
b_minus = OpType(value='b-', mode=<Mode.Application|Signature: 3>, min_version=4)
b_mod = OpType(value='b%', mode=<Mode.Application|Signature: 3>, min_version=4)
b_mul = OpType(value='b*', mode=<Mode.Application|Signature: 3>, min_version=4)
b_neq = OpType(value='b!=', mode=<Mode.Application|Signature: 3>, min_version=4)
b_not = OpType(value='b~', mode=<Mode.Application|Signature: 3>, min_version=4)
b_or = OpType(value='b|', mode=<Mode.Application|Signature: 3>, min_version=4)
b_xor = OpType(value='b^', mode=<Mode.Application|Signature: 3>, min_version=4)
balance = OpType(value='balance', mode=<Mode.Application: 2>, min_version=2)
bitlen = OpType(value='bitlen', mode=<Mode.Application|Signature: 3>, min_version=4)
bitwise_and = OpType(value='&', mode=<Mode.Application|Signature: 3>, min_version=2)
bitwise_not = OpType(value='~', mode=<Mode.Application|Signature: 3>, min_version=2)
bitwise_or = OpType(value='|', mode=<Mode.Application|Signature: 3>, min_version=2)
bitwise_xor = OpType(value='^', mode=<Mode.Application|Signature: 3>, min_version=2)
bnz = OpType(value='bnz', mode=<Mode.Application|Signature: 3>, min_version=2)
bsqrt = OpType(value='bsqrt', mode=<Mode.Application|Signature: 3>, min_version=6)
btoi = OpType(value='btoi', mode=<Mode.Application|Signature: 3>, min_version=2)
byte = OpType(value='byte', mode=<Mode.Application|Signature: 3>, min_version=2)
bytec = OpType(value='bytec', mode=<Mode.Application|Signature: 3>, min_version=2)
bytec_0 = OpType(value='bytec_0', mode=<Mode.Application|Signature: 3>, min_version=2)
bytec_1 = OpType(value='bytec_1', mode=<Mode.Application|Signature: 3>, min_version=2)

```

```

bytec_2 = OpType(value='bytec_2', mode=<Mode.Application|Signature: 3>, min_version=2)
bytec_3 = OpType(value='bytec_3', mode=<Mode.Application|Signature: 3>, min_version=2)
bytecblock = OpType(value='bytecblock', mode=<Mode.Application|Signature: 3>, min_ver
bz = OpType(value='bz', mode=<Mode.Application|Signature: 3>, min_version=2)
bzero = OpType(value='bzero', mode=<Mode.Application|Signature: 3>, min_version=4)
callsub = OpType(value='callsub', mode=<Mode.Application|Signature: 3>, min_version=4)
concat = OpType(value='concat', mode=<Mode.Application|Signature: 3>, min_version=2)
cover = OpType(value='cover', mode=<Mode.Application|Signature: 3>, min_version=5)
dig = OpType(value='dig', mode=<Mode.Application|Signature: 3>, min_version=3)
div = OpType(value='/', mode=<Mode.Application|Signature: 3>, min_version=2)
divmodw = OpType(value='divmodw', mode=<Mode.Application|Signature: 3>, min_version=4)
divw = OpType(value='divw', mode=<Mode.Application|Signature: 3>, min_version=6)
dup = OpType(value='dup', mode=<Mode.Application|Signature: 3>, min_version=2)
dup2 = OpType(value='dup2', mode=<Mode.Application|Signature: 3>, min_version=2)
ecdsa_pk_decompress = OpType(value='ecdsa_pk_decompress', mode=<Mode.Application|Signa
ecdsa_pk_recover = OpType(value='ecdsa_pk_recover', mode=<Mode.Application|Signature:
ecdsa_verify = OpType(value='ecdsa_verify', mode=<Mode.Application|Signature: 3>, min
ed25519verify = OpType(value='ed25519verify', mode=<Mode.Application|Signature: 3>, m
eq = OpType(value='==', mode=<Mode.Application|Signature: 3>, min_version=2)
err = OpType(value='err', mode=<Mode.Application|Signature: 3>, min_version=2)
exp = OpType(value='exp', mode=<Mode.Application|Signature: 3>, min_version=4)
expw = OpType(value='expw', mode=<Mode.Application|Signature: 3>, min_version=4)
extract = OpType(value='extract', mode=<Mode.Application|Signature: 3>, min_version=5)
extract3 = OpType(value='extract3', mode=<Mode.Application|Signature: 3>, min_version
extract_uint16 = OpType(value='extract_uint16', mode=<Mode.Application|Signature: 3>,
extract_uint32 = OpType(value='extract_uint32', mode=<Mode.Application|Signature: 3>,
extract_uint64 = OpType(value='extract_uint64', mode=<Mode.Application|Signature: 3>,
gaid = OpType(value='gaid', mode=<Mode.Application: 2>, min_version=4)
gaids = OpType(value='gaids', mode=<Mode.Application: 2>, min_version=4)
ge = OpType(value='>=', mode=<Mode.Application|Signature: 3>, min_version=2)
getbit = OpType(value='getbit', mode=<Mode.Application|Signature: 3>, min_version=3)
getbyte = OpType(value='getbyte', mode=<Mode.Application|Signature: 3>, min_version=3)
gitxn = OpType(value='gitxn', mode=<Mode.Application: 2>, min_version=6)
gitxna = OpType(value='gitxna', mode=<Mode.Application: 2>, min_version=6)
gitxnas = OpType(value='gitxnas', mode=<Mode.Application: 2>, min_version=6)
gload = OpType(value='gload', mode=<Mode.Application: 2>, min_version=4)

```

```
gloads = OpType(value='gloads', mode=<Mode.Application: 2>, min_version=4)
gloadss = OpType(value='gloadss', mode=<Mode.Application: 2>, min_version=6)
global_ = OpType(value='global', mode=<Mode.Application|Signature: 3>, min_version=2)
gt = OpType(value='>', mode=<Mode.Application|Signature: 3>, min_version=2)
gtxn = OpType(value='gtxn', mode=<Mode.Application|Signature: 3>, min_version=2)
gtxna = OpType(value='gtxna', mode=<Mode.Application|Signature: 3>, min_version=2)
gtxnas = OpType(value='gtxnas', mode=<Mode.Application|Signature: 3>, min_version=5)
gtxns = OpType(value='gtxns', mode=<Mode.Application|Signature: 3>, min_version=3)
gtxnsa = OpType(value='gtxnsa', mode=<Mode.Application|Signature: 3>, min_version=3)
gtxnsas = OpType(value='gtxnsas', mode=<Mode.Application|Signature: 3>, min_version=5)
int = OpType(value='int', mode=<Mode.Application|Signature: 3>, min_version=2)
intc = OpType(value='intc', mode=<Mode.Application|Signature: 3>, min_version=2)
intc_0 = OpType(value='intc_0', mode=<Mode.Application|Signature: 3>, min_version=2)
intc_1 = OpType(value='intc_1', mode=<Mode.Application|Signature: 3>, min_version=2)
intc_2 = OpType(value='intc_2', mode=<Mode.Application|Signature: 3>, min_version=2)
intc_3 = OpType(value='intc_3', mode=<Mode.Application|Signature: 3>, min_version=2)
intcblock = OpType(value='intcblock', mode=<Mode.Application|Signature: 3>, min_version=2)
itob = OpType(value='itob', mode=<Mode.Application|Signature: 3>, min_version=2)
itxn = OpType(value='itxn', mode=<Mode.Application: 2>, min_version=5)
itxn_begin = OpType(value='itxn_begin', mode=<Mode.Application: 2>, min_version=5)
itxn_field = OpType(value='itxn_field', mode=<Mode.Application: 2>, min_version=5)
itxn_next = OpType(value='itxn_next', mode=<Mode.Application: 2>, min_version=6)
itxn_submit = OpType(value='itxn_submit', mode=<Mode.Application: 2>, min_version=5)
itxna = OpType(value='itxna', mode=<Mode.Application: 2>, min_version=5)
itxnas = OpType(value='itxnas', mode=<Mode.Application: 2>, min_version=6)
keccak256 = OpType(value='keccak256', mode=<Mode.Application|Signature: 3>, min_version=2)
le = OpType(value='<=', mode=<Mode.Application|Signature: 3>, min_version=2)
len = OpType(value='len', mode=<Mode.Application|Signature: 3>, min_version=2)
load = OpType(value='load', mode=<Mode.Application|Signature: 3>, min_version=2)
loads = OpType(value='loads', mode=<Mode.Application|Signature: 3>, min_version=5)
log = OpType(value='log', mode=<Mode.Application: 2>, min_version=5)
logic_and = OpType(value='&&', mode=<Mode.Application|Signature: 3>, min_version=2)
logic_not = OpType(value='!', mode=<Mode.Application|Signature: 3>, min_version=2)
logic_or = OpType(value='||', mode=<Mode.Application|Signature: 3>, min_version=2)
lt = OpType(value='<', mode=<Mode.Application|Signature: 3>, min_version=2)
method_signature = OpType(value='method', mode=<Mode.Application|Signature: 3>, min_version=2)
```

```

min_balance = OpType(value='min_balance', mode=<Mode.Application: 2>, min_version=3)
min_version
    Get the minimum version where this op is available.
minus = OpType(value='-', mode=<Mode.Application|Signature: 3>, min_version=2)
mod = OpType(value='%', mode=<Mode.Application|Signature: 3>, min_version=2)
mode
    Get the modes where this op is available.
mul = OpType(value='*', mode=<Mode.Application|Signature: 3>, min_version=2)
mulw = OpType(value='mulw', mode=<Mode.Application|Signature: 3>, min_version=2)
neq = OpType(value='!=', mode=<Mode.Application|Signature: 3>, min_version=2)
pop = OpType(value='pop', mode=<Mode.Application|Signature: 3>, min_version=2)
pushbytes = OpType(value='pushbytes', mode=<Mode.Application|Signature: 3>, min_version=3)
pushint = OpType(value='pushint', mode=<Mode.Application|Signature: 3>, min_version=3)
retsub = OpType(value='retsub', mode=<Mode.Application|Signature: 3>, min_version=4)
return_ = OpType(value='return', mode=<Mode.Application|Signature: 3>, min_version=2)
select = OpType(value='select', mode=<Mode.Application|Signature: 3>, min_version=3)
setbit = OpType(value='setbit', mode=<Mode.Application|Signature: 3>, min_version=3)
setbyte = OpType(value='setbyte', mode=<Mode.Application|Signature: 3>, min_version=3)
sha256 = OpType(value='sha256', mode=<Mode.Application|Signature: 3>, min_version=2)
sha512_256 = OpType(value='sha512_256', mode=<Mode.Application|Signature: 3>, min_version=2)
shl = OpType(value='shl', mode=<Mode.Application|Signature: 3>, min_version=4)
shr = OpType(value='shr', mode=<Mode.Application|Signature: 3>, min_version=4)
sqrt = OpType(value='sqrt', mode=<Mode.Application|Signature: 3>, min_version=4)
store = OpType(value='store', mode=<Mode.Application|Signature: 3>, min_version=2)
stores = OpType(value='stores', mode=<Mode.Application|Signature: 3>, min_version=5)
substring = OpType(value='substring', mode=<Mode.Application|Signature: 3>, min_version=3)
substring3 = OpType(value='substring3', mode=<Mode.Application|Signature: 3>, min_version=3)
swap = OpType(value='swap', mode=<Mode.Application|Signature: 3>, min_version=3)
txn = OpType(value='txn', mode=<Mode.Application|Signature: 3>, min_version=2)
txna = OpType(value='txna', mode=<Mode.Application|Signature: 3>, min_version=2)
txnas = OpType(value='txnas', mode=<Mode.Application|Signature: 3>, min_version=5)
uncover = OpType(value='uncover', mode=<Mode.Application|Signature: 3>, min_version=5)

class pyteal.Mode
    Bases: enum.Flag
    Enum of program running modes.
    Application = 2
    Signature = 1

```

```
class pyteal.TealComponent (expr: Optional[Expr])
    Bases: abc.ABC

    class Context
        Bases: object

        class EqualityContext
            Bases: contextlib.AbstractContextManager

        checkExpr = True

        classmethod ignoreExprEquality ()

    assemble () → str

    assignSlot (slot: ScratchSlot, location: int) → None

    getSlots () → List[ScratchSlot]

    getSubroutines () → List[SubroutineDefinition]

    resolveSubroutine (subroutine: SubroutineDefinition, label: str) → None

class pyteal.TealOp (expr: Optional[Expr], op: pyteal.Op, *args)
    Bases: pyteal.TealComponent

    assemble () → str

    assignSlot (slot: ScratchSlot, location: int) → None

    getOp () → pyteal.Op

    getSlots () → List[ScratchSlot]

    getSubroutines () → List[SubroutineDefinition]

    resolveSubroutine (subroutine: SubroutineDefinition, label: str) → None

class pyteal.TealLabel (expr: Optional[Expr], label: pyteal.ir.labelref.LabelReference, comment: str
                        = None)
    Bases: pyteal.TealComponent

    assemble () → str

    getLabelRef () → pyteal.ir.labelref.LabelReference

class pyteal.TealBlock (ops: List[pyteal.TealOp])
    Bases: abc.ABC

    Represents a basic block of TealComponents in a graph.

    classmethod FromOp (options: CompileOptions, op: pyteal.TealOp, *args) → Tuple[TealBlock,
                                           TealSimpleBlock]
        Create a path of blocks from a TealOp and its arguments.

        Returns The starting and ending block of the path that encodes the given TealOp and arguments.

    classmethod Iterate (start: pyteal.TealBlock) → Iterator[pyteal.TealBlock]
        Perform a depth-first search of the graph of blocks starting with start.

    classmethod NormalizeBlocks (start: pyteal.TealBlock) → pyteal.TealBlock
        Minimize the number of blocks in the graph of blocks starting with start by combining sequential blocks.
        This operation does not alter the operations of the graph or the functionality of its underlying program,
        however it does mutate the input graph.

        Returns The new starting point of the altered graph. May be the same or different than start.
```

addIncoming (*parent*: *Optional*[*pyteal.TealBlock*] = *None*, *visited*: *List*[*TealBlock*] = *None*) → *None*
 Calculate the parent blocks for this block and its children.

Parameters

- **parent** (*optional*) – The parent block to this one, if it has one. Defaults to *None*.
- **visited** (*optional*) – Used internally to remember blocks that have been visited. Set to *None*.

getOutgoing () → *List*[*pyteal.TealBlock*]
 Get this block's children blocks, if any.

isTerminal () → *bool*
 Check if this block ends the program.

replaceOutgoing (*oldBlock*: *pyteal.TealBlock*, *newBlock*: *pyteal.TealBlock*) → *None*
 Replace one of this block's child blocks.

validateSlots (*slotsInUse*: *Set*[*ScratchSlot*] = *None*, *visited*: *Set*[*Tuple*[*int*, ...]] = *None*) → *List*[*pyteal.TealCompileError*]

validateTree (*parent*: *Optional*[*pyteal.TealBlock*] = *None*, *visited*: *List*[*TealBlock*] = *None*) → *None*
 Check that this block and its children have valid parent pointers.

Parameters

- **parent** (*optional*) – The parent block to this one, if it has one. Defaults to *None*.
- **visited** (*optional*) – Used internally to remember blocks that have been visited. Set to *None*.

class *pyteal.TealSimpleBlock* (*ops*: *List*[*pyteal.TealOp*])
 Bases: *pyteal.TealBlock*

Represents a basic block of *TealComponents* in a graph that does not contain a branch condition.

getOutgoing () → *List*[*pyteal.TealBlock*]
 Get this block's children blocks, if any.

replaceOutgoing (*oldBlock*: *pyteal.TealBlock*, *newBlock*: *pyteal.TealBlock*) → *None*
 Replace one of this block's child blocks.

setNextBlock (*block*: *pyteal.TealBlock*) → *None*
 Set the block that follows this one.

class *pyteal.TealConditionalBlock* (*ops*: *List*[*pyteal.TealOp*])
 Bases: *pyteal.TealBlock*

Represents a basic block of *TealComponents* in a graph ending with a branch condition.

getOutgoing () → *List*[*pyteal.TealBlock*]
 Get this block's children blocks, if any.

replaceOutgoing (*oldBlock*: *pyteal.TealBlock*, *newBlock*: *pyteal.TealBlock*) → *None*
 Replace one of this block's child blocks.

setFalseBlock (*block*: *pyteal.TealBlock*) → *None*
 Set the block that this one should branch to if its condition is false.

setTrueBlock (*block*: *pyteal.TealBlock*) → *None*
 Set the block that this one should branch to if its condition is true.

class *pyteal.LabelReference* (*label*: *str*)
 Bases: *object*

```
    addPrefix(prefix: str) → None
    getLabel() → str
class pyteal.CompileOptions(*, mode: pyteal.Mode = <Mode.Signature: 1>, version: int = 2)
    Bases: object
    addLoopBreakBlock(block: pyteal.TealSimpleBlock) → None
    addLoopContinueBlock(block: pyteal.TealSimpleBlock) → None
    enterLoop() → None
    exitLoop() → Tuple[List[pyteal.TealSimpleBlock], List[pyteal.TealSimpleBlock]]
    isInLoop() → bool
    setSubroutine(subroutine: Optional[pyteal.SubroutineDefinition]) → None
pyteal.compileTeal(ast: pyteal.Expr, mode: pyteal.Mode, *, version: int = 2, assembleConstants: bool
                  = False) → str
    Compile a PyTeal expression into TEAL assembly.
```

Parameters

- **ast** – The PyTeal expression to assemble.
- **mode** – The mode of the program to assemble. Must be Signature or Application.
- **version** (*optional*) – The TEAL version used to assemble the program. This will determine which expressions and fields are able to be used in the program and how expressions compile to TEAL opcodes. Defaults to 2 if not included.
- **assembleConstants** (*optional*) – When true, the compiler will produce a program with fully assembled constants, rather than using the pseudo-ops *int*, *byte*, and *addr*. These constants will be assembled in the most space-efficient way, so enabling this may reduce the compiled program's size. Enabling this option requires a minimum TEAL version of 3. Defaults to false.

Returns A TEAL assembly program compiled from the input expression.

Raises

- *TealInputError* – if an operation in ast is not supported by the supplied mode and version.
- *TealInternalError* – if an internal error is encountered during compilation.

```
class pyteal.TealType
    Bases: enum.Enum
    Teal type enum.
    anytype = 2
    bytes = 1
    none = 3
    uint64 = 0
exception pyteal.TealInternalError(message: str)
    Bases: Exception
exception pyteal.TealTypeError(actual, expected)
    Bases: Exception
```

```
exception pyteal.TealInputError (msg: str)  
    Bases: Exception
```

```
exception pyteal.TealCompileError (msg: str, sourceExpr: Optional[Expr])  
    Bases: Exception
```


CHAPTER 16

Indices and tables

- `genindex`

p

pyteal, [73](#)

Symbols

__getitem__ () (*pyteal.Array method*), 93
 __getitem__ () (*pyteal.InnerTxnGroup method*), 93
 __getitem__ () (*pyteal.TxnArray method*), 77
 __getitem__ () (*pyteal.TxnGroup method*), 84
 __init__ () (*pyteal.Addr method*), 74
 __init__ () (*pyteal.Arg method*), 75
 __init__ () (*pyteal.Assert method*), 103
 __init__ () (*pyteal.Break method*), 113
 __init__ () (*pyteal.Bytes method*), 74
 __init__ () (*pyteal.Cond method*), 102
 __init__ () (*pyteal.Continue method*), 113
 __init__ () (*pyteal.EnumInt method*), 74
 __init__ () (*pyteal.For method*), 112
 __init__ () (*pyteal.GeneratedID method*), 84
 __init__ () (*pyteal.If method*), 102
 __init__ () (*pyteal.ImportScratchValue method*), 84
 __init__ () (*pyteal.Int method*), 74
 __init__ () (*pyteal.MaybeValue method*), 107
 __init__ () (*pyteal.MethodSignature method*), 75
 __init__ () (*pyteal.MultiValue method*), 107
 __init__ () (*pyteal.Nonce method*), 94
 __init__ () (*pyteal.Return method*), 103
 __init__ () (*pyteal.ScratchLoad method*), 105
 __init__ () (*pyteal.ScratchSlot method*), 105
 __init__ () (*pyteal.ScratchStackStore method*), 106
 __init__ () (*pyteal.ScratchStore method*), 106
 __init__ () (*pyteal.ScratchVar method*), 106
 __init__ () (*pyteal.Seq method*), 103
 __init__ () (*pyteal.Subroutine method*), 104
 __init__ () (*pyteal.While method*), 112
 __init__ () (*pyteal.WideRatio method*), 101

A

AccountParam (*class in pyteal*), 91
 accounts (*pyteal.TxnField attribute*), 75
 accounts (*pyteal.TxnObject attribute*), 78
 acct_params_get (*pyteal.Op attribute*), 113
 add (*pyteal.Op attribute*), 113

Add () (*in module pyteal*), 95
 addIncoming () (*pyteal.TealBlock method*), 118
 addLoopBreakBlock () (*pyteal.CompileOptions method*), 120
 addLoopContinueBlock () (*pyteal.CompileOptions method*), 120
 addPrefix () (*pyteal.LabelReference method*), 119
 Addr (*class in pyteal*), 74
 addr (*pyteal.Op attribute*), 113
 Addr () (*pyteal.Tmpl class method*), 93
 address () (*pyteal.AppParam class method*), 88
 addw (*pyteal.Op attribute*), 113
 amount (*pyteal.TxnField attribute*), 75
 amount () (*pyteal.TxnObject method*), 78
 And () (*in module pyteal*), 100
 And () (*pyteal.Expr method*), 73
 anytype (*pyteal.TealType attribute*), 120
 App (*class in pyteal*), 86
 app_global_del (*pyteal.Op attribute*), 113
 app_global_get (*pyteal.Op attribute*), 113
 app_global_get_ex (*pyteal.Op attribute*), 113
 app_global_put (*pyteal.Op attribute*), 113
 app_local_del (*pyteal.Op attribute*), 113
 app_local_get (*pyteal.Op attribute*), 113
 app_local_get_ex (*pyteal.Op attribute*), 113
 app_local_put (*pyteal.Op attribute*), 113
 app_opted_in (*pyteal.Op attribute*), 113
 app_params_get (*pyteal.Op attribute*), 114
 AppField (*class in pyteal*), 88
 Application (*pyteal.Mode attribute*), 117
 application_args (*pyteal.TxnField attribute*), 75
 application_args (*pyteal.TxnObject attribute*), 78
 application_id (*pyteal.TxnField attribute*), 75
 application_id () (*pyteal.TxnObject method*), 78
 ApplicationCall (*pyteal.TxnType attribute*), 75
 applications (*pyteal.TxnField attribute*), 75
 applications (*pyteal.TxnObject attribute*), 78
 AppParam (*class in pyteal*), 88
 approval_program (*pyteal.TxnField attribute*), 75

approval_program() (pyteal.TxnObject method), 78
 approvalProgram() (pyteal.AppParam class method), 88
 Approve() (in module pyteal), 104
 Arg (class in pyteal), 75
 arg (pyteal.Op attribute), 114
 args (pyteal.Op attribute), 114
 argumentCount() (pyteal.SubroutineDefinition method), 104
 Array (class in pyteal), 93
 assemble() (pyteal.TealComponent method), 118
 assemble() (pyteal.TealLabel method), 118
 assemble() (pyteal.TealOp method), 118
 Assert (class in pyteal), 103
 assert_ (pyteal.Op attribute), 114
 asset_amount (pyteal.TxnField attribute), 76
 asset_amount() (pyteal.TxnObject method), 78
 asset_close_to (pyteal.TxnField attribute), 76
 asset_close_to() (pyteal.TxnObject method), 78
 asset_holding_get (pyteal.Op attribute), 114
 asset_params_get (pyteal.Op attribute), 114
 asset_receiver (pyteal.TxnField attribute), 76
 asset_receiver() (pyteal.TxnObject method), 78
 asset_sender (pyteal.TxnField attribute), 76
 asset_sender() (pyteal.TxnObject method), 78
 AssetConfig (pyteal.TxnType attribute), 75
 AssetFreeze (pyteal.TxnType attribute), 75
 AssetHolding (class in pyteal), 89
 AssetParam (class in pyteal), 90
 assets (pyteal.TxnField attribute), 76
 assets (pyteal.TxnObject attribute), 79
 AssetTransfer (pyteal.TxnType attribute), 75
 assignSlot() (pyteal.TealComponent method), 118
 assignSlot() (pyteal.TealOp method), 118
 authAddr() (pyteal.AccountParam class method), 91

B

b (pyteal.Op attribute), 114
 b_add (pyteal.Op attribute), 114
 b_and (pyteal.Op attribute), 114
 b_div (pyteal.Op attribute), 114
 b_eq (pyteal.Op attribute), 114
 b_ge (pyteal.Op attribute), 114
 b_gt (pyteal.Op attribute), 114
 b_le (pyteal.Op attribute), 114
 b_lt (pyteal.Op attribute), 114
 b_minus (pyteal.Op attribute), 114
 b_mod (pyteal.Op attribute), 114
 b_mul (pyteal.Op attribute), 114
 b_neq (pyteal.Op attribute), 114
 b_not (pyteal.Op attribute), 114
 b_or (pyteal.Op attribute), 114
 b_xor (pyteal.Op attribute), 114

balance (pyteal.Op attribute), 114
 Balance() (in module pyteal), 95
 balance() (pyteal.AccountParam class method), 91
 balance() (pyteal.AssetHolding class method), 89
 Begin (pyteal.InnerTxnAction attribute), 93
 Begin() (pyteal.InnerTxnBuilder class method), 91
 BinaryExpr (class in pyteal), 95
 bitlen (pyteal.Op attribute), 114
 BitLen() (in module pyteal), 94
 bitwise_and (pyteal.Op attribute), 114
 bitwise_not (pyteal.Op attribute), 114
 bitwise_or (pyteal.Op attribute), 114
 bitwise_xor (pyteal.Op attribute), 114
 BitwiseAnd() (in module pyteal), 96
 BitwiseNot() (in module pyteal), 95
 BitwiseOr() (in module pyteal), 97
 BitwiseXor() (in module pyteal), 97
 bnz (pyteal.Op attribute), 114
 Break (class in pyteal), 113
 bsqrt (pyteal.Op attribute), 114
 btoi (pyteal.Op attribute), 114
 Btoi() (in module pyteal), 94
 byte (pyteal.Op attribute), 114
 bytec (pyteal.Op attribute), 114
 bytec_0 (pyteal.Op attribute), 114
 bytec_1 (pyteal.Op attribute), 114
 bytec_2 (pyteal.Op attribute), 114
 bytec_3 (pyteal.Op attribute), 115
 bytecblock (pyteal.Op attribute), 115
 Bytes (class in pyteal), 74
 bytes (pyteal.TealType attribute), 120
 Bytes() (pyteal.Tmpl class method), 93
 BytesAdd() (in module pyteal), 108
 BytesAnd() (in module pyteal), 109
 BytesDiv() (in module pyteal), 108
 BytesEq() (in module pyteal), 109
 BytesGe() (in module pyteal), 111
 BytesGt() (in module pyteal), 110
 BytesLe() (in module pyteal), 110
 BytesLt() (in module pyteal), 110
 BytesMinus() (in module pyteal), 108
 BytesMod() (in module pyteal), 109
 BytesMul() (in module pyteal), 108
 BytesNeq() (in module pyteal), 110
 BytesNot() (in module pyteal), 111
 BytesOr() (in module pyteal), 109
 BytesSqrt() (in module pyteal), 111
 BytesXor() (in module pyteal), 109
 BytesZero() (in module pyteal), 111
 bz (pyteal.Op attribute), 115
 bzero (pyteal.Op attribute), 115

C

caller_app_address (pyteal.GlobalField at-

tribute), 86
 caller_app_address() (pyteal.Global class method), 85
 caller_app_id(pyteal.GlobalField attribute), 86
 caller_app_id() (pyteal.Global class method), 85
 callsub(pyteal.Op attribute), 115
 checkExpr(pyteal.TealComponent.Context attribute), 118
 clawback() (pyteal.AssetParam class method), 90
 clear_state_program(pyteal.TxnField attribute), 76
 clear_state_program() (pyteal.TxnObject method), 79
 ClearState(pyteal.OnComplete attribute), 88
 clearStateProgram() (pyteal.AppParam class method), 89
 close_remainder_to(pyteal.TxnField attribute), 76
 close_remainder_to() (pyteal.TxnObject method), 79
 CloseOut(pyteal.OnComplete attribute), 88
 CompileOptions(class in pyteal), 120
 compileTeal() (in module pyteal), 120
 concat(pyteal.Op attribute), 115
 Concat() (in module pyteal), 101
 Cond(class in pyteal), 102
 config_asset(pyteal.TxnField attribute), 76
 config_asset() (pyteal.TxnObject method), 79
 config_asset_clawback(pyteal.TxnField attribute), 76
 config_asset_clawback() (pyteal.TxnObject method), 79
 config_asset_decimals(pyteal.TxnField attribute), 76
 config_asset_decimals() (pyteal.TxnObject method), 79
 config_asset_default_frozen(pyteal.TxnField attribute), 76
 config_asset_default_frozen() (pyteal.TxnObject method), 79
 config_asset_freeze(pyteal.TxnField attribute), 76
 config_asset_freeze() (pyteal.TxnObject method), 79
 config_asset_manager(pyteal.TxnField attribute), 76
 config_asset_manager() (pyteal.TxnObject method), 79
 config_asset_metadata_hash(pyteal.TxnField attribute), 76
 config_asset_metadata_hash() (pyteal.TxnObject method), 79
 config_asset_name(pyteal.TxnField attribute), 76
 config_asset_name() (pyteal.TxnObject method), 80
 config_asset_reserve(pyteal.TxnField attribute), 76
 config_asset_reserve() (pyteal.TxnObject method), 80
 config_asset_total(pyteal.TxnField attribute), 76
 config_asset_total() (pyteal.TxnObject method), 80
 config_asset_unit_name(pyteal.TxnField attribute), 76
 config_asset_unit_name() (pyteal.TxnObject method), 80
 config_asset_url(pyteal.TxnField attribute), 76
 config_asset_url() (pyteal.TxnObject method), 80
 Continue(class in pyteal), 113
 cover(pyteal.Op attribute), 115
 created_application_id(pyteal.TxnField attribute), 76
 created_application_id() (pyteal.TxnObject method), 80
 created_asset_id(pyteal.TxnField attribute), 76
 created_asset_id() (pyteal.TxnObject method), 80
 creator() (pyteal.AppParam class method), 89
 creator() (pyteal.AssetParam class method), 90
 creator_address(pyteal.GlobalField attribute), 86
 creator_address() (pyteal.Global class method), 85
 current_app_address(pyteal.GlobalField attribute), 86
 current_app_id(pyteal.GlobalField attribute), 86
 current_application_address() (pyteal.Global class method), 85
 current_application_id() (pyteal.Global class method), 85

D

decimals() (pyteal.AssetParam class method), 90
 defaultFrozen() (pyteal.AssetParam class method), 90
 DeleteApplication(pyteal.OnComplete attribute), 88
 dig(pyteal.Op attribute), 115
 div(pyteal.Op attribute), 115
 Div() (in module pyteal), 96
 divmodw(pyteal.Op attribute), 115
 divw(pyteal.Op attribute), 115
 Divw() (in module pyteal), 96
 Do() (pyteal.For method), 112
 Do() (pyteal.While method), 112
 dup(pyteal.Op attribute), 115
 dup2(pyteal.Op attribute), 115

E

ecdsa_pk_decompress (*pyteal.Op attribute*), 115
 ecdsa_pk_recover (*pyteal.Op attribute*), 115
 ecdsa_verify (*pyteal.Op attribute*), 115
 ed25519verify (*pyteal.Op attribute*), 115
 Ed25519Verify () (*in module pyteal*), 99
 Else () (*pyteal.If method*), 102
 ElseIf () (*pyteal.If method*), 102
 enterLoop () (*pyteal.CompileOptions method*), 120
 EnumInt (*class in pyteal*), 74
 eq (*pyteal.Op attribute*), 115
 Eq () (*in module pyteal*), 97
 Err (*class in pyteal*), 103
 err (*pyteal.Op attribute*), 115
 exitLoop () (*pyteal.CompileOptions method*), 120
 exp (*pyteal.Op attribute*), 115
 Exp () (*in module pyteal*), 96
 Expr (*class in pyteal*), 73
 expw (*pyteal.Op attribute*), 115
 extra_program_pages (*pyteal.TxnField attribute*), 76
 extra_program_pages () (*pyteal.TxnObject method*), 80
 extract (*pyteal.Op attribute*), 115
 Extract () (*in module pyteal*), 99
 extract3 (*pyteal.Op attribute*), 115
 extract_uint16 (*pyteal.Op attribute*), 115
 extract_uint32 (*pyteal.Op attribute*), 115
 extract_uint64 (*pyteal.Op attribute*), 115
 ExtractUint16 () (*in module pyteal*), 111
 ExtractUint32 () (*in module pyteal*), 111
 ExtractUint64 () (*in module pyteal*), 111
 extraProgramPages () (*pyteal.AppParam class method*), 89

F

fee (*pyteal.TxnField attribute*), 76
 fee () (*pyteal.TxnObject method*), 81
 first_valid (*pyteal.TxnField attribute*), 76
 first_valid () (*pyteal.TxnObject method*), 81
 first_valid_time (*pyteal.TxnField attribute*), 76
 For (*class in pyteal*), 112
 freeze () (*pyteal.AssetParam class method*), 90
 freeze_asset (*pyteal.TxnField attribute*), 76
 freeze_asset () (*pyteal.TxnObject method*), 81
 freeze_asset_account (*pyteal.TxnField attribute*), 76
 freeze_asset_account () (*pyteal.TxnObject method*), 81
 freeze_asset_frozen (*pyteal.TxnField attribute*), 76
 freeze_asset_frozen () (*pyteal.TxnObject method*), 81
 FromOp () (*pyteal.TealBlock class method*), 118

frozen () (*pyteal.AssetHolding class method*), 89

G

gaid (*pyteal.Op attribute*), 115
 gaidss (*pyteal.Op attribute*), 115
 ge (*pyteal.Op attribute*), 115
 Ge () (*in module pyteal*), 98
 GeneratedID (*class in pyteal*), 84
 get_op () (*pyteal.AppField method*), 88
 getbit (*pyteal.Op attribute*), 115
 GetBit () (*in module pyteal*), 98
 getbyte (*pyteal.Op attribute*), 115
 GetByte () (*in module pyteal*), 98
 getDeclaration () (*pyteal.SubroutineDefinition method*), 104
 getDefinitionTrace () (*pyteal.Expr method*), 73
 getLabel () (*pyteal.LabelReference method*), 120
 getLabelRef () (*pyteal.TealLabel method*), 118
 getOp () (*pyteal.TealOp method*), 118
 getOutgoing () (*pyteal.TealBlock method*), 119
 getOutgoing () (*pyteal.TealConditionalBlock method*), 119
 getOutgoing () (*pyteal.TealSimpleBlock method*), 119
 getSlots () (*pyteal.TealComponent method*), 118
 getSlots () (*pyteal.TealOp method*), 118
 getSubroutines () (*pyteal.TealComponent method*), 118
 getSubroutines () (*pyteal.TealOp method*), 118
 gitxn (*pyteal.Op attribute*), 115
 gitxna (*pyteal.Op attribute*), 115
 GitxnaExpr (*class in pyteal*), 93
 gitxnas (*pyteal.Op attribute*), 115
 GitxnExpr (*class in pyteal*), 93
 gload (*pyteal.Op attribute*), 115
 gloads (*pyteal.Op attribute*), 115
 gloadss (*pyteal.Op attribute*), 116
 Global (*class in pyteal*), 84
 global_ (*pyteal.Op attribute*), 116
 global_num_byte_slices (*pyteal.TxnField attribute*), 76
 global_num_byte_slices () (*pyteal.TxnObject method*), 81
 global_num_uints (*pyteal.TxnField attribute*), 76
 global_num_uints () (*pyteal.TxnObject method*), 81
 globalDel (*pyteal.AppField attribute*), 88
 globalDel () (*pyteal.App class method*), 86
 GlobalField (*class in pyteal*), 86
 globalGet (*pyteal.AppField attribute*), 88
 globalGet () (*pyteal.App class method*), 86
 globalGetEx (*pyteal.AppField attribute*), 88
 globalGetEx () (*pyteal.App class method*), 86

[globalNumByteSlice\(\)](#) (*pyteal.AppParam class method*), 89
[globalNumUnit\(\)](#) (*pyteal.AppParam class method*), 89
[globalPut](#) (*pyteal.AppField attribute*), 88
[globalPut\(\)](#) (*pyteal.App class method*), 86
[group_id](#) (*pyteal.GlobalField attribute*), 86
[group_id\(\)](#) (*pyteal.Global class method*), 85
[group_index](#) (*pyteal.TxnField attribute*), 76
[group_index\(\)](#) (*pyteal.TxnObject method*), 81
[group_size](#) (*pyteal.GlobalField attribute*), 86
[group_size\(\)](#) (*pyteal.Global class method*), 85
[gt](#) (*pyteal.Op attribute*), 116
[Gt\(\)](#) (*in module pyteal*), 98
[Gtxn](#) (*in module pyteal*), 73
[gtxn](#) (*pyteal.Op attribute*), 116
[gtxna](#) (*pyteal.Op attribute*), 116
[GtxnaExpr](#) (*class in pyteal*), 83
[gtxnas](#) (*pyteal.Op attribute*), 116
[GtxnExpr](#) (*class in pyteal*), 83
[gtxns](#) (*pyteal.Op attribute*), 116
[gtxnlsa](#) (*pyteal.Op attribute*), 116
[gtxnlsas](#) (*pyteal.Op attribute*), 116

H

[has_return\(\)](#) (*pyteal.Assert method*), 103
[has_return\(\)](#) (*pyteal.BinaryExpr method*), 95
[has_return\(\)](#) (*pyteal.Break method*), 113
[has_return\(\)](#) (*pyteal.Cond method*), 102
[has_return\(\)](#) (*pyteal.Continue method*), 113
[has_return\(\)](#) (*pyteal.Err method*), 103
[has_return\(\)](#) (*pyteal.Expr method*), 73
[has_return\(\)](#) (*pyteal.For method*), 113
[has_return\(\)](#) (*pyteal.If method*), 102
[has_return\(\)](#) (*pyteal.LeafExpr method*), 73
[has_return\(\)](#) (*pyteal.NaryExpr method*), 100
[has_return\(\)](#) (*pyteal.Nonce method*), 94
[has_return\(\)](#) (*pyteal.Return method*), 104
[has_return\(\)](#) (*pyteal.ScratchLoad method*), 105
[has_return\(\)](#) (*pyteal.ScratchStackStore method*), 106
[has_return\(\)](#) (*pyteal.ScratchStore method*), 106
[has_return\(\)](#) (*pyteal.Seq method*), 103
[has_return\(\)](#) (*pyteal.SubroutineCall method*), 104
[has_return\(\)](#) (*pyteal.SubroutineDeclaration method*), 104
[has_return\(\)](#) (*pyteal.SubroutineFnWrapper method*), 105
[has_return\(\)](#) (*pyteal.UnaryExpr method*), 94
[has_return\(\)](#) (*pyteal.While method*), 112
[has_return\(\)](#) (*pyteal.WideRatio method*), 101
[hasValue\(\)](#) (*pyteal.MaybeValue method*), 107

I

[id\(\)](#) (*pyteal.App class method*), 87
[If](#) (*class in pyteal*), 101
[ignoreExprEquality\(\)](#) (*pyteal.TealComponent.Context class method*), 118
[ImportScratchValue](#) (*class in pyteal*), 84
[InnerTxn](#) (*in module pyteal*), 73
[InnerTxnAction](#) (*class in pyteal*), 92
[InnerTxnBuilder](#) (*class in pyteal*), 91
[InnerTxnGroup](#) (*class in pyteal*), 93
[Int](#) (*class in pyteal*), 74
[int](#) (*pyteal.Op attribute*), 116
[Int\(\)](#) (*pyteal.Tmpl class method*), 93
[intc](#) (*pyteal.Op attribute*), 116
[intc_0](#) (*pyteal.Op attribute*), 116
[intc_1](#) (*pyteal.Op attribute*), 116
[intc_2](#) (*pyteal.Op attribute*), 116
[intc_3](#) (*pyteal.Op attribute*), 116
[intcblock](#) (*pyteal.Op attribute*), 116
[invoke\(\)](#) (*pyteal.SubroutineDefinition method*), 104
[isInLoop\(\)](#) (*pyteal.CompileOptions method*), 120
[isTerminal\(\)](#) (*pyteal.TealBlock method*), 119
[Iterate\(\)](#) (*pyteal.TealBlock class method*), 118
[itob](#) (*pyteal.Op attribute*), 116
[Itob\(\)](#) (*in module pyteal*), 94
[itxn](#) (*pyteal.Op attribute*), 116
[itxn_begin](#) (*pyteal.Op attribute*), 116
[itxn_field](#) (*pyteal.Op attribute*), 116
[itxn_next](#) (*pyteal.Op attribute*), 116
[itxn_submit](#) (*pyteal.Op attribute*), 116
[itxna](#) (*pyteal.Op attribute*), 116
[itxnas](#) (*pyteal.Op attribute*), 116

K

[keccak256](#) (*pyteal.Op attribute*), 116
[Keccak256\(\)](#) (*in module pyteal*), 94
[KeyRegistration](#) (*pyteal.TxnType attribute*), 75

L

[LabelReference](#) (*class in pyteal*), 119
[last_log](#) (*pyteal.TxnField attribute*), 76
[last_log\(\)](#) (*pyteal.TxnObject method*), 81
[last_valid](#) (*pyteal.TxnField attribute*), 76
[last_valid\(\)](#) (*pyteal.TxnObject method*), 81
[latest_timestamp](#) (*pyteal.GlobalField attribute*), 86
[latest_timestamp\(\)](#) (*pyteal.Global class method*), 85
[le](#) (*pyteal.Op attribute*), 116
[Le\(\)](#) (*in module pyteal*), 98
[LeafExpr](#) (*class in pyteal*), 73
[lease](#) (*pyteal.TxnField attribute*), 76

lease() (*pyteal.TxnObject* method), 82
 len (*pyteal.Op* attribute), 116
 Len() (*in module pyteal*), 94
 length() (*pyteal.Array* method), 93
 length() (*pyteal.TxnArray* method), 78
 load (*pyteal.Op* attribute), 116
 load() (*pyteal.ScratchSlot* method), 105
 load() (*pyteal.ScratchVar* method), 107
 loads (*pyteal.Op* attribute), 116
 local_num_byte_slices (*pyteal.TxnField* attribute), 76
 local_num_byte_slices() (*pyteal.TxnObject* method), 82
 local_num_uints (*pyteal.TxnField* attribute), 76
 local_num_uints() (*pyteal.TxnObject* method), 82
 localDel (*pyteal.AppField* attribute), 88
 localDel() (*pyteal.App* class method), 87
 localGet (*pyteal.AppField* attribute), 88
 localGet() (*pyteal.App* class method), 87
 localGetEx (*pyteal.AppField* attribute), 88
 localGetEx() (*pyteal.App* class method), 87
 localNumByteSlice() (*pyteal.AppParam* class method), 89
 localNumUnit() (*pyteal.AppParam* class method), 89
 localPut (*pyteal.AppField* attribute), 88
 localPut() (*pyteal.App* class method), 87
 log (*pyteal.Op* attribute), 116
 Log() (*in module pyteal*), 112
 logic_and (*pyteal.Op* attribute), 116
 logic_not (*pyteal.Op* attribute), 116
 logic_or (*pyteal.Op* attribute), 116
 logic_sig_version (*pyteal.GlobalField* attribute), 86
 logic_sig_version() (*pyteal.Global* class method), 85
 logs (*pyteal.TxnField* attribute), 77
 logs (*pyteal.TxnObject* attribute), 82
 lt (*pyteal.Op* attribute), 116
 Lt() (*in module pyteal*), 98

M

manager() (*pyteal.AssetParam* class method), 90
 max_txn_life (*pyteal.GlobalField* attribute), 86
 max_txn_life() (*pyteal.Global* class method), 85
 MaybeValue (*class in pyteal*), 107
 metadataHash() (*pyteal.AssetParam* class method), 90
 method_signature (*pyteal.Op* attribute), 116
 MethodSignature (*class in pyteal*), 75
 min_balance (*pyteal.GlobalField* attribute), 86
 min_balance (*pyteal.Op* attribute), 116
 min_balance() (*pyteal.Global* class method), 85
 min_txn_fee (*pyteal.GlobalField* attribute), 86

min_txn_fee() (*pyteal.Global* class method), 85
 min_version (*pyteal.Op* attribute), 117
 MinBalance() (*in module pyteal*), 95
 minBalance() (*pyteal.AccountParam* class method), 91
 minus (*pyteal.Op* attribute), 117
 Minus() (*in module pyteal*), 95
 mod (*pyteal.Op* attribute), 117
 Mod() (*in module pyteal*), 96
 Mode (*class in pyteal*), 117
 mode (*pyteal.Op* attribute), 117
 mul (*pyteal.Op* attribute), 117
 Mul() (*in module pyteal*), 96
 MultiValue (*class in pyteal*), 107
 mulw (*pyteal.Op* attribute), 117

N

name() (*pyteal.AssetParam* class method), 90
 name() (*pyteal.SubroutineDefinition* method), 104
 name() (*pyteal.SubroutineFnWrapper* method), 105
 NaryExpr (*class in pyteal*), 100
 neq (*pyteal.Op* attribute), 117
 Neq() (*in module pyteal*), 97
 Next (*pyteal.InnerTxnAction* attribute), 93
 Next() (*pyteal.InnerTxnBuilder* class method), 92
 nextSlotId (*pyteal.ScratchSlot* attribute), 105
 nextSubroutineId (*pyteal.SubroutineDefinition* attribute), 104
 Nonce (*class in pyteal*), 93
 none (*pyteal.TealType* attribute), 120
 nonparticipation (*pyteal.TxnField* attribute), 77
 nonparticipation() (*pyteal.TxnObject* method), 82
 NoOp (*pyteal.OnComplete* attribute), 88
 NormalizeBlocks() (*pyteal.TealBlock* class method), 118
 Not() (*in module pyteal*), 94
 note (*pyteal.TxnField* attribute), 77
 note() (*pyteal.TxnObject* method), 82
 num_accounts (*pyteal.TxnField* attribute), 77
 num_app_args (*pyteal.TxnField* attribute), 77
 num_applications (*pyteal.TxnField* attribute), 77
 num_assets (*pyteal.TxnField* attribute), 77
 num_logs (*pyteal.TxnField* attribute), 77

O

on_completion (*pyteal.TxnField* attribute), 77
 on_completion() (*pyteal.TxnObject* method), 82
 OnComplete (*class in pyteal*), 88
 Op (*class in pyteal*), 113
 opcode_budget (*pyteal.GlobalField* attribute), 86
 opcode_budget() (*pyteal.Global* class method), 85
 optedIn (*pyteal.AppField* attribute), 88
 optedIn() (*pyteal.App* class method), 87

OptIn (*pyteal.OnComplete attribute*), 88
 Or () (*in module pyteal*), 101
 Or () (*pyteal.Expr method*), 73
 outputReducer () (*pyteal.MultiValue method*), 108

P

Payment (*pyteal.TxnType attribute*), 75
 pop (*pyteal.Op attribute*), 117
 Pop () (*in module pyteal*), 95
 pushbytes (*pyteal.Op attribute*), 117
 pushint (*pyteal.Op attribute*), 117
 pyteal (*module*), 73

R

receiver (*pyteal.TxnField attribute*), 77
 receiver () (*pyteal.TxnObject method*), 82
 Reject () (*in module pyteal*), 104
 rekey_to (*pyteal.TxnField attribute*), 77
 rekey_to () (*pyteal.TxnObject method*), 82
 replaceOutgoing () (*pyteal.TealBlock method*), 119
 replaceOutgoing () (*pyteal.TealConditionalBlock method*), 119
 replaceOutgoing () (*pyteal.TealSimpleBlock method*), 119
 reserve () (*pyteal.AssetParam class method*), 91
 resolveSubroutine () (*pyteal.TealComponent method*), 118
 resolveSubroutine () (*pyteal.TealOp method*), 118
 retsub (*pyteal.Op attribute*), 117
 Return (*class in pyteal*), 103
 return_ (*pyteal.Op attribute*), 117
 RFC
 RFC 4648#section-4, 32
 RFC 4648#section-6, 32
 RFC 4648#section-8, 31
 round (*pyteal.GlobalField attribute*), 86
 round () (*pyteal.Global class method*), 85

S

ScratchLoad (*class in pyteal*), 105
 ScratchSlot (*class in pyteal*), 105
 ScratchStackStore (*class in pyteal*), 106
 ScratchStore (*class in pyteal*), 106
 ScratchVar (*class in pyteal*), 106
 select (*pyteal.Op attribute*), 117
 selection_pk (*pyteal.TxnField attribute*), 77
 selection_pk () (*pyteal.TxnObject method*), 82
 sender (*pyteal.TxnField attribute*), 77
 sender () (*pyteal.TxnObject method*), 83
 Seq (*class in pyteal*), 102
 setbit (*pyteal.Op attribute*), 117
 SetBit () (*in module pyteal*), 100
 setbyte (*pyteal.Op attribute*), 117
 SetByte () (*in module pyteal*), 100

setFalseBlock () (*pyteal.TealConditionalBlock method*), 119
 SetField () (*pyteal.InnerTxnBuilder class method*), 92
 SetFields () (*pyteal.InnerTxnBuilder class method*), 92
 setNextBlock () (*pyteal.TealSimpleBlock method*), 119
 setSubroutine () (*pyteal.CompileOptions method*), 120
 setTrueBlock () (*pyteal.TealConditionalBlock method*), 119
 sha256 (*pyteal.Op attribute*), 117
 Sha256 () (*in module pyteal*), 94
 sha512_256 (*pyteal.Op attribute*), 117
 Sha512_256 () (*in module pyteal*), 94
 ShiftLeft () (*in module pyteal*), 97
 ShiftRight () (*in module pyteal*), 97
 shl (*pyteal.Op attribute*), 117
 shr (*pyteal.Op attribute*), 117
 Signature (*pyteal.Mode attribute*), 117
 slotOk (*pyteal.MaybeValue attribute*), 107
 slotValue (*pyteal.MaybeValue attribute*), 107
 sqrt (*pyteal.Op attribute*), 117
 Sqrt () (*in module pyteal*), 95
 state_proof_pk (*pyteal.TxnField attribute*), 77
 state_proof_pk () (*pyteal.TxnObject method*), 83
 storage_type () (*pyteal.ScratchVar method*), 107
 store (*pyteal.Op attribute*), 117
 store () (*pyteal.ScratchSlot method*), 105
 store () (*pyteal.ScratchVar method*), 107
 stores (*pyteal.Op attribute*), 117
 Submit (*pyteal.InnerTxnAction attribute*), 93
 Submit () (*pyteal.InnerTxnBuilder class method*), 92
 Subroutine (*class in pyteal*), 104
 SubroutineCall (*class in pyteal*), 104
 SubroutineDeclaration (*class in pyteal*), 104
 SubroutineDefinition (*class in pyteal*), 104
 SubroutineFnWrapper (*class in pyteal*), 105
 substring (*pyteal.Op attribute*), 117
 Substring () (*in module pyteal*), 99
 substring3 (*pyteal.Op attribute*), 117
 Suffix () (*in module pyteal*), 99
 swap (*pyteal.Op attribute*), 117

T

TealBlock (*class in pyteal*), 118
 TealCompileError, 121
 TealComponent (*class in pyteal*), 117
 TealComponent.Context (*class in pyteal*), 118
 TealComponent.Context.EqualityContext (*class in pyteal*), 118
 TealConditionalBlock (*class in pyteal*), 119
 TealInputError, 120

TealInternalError, 120
 TealLabel (class in pyteal), 118
 TealOp (class in pyteal), 118
 TealSimpleBlock (class in pyteal), 119
 TealType (class in pyteal), 120
 TealTypeError, 120
 Then () (pyteal.If method), 102
 Tmpl (class in pyteal), 93
 total () (pyteal.AssetParam class method), 91
 tx_id (pyteal.TxnField attribute), 77
 tx_id () (pyteal.TxnObject method), 83
 Txn (in module pyteal), 73
 txn (pyteal.Op attribute), 117
 txna (pyteal.Op attribute), 117
 TxnaExpr (class in pyteal), 77
 TxnArray (class in pyteal), 77
 txnas (pyteal.Op attribute), 117
 TxnExpr (class in pyteal), 77
 TxnField (class in pyteal), 75
 TxnGroup (class in pyteal), 84
 TxnObject (class in pyteal), 78
 TxnType (class in pyteal), 75
 type (pyteal.TxnField attribute), 77
 type () (pyteal.TxnObject method), 83
 type_enum (pyteal.TxnField attribute), 77
 type_enum () (pyteal.TxnObject method), 83
 type_of () (pyteal.Addr method), 74
 type_of () (pyteal.App method), 88
 type_of () (pyteal.AppField method), 88
 type_of () (pyteal.Arg method), 75
 type_of () (pyteal.Assert method), 103
 type_of () (pyteal.BinaryExpr method), 95
 type_of () (pyteal.Break method), 113
 type_of () (pyteal.Bytes method), 74
 type_of () (pyteal.Cond method), 102
 type_of () (pyteal.Continue method), 113
 type_of () (pyteal.EnumInt method), 74
 type_of () (pyteal.Err method), 103
 type_of () (pyteal.Expr method), 73
 type_of () (pyteal.For method), 113
 type_of () (pyteal.GeneratedID method), 84
 type_of () (pyteal.Global method), 85
 type_of () (pyteal.GlobalField method), 86
 type_of () (pyteal.If method), 102
 type_of () (pyteal.ImportScratchValue method), 84
 type_of () (pyteal.Int method), 74
 type_of () (pyteal.MethodSignature method), 75
 type_of () (pyteal.MultiValue method), 108
 type_of () (pyteal.NaryExpr method), 100
 type_of () (pyteal.Nonce method), 94
 type_of () (pyteal.Return method), 104
 type_of () (pyteal.ScratchLoad method), 106
 type_of () (pyteal.ScratchStackStore method), 106
 type_of () (pyteal.ScratchStore method), 106

type_of () (pyteal.Seq method), 103
 type_of () (pyteal.SubroutineCall method), 105
 type_of () (pyteal.SubroutineDeclaration method), 104
 type_of () (pyteal.SubroutineFnWrapper method), 105
 type_of () (pyteal.Tmpl method), 93
 type_of () (pyteal.TxnaExpr method), 77
 type_of () (pyteal.TxnExpr method), 77
 type_of () (pyteal.TxnField method), 77
 type_of () (pyteal.UnaryExpr method), 94
 type_of () (pyteal.While method), 112
 type_of () (pyteal.WideRatio method), 101

U

uint64 (pyteal.TealType attribute), 120
 UnaryExpr (class in pyteal), 94
 uncover (pyteal.Op attribute), 117
 unitName () (pyteal.AssetParam class method), 91
 Unknown (pyteal.TxnType attribute), 75
 UpdateApplication (pyteal.OnComplete attribute), 88
 url () (pyteal.AssetParam class method), 91

V

validateSlots () (pyteal.TealBlock method), 119
 validateTree () (pyteal.TealBlock method), 119
 value () (pyteal.MaybeValue method), 107
 vote_first (pyteal.TxnField attribute), 77
 vote_first () (pyteal.TxnObject method), 83
 vote_key_dilution (pyteal.TxnField attribute), 77
 vote_key_dilution () (pyteal.TxnObject method), 83
 vote_last (pyteal.TxnField attribute), 77
 vote_last () (pyteal.TxnObject method), 83
 vote_pk (pyteal.TxnField attribute), 77
 vote_pk () (pyteal.TxnObject method), 83

W

While (class in pyteal), 112
 WideRatio (class in pyteal), 101

X

xfer_asset (pyteal.TxnField attribute), 77
 xfer_asset () (pyteal.TxnObject method), 83

Z

zero_address (pyteal.GlobalField attribute), 86
 zero_address () (pyteal.Global class method), 86